

THE ASSOCIATION OF PROFESSIONAL ENGINEERS OF ALBERTA PERMIT NUMBER P 2 4 5 ELMER W. BROOKER & ASSOCIATES LTD.

#6

MACKENZIE HIGHWAY GEOTECHNICAL EVALUATION VOLUME XVIII DONNELLY RIVER CROSSING MILE 689.7 MACKENZIE HIGHWAY

Submitted To:

GOVERNMENT OF CANADA DEPARTMENT OF PUBLIC WORKS CONTRACT NUMBER A10/73 FILE NUMBER 9305-52-307

AUGUST, 1973

TABLE OF CONTENTS

					PAGE
1.	INTROD	UCTION			1
11.	SITE CONDITIONS				1
	2.1 2.2 2.3	Surface Field D Subsurf	Features and Geology rilling and Laboratory Testing ace Conditions		1 3 5
		2.3.1 2.3.2	Stratigraphy on Centerline - North Valley Wall Stratigraphy on Centerline -		5 7
111.	CONCLU	SIONS AN	D RECOMMENDATIONS		8
	3.1 3.2	 Foundation Types Foundation Design Parameters 			8 8
		3.2.1 3.2.2	Driven Steel H-Piles Prebored Driven Closed End Pipe Piles		8 9
	•	3.2.3	Prebored Driven Timber Piles		10
•	3.3 3.4 3.5	Negativ Frost H Subgrad	e Skin Friction eave of Piles e Considerations on Centerline		12 12 13
		3.5.1 3.5.2 3.5.3	North Valley Wall South Valley Wall Flood Plain Area		13 14 15
	3.6	Fill Placement			16
	3.7	7 Slope Stability Considerations			17
		3.7.1 3.7.2 3.7.3	North Valley Wall South Valley Wall General		17 18 19
	3.8 3.9 3.10	Drainag Cement Additio	e Considerations Type and Corrosion Considerations nal Studies		19 20 21

IV. LIMITATIONS

List of References

- APPENDICES
- Appendix A

Dwg. No. A-1 Key Plan Dwg. No. A-2 -Site & Borehole Location Plan Dwg. No. A-2a -General Terrain Legend Dwg. No. A-3 Plates 1 to 3 Dwg. No. A-4 Plates 4 to 6 Dwg. No. A-5 -Centerline Profile & Stratigraphy -----Dwg. No. A-6 Cross-Sections & Stratigraphy

Appendix B

Borehole Logs

Appendix C

Dwgs. No. C1 to C6 Dwg. No. C7 689-C-1 to 3, Inclusive 689-S-1 to 17, Inclusive

Grain Size Distribution Curves Summary of Results 21

I. INTRODUCTION

In conjunction with a geotechnical engineering study carried out from Mile 725 to Mile 632 of the proposed Mackenzie Highway, a number of bridge sites at major river and stream crossings were investigated. The Donnelly River Crossing, is one such site investigated in detail. Details of the investigation, together with geotechnical data and recommendations pertinent to bridge construction at the river crossing, are reported herein.

This work was carried out for the Government of Canada, Department of Public Works, and was authorized by Contract Number A10/73, File No. 9305-52-307,

II. SITE CONDITIONS

2.1 Surface Features and Geology

The proposed river crossing is approximately 1000 feet downstream of where the Donnelly River exits from Chick Lake and is at approximately Mile 689.7 of the proposed Mackenzie Highway. The approximate geographic location of the crossing is shown on the Key Plan, Drawing No. A-1, Appendix A, and the crossing site is shown on the Site Plan, Drawing No. A-2, Appendix A. Plates 1, 2, and 3, Drawing No. A-3, and Plate 5, Drawing No. A-4, Appendix A are low angle oblique photographs of the crossing area.

The valley of the Donnelly River has been formed in and is controlled by the local bedrock, which consists of Cretaceous (1)* silty clay shale. Except for the crossing area, the valley walls are relatively

* Numbers in parenthesis refer to List of References presented at the end of this report.

steep and the river channel is well defined. Very steep slope sections occur adjacent to meander bends where active erosion of the toe of most slopes is presently occurring. In some of these meander bends recent slide activity is apparent. A typical slide area, is located just downstream of the crossing site, as shown on Drawing No. A-2, and in Plates No. 2 and 3, Drawing No. A-3, Appendix A. Drawing No. A-2, Appendix A, shows the approximate extent of the flood plain which has developed primarily on the north bank of the present channel in the area proposed for the crossing.

Slope gradients of both north and south valley walls are relatively gentle in this area, with a maximum slope angle of about 11 degrees existing over approximately the upper third of the south valley wall. The overall slope angles of north and south valley walls are about 2 and 5 degrees, respectively. Plates 4 and 6, Drawing No. A-4, Appendix A, show morth and south valley walls, respectively, at the crossing site.

An aerial photographic interpretation of the surficial geology, of the immediate area of the Donnelly River crossing, is shown in Drawing No. A-2, Appendix A. The surficial deposits are believed to be primarily glacial lake basin sediments that have been reworked to some degree by slope wash action (GLB-1-(SL)) (2). A terrain legend, which describes the symbols used in the terrain analysis, is presented as Drawing No. A-2a, Appendix A. The soils consist of glaciolacustrine silty clays and clayey silts. This type of deposit has been confirmed, by subsurface borings, to be generally present both north and south of the Donnelly River. However, some of the borings revealed that glacial deposits, which have been classified as ground moraine with a shallow peat covering (GM(PT)), exist on the north bank of the Donnelly River in close proximity to the crossing. In this area the lacustrine clays appear to be absent. In addition, an area of near surface bedrock with thin drift covering (BR(Df)) is present a short distance to the west of the crossing. Silt, sand and gravel was noted in the flood plain area, within the present river valley.

Tree cover at the crossing consists primarily of sparse to medium dense black spruce. Some deciduous trees, such as poplar and willow are present along the Donnelly River channel, Chick Lake shoreline, and high ground areas adjacent to the river crossing site. Surficial drainage of the

area is generally well developed toward the Donnelly River and Chick Lake.

2.2 Field Drilling and Laboratory Testing

Evaluation of subsurface conditions was based on field data obtained from 20 boreholes, drilled at the locations shown on Drawing No. A-2, Appendix A. Of the 20 boreholes drilled, 3 were centerline boreholes, drilled in conjunction with the general route evaluation, and the remainder were located and drilled specifically to define subsurface conditions at the crossing.

The centerline boreholes were designated Boreholes 689-C-1 to 689-C-3, inclusive, and the special boreholes consisted of Boreholes 689-S-1 to 689-S-17, inclusive. Detailed borehole logs are presented in consecutive order in Appendix B.

With the exception of Boreholes 689-C-1 and 689-C-2, all holes were drilled with a track mounted Mayhew 500 rotary drill rig, using a continuous air return circulation system. Boreholes 689-C-1 and 689-C-2, were dry augered, utilizing a track mounted, Texoma Super Economatic power auger. Boreholes advanced with the rotary drill rig generally averaged about 4-3/4 inches in diameter, while the augered holes averaged about 12 inches in diameter. Borehole penetration ranged from 5 feet to 88 feet, and averaged 34 feet in depth. Sampling consisted of representative bag samples, obtained generally at depths of $2\frac{1}{2}$, 5, 10 and 18 feet below ground surface in the shallow holes; and at depth intervals of 5 feet, after a depth of 10 feet below ground

surface in the deep boreholes. Undisturbed samples were not obtained, other than a few fragmented core samples of silt, which is believed to be a weathered shale material. These cores were taken from two boreholes (Boreholes 689-S-6 and 689-S-8).

Laboratory testing was carried out on the disturbed soil samples to determine the natural water content profile, Atterberg limits, grain size distribution, soluble sulphate concentration, and pH range of the subsoil. The moisture content tests were undertaken in the field laboratory of Elmer W. Brooker and Associates Ltd. (EBA), while all other testing was confined to the EBA Edmonton laboratory. In addition to the laboratory testing outlined above, all samples were visually classified in both the EBA field and Edmonton laboratories. Soil classification was based on plasticity according to the extended Unified Classification System (3) and on textural classification according to U.S. Engineers Department (4) textural classification triangle. Frozen ground was classified according to a modification of the NRC system for describing permafrost (5). The modification consisted of dropping the modifying symbol describing the form of excess ice. This was necessary because the disturbed nature of the samples obtained from both rigs prevented accurate description of the form of the excess ice. The system used retains the symbols V and N for visible and non-visible ice, respectively, and the modifying symbols B and F for well bonded and poorly bonded non-visible ice, respectively. Excess ice quantities were estimated from visual observation, and based on previous experience are believed to be relatively accurate. The results of laboratory tests are presented on the borehole logs (Appendix B), where applicable, and on grain size distribution curves, Drawings No. C-1 to C-6, inclusive, Appendix C. Drawing No. C-7, Appendix C, presents a summary of laboratory results.

2.3 Subsurface Conditions

Based on observations from the boreholes, inferred stratigraphic sections have been compiled and are presented as Drawings No. A-4 and A-5, Appendix A. The generalized centerline stratigraphy noted at the site is summarized in the following Sub-Sections.

2.3.1 Stratigraphy on Centerline - North Valley Wall

Material	Description	Approximate Average Depth Below Existing Grade (FT)	Approximate Range of Thickness (FT)
ORGANIC SILT, ORGANIC CLAY, PEAT,	 black to dark brown, organic, fibrous, clayey and silty, V - (5% to 15%), moisture content (M.C.) avg. 	0 - 3.2	0.5 - 7.0
CLAY OR SILT (TILL)	<pre>= 85% - medium to dark browr silty or clayey, sandy and gravelly, low plastic, V - (0 to 10%), M.C. (avg.) = 35%</pre>	n, 3.2 - 9.0	4.0 - 6.0
SILT (WEATHERED SHALE)	<pre>- grey, clayey, shale fragments, soft, lov to medium plastic, NB, M.C(avg.) = 14%</pre>	9.0 - 21.6	10 - 17
SHALE	<pre>- grey, clayey silt to silty clay shale, weathered, soft, low to medium plastic, NB, M.C. (avg.) = 9.7%</pre>	o 21.6 - Depth of Penetration	Not Established

E~517

Page 6

The following additional information, which may influence design or construction decisions, was also obtained during the investigation at the subject site.

> The maximum depth of borehole penetration was 88 feet.

2. A grey silty clay layer was encountered in Boreholes 689-S-5 and 689-S-1, beneath the organic layer, and overlying the silt (weathered shale) and shale, respectively. The clay layer averaged 4.75 feet in thickness and exhibited excess ice contents estimated up to 30 percent (NB to V). The moisture content of the clay stratum averaged 27.3 percent. At the location of Boreholes 689-S-5 and 689-S-1, the shale was noted at depths of 8.5 feet and 12.5 feet, respectively.

3.

Due to a lack of downhole temperature measuring equipment and the absence of visible ice at depths greater than an average of about 6 feet in the boreholes, it was difficult to accurately determine to what depth permafrost extended in the borings. However, it is believed that all borings encountered frozen material to the maximum depth of penetration and that NB is the correct ice classification for the silt (weathered shale) and shale strata.

4.

Borehole 689-S-1 was the only borehole in which an unfrozen zone could be positively identified. This zone was noted at a depth of about 8 feet, where free water was noted to be entering the borehole.

2.3.2 Stratigraphy on Centerline - South Valley Wall

	Material Description	Approximate Average Depth Below Existing Grade (FT)	Approximate Range of Thickness (FT)
PEAT	 dark brown to black, clayey, silty, organic, fibrous, V-(15% - 20%), M.C. (avg.) 53% 	0 - 2.7	1.0 - 4.0
CLAY	<pre>- medium brown to grey, silty, some sand, low plastic, V- (10% - 15%) to NB, M.C. (avg.) = 31.9%</pre>	2.7 - 14	4 - 14.0
SHALE	<pre>- grey, clay-silt shale, some sand, weathered, soft, low plasticity, NB, M.C. (avg.) = 10.6%</pre>	14 - Depth of Penetration	Not Established

The following additional information, which may influence design or construction decisions, was also obtained during the field investigation.

- The maximum depth of borehole penetration was 38 feet.
- A medium brown to grey, silty, fine grained sand layer, was noted in Boreholes 689-S-2 and 689-S-12, overlying the shale stratum.

 All boreholes are believed to have encountered frozen material to the maximum depth of penetration.

111. CONCLUSIONS AND RECOMMENDATIONS

3.1 Foundation Types

The following foundation types are believed to be feasible for founding a bridge structure at the subject site. At present, preference has not been given to any of the types listed, as final selection of a foundation system should be determined in conjunction with economic and structural design considerations.

1.	Driven	'H' Piles.	
2.	Closed	End Pipe Piles Driven in Prebored Hol	les
3:	Timber	Piles Driven in Prebored Holes.	

3.2 Foundation Design Parameters

The recommended foundation types listed in Subsection 3.1, may be designed in accordance with the following parameters.

3.2.1 Driven Steel H-Piles

The design of steel H-piles is dependent upon the type of support that is provided the pile in or on the bearing material. In the case of the Donnelly River bridge crossing, it is considered that the shale bedrock material provides the only suitable bearing support for foundation elements. However, as the insitu density or consistency of the shale has not been precisely established; nor have the thermal conditions of the shale been accurately determined, only tentative pile designs or driving criteria can be provided at this time.

As a guide to the establishment of a pile design, it is recommended that standard H-piles 50 feet in length, with a minimum nominal size of 12 inches by 12 inches, and a minimum weight of 53 pounds per foot (12BP53), be considered for preliminary design purposes. It is believed that the suggested pile section can be driven, with an energy of 24,000 foot pounds, to a set of 1 inch per blow, measured over the last foot of driving. It is believed that piles driven to these specifications will permit an allowable static design load of 70 kips to be used. Although preboring is not considered necessary for the installation of steel H-piles in frozen ground, at this site, it may be desirable in very hard seasonally frozen ground to ensure the alignment of the driven pile section. This will be particularly true if very long sections are to be driven.

It is essential that the fill be placed to final grade before the piles are driven or pre-bored in order to prevent damage to the pile and to ensure proper compaction of the fill, which will limit negative skin friction loads on the pile. On site inspection and supervision of the driving of test piles or the initial piles of the foundation system is considered absolutely necessary in order to establish the final design bearing capacity. It is also considered essential that a pile driving record be maintained for all piles. The driving record of all piles should be reviewed as is practical, by the geotechnical consultant, to ensure the design intention has been realized.

3.2.2 Prebored Driven Closed End Pipe Piles

As in the case of steel H-piles, pipe pile design is based on the means of support achieved. Preboring of closed end pipe piles, driven into the shale stratum, is considered necessary to facilitate the driving operation and maintain alignment of the piles. The prebored hole size should be 85 to 90 percent of the outside pile diameter to ensure a 'snug' fit, and should extend the full length of the intended pile penetration. It is essential that the fill be placed to final grade before the piles are

driven or pre-bored in order to prevent damage to the pile and ensure proper compaction of the fill, which will limit negative skin friction loads on the pile.

For preliminary design purposes, it is recommended that closed end pipe piles with a minimum length of 50 feet, a minimum nominal diameter of 10 inches, and a minimum weight of 40 pounds per foot be considered. It is believed that the suggested pile section can be driven, with an energy of 24,000 foot pounds, to a set of 1 inch per blow, measured over the last foot of driving. It is believed that piles driven to these specifications will permit an allowable static design load of 60 kips to be used. Driven piles must penetrate to at least the full pre-bored depth. As for steel H-piles, inspection of the driving of test piles, or the first few piles of the foundation system is considered absolutely necessary to confirm or alter the design bearing capacity recommended herein. A pile driving record must be kept for all piles for immediate review by the geotechnical consultant.

3.2.3 Prebored Driven Timber Piles

For preliminary design purposes, it is recommended that Number 12 Douglas Fir timber piles, with a minimum length of 50 feet, be considered for foundation support. The piles should be pressure treated with creosote and should have a minimum creosote retention of 12 pounds per cubic foot.

It is essential that the fill be placed to final grade before the piles are driven or pre-bored to prevent damage to the pile and to ensure proper compaction of the fill, which will limit negative skin friction loads on the pile. Preboring into the shale stratum, is considered essential to limit pile damage in frozen ground. Prebored holes should have a maximum diameter equivalent to the pile tip diameter to permit a snug fit, and should extend for the full depth of anticipated pile penetration. If excessive driving resistance is encountered, overboring of approximately the upper half section of the hole may be required. Details of the overbore should be determined in the field, on the basis of driving records obtained from test piles.

As the pile capacity will depend on the preboring and overboring of the pile holes, which remains to be proven in the field, the set to which the piles can be driven cannot be predicted. However, if the suggested pile section can be driven, with an energy of 24,000 foot pounds, to a set of 1 inch per blow, measured over the last foot of driving; it is believed that an allowable static design load of 40 kips may be used. Piles must penetrate to at least the full prebored depth.

If timber piles cannot be driven to the foregoing specifications, their design bearing capacity must be determined on the basis of field driving records or load tests. Field inspection by qualified personnel is considered necessary during the preboring, overboring and driving of test piles or the first few foundation piles, to establish or alter the preliminary design capacity and method of installation recommended herein. A driving record should be kept, for all piles installed, for immediate review by the geotechnical consultant.

3.3 Negative Skin Friction

The effect of negative skin friction, on individual piles and pile groups, will be dependent upon the occurrence and magnitude of settlement within both the fill surrounding the piles and the natural subgrade materials. At the crossing site, it is considered that all subgrade materials, with

the exception of the silt (weathered shale) and shale strata are thaw unstable and significant subsidence can be expected if thawing occurs. Consequently, significant negative skin friction effects can be anticipated in these materials if thawing is allowed. Substantial negative skin friction effects will also be mobilized in any road grade fill

surrounding piles, if loss of subgrade support occurs.

As it is extremely difficult to accurately predict the anticipated total magnitude of negative skin friction loads, on any pile or pile group that may be installed at the subject site, no allowance has been made for skin friction in the design pile capacities quoted in Subsection 3.2 of this report. However, Table 3.3.1 is presented as an aid to the design of pile foundation systems at the site. As is evident from the borehole logs, soils in the vicinity of probable pile installations fall in the CL to Cl category. Therefore a negative skin friction value of 800 pounds per square foot for the subgrade soils at the site, is believed to be maximum negative skin friction value applicable to pile design. It is believed that the maximum load attributable to skin friction can be obtained by assuming that the entire depth of thaw sensitive material plus the depth of granular fill at the pile locations will contribute to negative skin friction.

3.4 Frost Heave of Piles

Frost heaving of piles can occur as the active layer freezes each winter. During the cold winter months the surface soils freeze and bond to the pile at low temperatures. Ice segregation in soils containing silt and clay causes a heaving force on the pile which must be resisted by the

TABLE 3.3.1

-NEGATIVE SKIN FRICTION OF UNFROZEN SOIL FOR PILE DESIGN (AFTER WOODWARD LUNDGREN AND ASSOCIATES, 1971) (6)

DESCRIPTION OF SOIL CATEGORIES

DESIGN NEGATIVE SKIN FRICTION

Clean sands and gravels with little or no silt or clay. Typically: GW, $P_{e} = 30d (X^{2} + 2HX)^{*}$ GP, SW, SP Silty or clayey sand and gravel mixtures with considerable amounts of silt and clay. Typically: GM, SM, GC, SC, SF 700 PSF Moderately plastic to highly plastic inorganic clays. Typically: CL, CH 800 PSF Non-plastic to slightly plastic inorganic silts and lean clays. 350 PSF Typically: ML, MH Organic silts and clays. Typically: OL, OH 150 PSF

Load developed on that portion of a pile embedded in a granular stratum.

Load developed, lbs. Ρ = dS

Н

Х

- = Diameter of pile, ft.
 - = Depth of overburden to top of granular stratum ft.
 - Length of pile embedded in granular stratum, ft. -

<u>.</u>....

available adfreeze bond in the permafrost or the skin friction in unfrozen soils which the piles may be imbedded in.

The design of a pile in permafrost is often controlled by the embedment required to resist the heave stress. In general it has been found that a slightly deeper pile embedment is the cheapest means of overcoming undesireable frost heaving stresses. Increasing the pile length will only be necessary, however, if the pile loads will be less than the frost heave force anticipated. Suggested design adfreeze bond stresses for general permafrost soils are presented in Table 3.4.1. These design stresses may be used in conjunction with an assumed or measured frost penetration depth to determine the frost heave force.

3.5 Subgrade Considerations on Centerline

3.5.1 North Valley Wall

As indicated in Subsection 2.1, the subsurface borings generally revealed a succession of peaty organic topsoil, underlain by a silt or clay till, a layer of silt or weathered shale, and shale bedrock to the depth of borehole penetration. Visual observations revealed that generally only the organic and till strata possessed visible excess ice (V) but that all strata appeared to be frozen.

Although no shear strength data for thawed or frozen soil at the site is available, qualitative evaluation of the shear strength of the various strata can be made, based on visual observations, ice content estimates, moisture content profiles and classification test results. Based on these factors, it is concluded that low shear strengths can be expected for the organic and till strata if these materials were

TABLE 3.4.1

FROZEN SOIL ADFREEZE BOND STRENGTH FOR PILE DESIGN (AFTER WOODWARD LUNDGREN AND ASSOCIATES, 1971) (6)

APPLICABLE CRITERIA

. ..

DESIGN ADFREEZE BOND STRESS, PSF

DES	IGN CATEGORY	SEGREGATED ICE CONDITION	WATER Content of Soil, %	FROST ¹ HEAVING SOILS
1	-Above Average Soil-ice	No Visible Ice,	< 15	5000
	Condition	1%	15-40	4000
ņ	~Average	Little Visible	< 15	4000
	Condition	1-10%	15-40	2000
	-Below	Occasional	<15	2000
	Average Soil-ice Condition	Visible Ice, 11-20%	15-40	
			>40	1350
IV	-Poor Soil-ice	Some Visible	15-40	1350
	Condition	21-35%	> 40	900
v	-Very Poor	Considerable	A	700
	Condition	ice,>35%	АПУ	700

1. Applies only for soils containing 5% or more of silt or clay size particles.

allowed to thaw. Consequently, these materials will provide poor subgrade support in a thawed condition. The silt (weathered shale) and shale possess lower moisture contents and substantially greater shear strength in a thawed condition.

To accurately predict settlement of fill placed on permafrost soils containing excess ice_detailed knowledge of ground ice distribution together with an assessment of the thermal disturbance caused by fill placement are required. Therefore, only qualitative estimates of thaw settlement can be made at this time. Based on visual estimates of excess ice content, it is believed that total thaw settlement of about 15 and 10 percent of the original thickness of the strata, can be expected in the organic and till layers, respectively. This estimate assumes complete thawing of the strata, but does not take into account normal consolidation settlement of the unfrozen material under the influence of the surcharge load of road fills. In the case of peat soils, normal consolidation settlement can easily reach 50 percent of the original thickness of the deposit; and can, as with the thaw settlement, occur fairly rapidly. Normal consolidation settlement of the till would be much less and would likely be in the order of 1 or 2 percent of the thickness of the strata, under the influence of the surcharge load. Consolidation of the underlying silt (weathered shale) and shale strata, due to thaw subsidence and normal consolidation under loading, is anticipated to be much less significant, except where visible excess ice may occur.

3.5.2 South Valley Wall

The succession of strata on the south valley wall, consisted of peat or organic topsoil, clay and shale. Generally, the noted ice contents and moisture profiles indicate that the near surface subgrade soils on the south valley wall are slightly more stable than on the north wall. However, as on the north wall, the high excess ice and moisture contents infer low shear strength for the peat and clay strata when these materials thaw. The shale stratum, existing in the south valley wall, has the same characteristics as that present in the north wall. The silt (weathered shale) stratum, which was noted on the north valley wall, appears to be absent on the south wall, with the more resistant shale being present directly beneath the clay stratum. However, the clay stratum has properties very much similar to the silt (weathered shale) and may in fact be the same stratum, but with a higher average moisture content.

Qualitative estimates of thaw subsidence, assuming the entire strata thaw, are about 15 and 10 percent of the peat and clay strata thicknesses respectively. The subsidence potential on the south valley wall is considered to be of the same magnitude as on the north wall.

3.5.3 Flood Plain Area

The river flood plain area is outlined on Drawing No. A-2, Appendix A. On the north side of the river, organic silt and clay overlie clay and silt (weathered shale) or shale. On the south side of the river peat overlies clay, silty sand and shale. The excess ice content and moisture content of the peat and organic layers are fairly erratic. The ice classification varies from non visible well bonded (NB) to visible (V, 5 to 10 percent). The average moisture content is approximately 80 percent. Ice distribution within the clay is also varied and ranges from non visible, well bonded (NB) to visible (V, 25 to 30 percent). The moisture content of the clay is about 30 percent. Some silty sand was observed to overlie the shale in the south river bank, adjacent to the river edge. This sand stratum possessed low ice contents which generally ranged from non-visible, well bonded (NB) to visible (V, 0 to 5 percent). Moisture contents were high and ranged from 20 to 40 percent. The remaining underlying strata (silt and shale) were similar to that encountered beneath both valley walls. Some seepage water was, however, noted at a depth of 8 feet within the silt (weathered shale) stratum, at the location of Borehole 689-S-1. It was also observed, within this borehole, that the moisture content of the shale was higher than in the other boreholes, for a depth extending to about 35 feet below ground surface. However, it is believed that the higher moisture content is not representative and is due to sample contamination from free seepage water from above.

Based on the foregoing observations it is concluded that subgrade support within the flood plain area is essentially the same as that found further upslope. Ice contents and moisture contents are similar and thaw subsidence of the same magnitude is anticipated.

3.6 Fill Placement

It is considered that the conventional northern construction practice of placing fill material directly on the organic subgrade is desirable at this site. Fills for bridge approaches should be constructed with allowance being made for the occurrence of thaw subsidence, if sufficient thickness of fill is not placed to preserve the frozen material. Allowance for expected subsidence can be made by either providing extra fill to compensate for the anticipated settlement or to upgrade as subsidence occurs, or both. A thickness of dry granular fill material (gravel or quarried rock) of about 4 to 5 feet is considered to be the minimum recommended for road grade construction on underlying frozen subgrade materials. Local fine grained materials such as silts and clays are not considered suitable for abutment or approach fills. The thickness of road grade material required to prevent degradation of the permafrost can only be predicted after detailed theoretical analyses, which are considered to be beyond the scope of this investigation. It is believed that fill placement should be carried out during the late winter period to minimize thermal disturbance, and possible detrimental effects on the existing slopes, occassioned by the construction equipment. The fill should be placed before preboring of piles. Placement of fills on layers of snow, either on the existing subgrade or on subsequent layers of the grade is not recommended. Snow clearing should be carried out prior to fill placement. Placement of the fill should be carried out through end dumping with subsequent spreading by dozing equipment. Minimum initial lift thicknesses of 2 feet are suggested. Depending on construction completion schedules, construction of fills may be staged for several seasons or carried to completion as construction progresses.

3.7 Slope Stability Considerations

3.7.1 North Valley Wall

No evidence of recent slope instability was detected on the north valley wall, in the immediate vicinity of the proposed river crossing and approach fills. Based on available survey information, plotted on Drawing No. A-5, Appendix A, the slope gradient along centerline averages about 2 degrees (about 3.5 percent). Rudimentary slope stability calculations, using assumed shear strength values for thawed materials and the known slope configuration, revealed adequate factors of safety with respect to sliding. Consequently, it is considered that approaches can be constructed on the north side of the river, on the proposed alignment, in comparative safety with respect to slope instability. However, it is recommended that excessive fill thicknesses be avoided near the crest of the slope. In addition, cutting or excavating of slope material is not recommended and desired grades should be achieved solely through placement of fill. Placement of fill directly on underlying organic layers should be carried out, and the underlying organic layers should be disturbed as little as possible.

3.7.2 South Valley Wall_

Evidence of recent slope instability has been observed on the south valley wall adjacent to the proposed crossing of the Donnelly River channel. Drawing No. A-2, and Plates No. 2 and 3, Drawing No. A-3, Appendix A, show a recent slide that has occurred 200 to 300 feet downstream of the proposed bridge crossing. It appears, from visual observations, that this is a shallow slide, concentrated in surficial materials. Other shallow seated slides further downstream, have been detected through aerial photographic interpretation. These slides, including the one near the Donnelly River crossing, generally occur at meander bends where river flow results in active toe erosion of the slope. Another common feature of the slides is their occurrence on steep slopes, estimated to be in the order of 20 to 30 degrees.

For purposes of slope stability calculations, assumed strength parameters for thawed soils were used in conjunction with the slope profile determined from survey information. The maximum slope angle on the south valley wall appears to be about 11 degrees. This slope gradient extends over a section of the slope, approximately from Borehole 689-S-3 to a point between Boreholes 689-S-14 and 689-C-3, as shown on Drawing No. A-5, Appendix A. The average overall slope of the south valley wall is about 5 degrees.

Using the foregoing slope data and assumed soil strength parameters, it was determined that adequate factors of safety exist for this slope gradient, assuming a shallow failure surface. Factors of safety for deep seated movements within the shale are expected to be even greater.

3.7.3 <u>General</u>

Based on observations of local failures, and rudimentary slope stability calculations, using assumed strength parameters for thawed soils, it is considered that the slopes on centerline are presently stable, and that an approach road grade may be constructed upon them. However, it is recommended that large fills be limited to lower slope sections, where they will act as a toe load and assist in maintaining slope stability. Cutting of slope material is not recommended. Placement of fill directly on the organic surface material is advocated.

Observations of vegation cover, adjacent to the channel banks at the crossing, reveal that some slumping of channel banks likely occurs under the influence of channel erosion. Consequently, it is considered that rip-rap protection of the existing defined channel, upstream and downstream of the bridge crossing, may be necessary to protect the overall stability of the crossing site. Bridge abutments should be set as far back from the channel banks as is practicable.

3.8 Drainage Considerations

As approach fills will concentrate runoff water on slope, along the upslope sides of the fills, it is considered essential that considerable effort and care be given to minimizing erosion on the slope parallel to the fill. Every effort should be made to preserve the vegetal lining of all natural water courses. However, where this is impossible, coarse gravel should be used as channel lining. Transverse flow breakers at frequent intervals may be required to reduce the flow velocities along the fill and thereby reduce the potential for erosion by running water. Spacing of the flow breakers will become apparent in the field when drainage courses and gradients become accurately defined. Ponding of water adjacent to fills should be

discouraged as ponded water will act as a heat source for rapid degradation of permafrost. It will also tend to reduce the shear strength of the adjacent subgrade soil and road grade fill, unless the road grade is a very competent granular material.

3.9 Cement Type and Corrosion Considerations

Two representative soil samples were tested to determine their soluble sulphate concentration and general range of acidity. The soluble sulphate concentrations determined from the tests, ranged from negligible to severe (0.52%) and the pH of the samples was found to be about 6.5, which indicates slight acidity.

Although these results are inconclusive, it is recommended that Type V Sulphate Resistant Cement be used for all concrete in contact with the subsoil. A minimum 28 day compressive strength of 3000 pounds per square inch is recommended for all concrete forming foundation elements.

In view of the low acidity of the subsoil, it is considered that corrosion of steel piles embedded within the soil, will not be greater than normal. Consequently, special protective measures are not believed necessary. For piles extending above grade or above water level, corrosion protection may be achieved by painting or encasement with concrete. In this case, the protective coating should extend to a minimum distance of 2 feet below final grade or minimum anticipated low water level, whichever is deeper. In the case of pipe piles protective coating should be provided on the interior of the pipes to prevent possible corrosion. If practical, this may also be achieved through filling of the piles with concrete.

3.10 Additional Studies

In order to more accurately assess such factors as insitu shear strength, thaw subsidence, and slope stability, it would be desirable to obtain additional detailed geotechnical information at the site. Such items as acquisition of representative undisturbed samples of the various soil types, a thorough study of existing stable and failed slopes, refined field and laboratory tests to determine shear strength and thaw subsidence factors, and a refined theoretical analysis of these factors, constitute the additional detailed geotechnical information that is considered to be desirable. It is believed that most of this information could be readily acquired during the summer season, and it is recommended that consideration be given to the acquisition of some of this information.

In addition to the desirability of obtaining further detailed geotechnical information, it is recommended that consideration be given to establishment of a series of closely supervised and documented pile driving and pile load tests. Although desirable, these tests need not be carried out at actual bridge crossing sites, but may be carried out in areas where materials and conditions would be representative of general foundation conditions at most of the proposed bridge sites. Such tests would provide invaluable design data on which future designs of pile foundation systems could be established.

IV. LIMITATIONS

The foregoing recommendations have been prepared based on our knowledge of existing conditions along the Donnelly River Valley, at the proposed highway crossing. This knowledge has been derived from visual, physical and analytical considerations of existing soil and slope conditions, which were obtained from our field investigation. The findings and comments presented are believed to accurately reflect conditions as they are known to exist.

However, due to the general nature of the study, the findings cannot be considered to be a comprehensive assessment of slope and foundation conditions at the crossing. Should conditions be encountered, other than described herein, the geotechnical consultant should be contacted so that recommendations may be evaluated in light of new findings.

Respectfully Submitted,

ELMER W. BROOKER & ASSOCIATES LTD. ENG Lawrence A. Balanko, P. Eng. FESSION brið **΄**ω· Garry R. Gilchrist, P. Eng. ß LAB: 1mh

E.W.Brooker & Associates Ltd.

LIST OF REFERENCES

- Hume G.S., 1954. The Lower Mackenzie River Area, Northwest Territories and Yukon: Geological Survey of Canada, Memoir 273.
- Canadian Arctic Gas Study Limited, Gas Pipeline Route Alignment and Terrain Data, prepared by J.D. Mollard and Associates Ltd. (unpublished)
- Yong, R.N. and Warkentin, B.P., 1966, Introduction to Soil Behavior, The MacMillan Company, New York.
- Means, R.E. and Parcher, J.V., 1963, Physical Properties of Soils, Charles E. Merril Books Inc., Columbus Ohio.
- Pihlainen, J.A., and Johnston, G.H., 1963, Guide to a Field Description of Permafrost, N.R.C. Technical Memorandum 79.
- Woodward Lundgren & Associates, 1971. Results of Pile and Anchor Installation and Load Tests, and Recommended Design Procedures. Trans Alaska Pipeline System, (unpublished).

E.W.Brooker & Associates Ltd.







PLATE No. 1

North easterly view of Donnelly River Crossing & Chick Lake (February, 1973)

PLATE No. 2

Southwesterly view of Donnelly River Crossing NOTE SLIDE AREA (February, 1973)

PLATE No. 3

Close up view of Donnelly River Crossing NOTE SLIDE AREA. (Late September 1972)

Drawing No. A-3

E.W. Brooker & Associates Ltd.



PLATE No. 4

Donnelly River Crossing North approach. Plate taken approximately 15 feet north of the river. (June, 1973)

PLATE No. 5

Donnelly River Crossing North is to the bottom left. (June, 1973)

PLATE No. 6

Donnelly River Crossing View from north side towards the south approach. (June, 1973)

Drawing A-4 E.W.Brooker & Associates Ltd.




	E. W	I. B	RO	OK	ER	8	AS	soc	TAI	ES	LT	D.	DRILL	но	LE	R	EP	ORI	<u>-</u>			DE	PA	RTI		OF CKE	PU NZ	BLI E		VOF	RKS	, CAN	ADA	283
DWI	N BL		FIEL	DEN	IG:	LAB	DAT	TE DR	ILLED	60/1	/73 AI	PHOT	TO NO: A-227	74-8	61	Сн	AINAG	6E [8	136	+ 36					OFF	SET						TEST	HOLE	
СКС		<u>M</u>	TEC	;н: 11	· .	НС	RIG) Tex	<u>coma</u>		SU	RFACE	DRAINAGE:	<u>Very</u>	<u>, G</u>	ood	Sout	hVEG	ETA	TION	Ble	ack	Spru	ice [Dense]	0'-1	DELE				·			T
			2	Z	ğ							DNDO	ICE					~~~~		101				u z)		ANA	LYSI	S	1	11	Ł	MILE	B,C,S	NUMBER
PTH (133	200	سرب	COVE	TANC	USI SYME	\$0	1 1	DESCF	RIPTIC)N		N S O	DESCRIPTION	PTH (13		(= WA ∖= ICE	E COI		en i t (9	(%) 6 OF	SAM	IPLE	VOL	UME	}	LAY	LT	AND	AVEL	DENS C.F.)	DENS C.F.)	689	С	T
185	SAM	SAMP TYP	RE	ENET	OF N							MITS		25			ρ	LASTI	c				D			0	s V	's	5	VET (P	Υ ^R	F	FMARK!	
	<u> </u>	ļ	 [≫]	ē œ	69							13 2					20	4	0		<u> </u>		<u></u>	100	0 100-	× %	<i>%</i>	%	%	-	-			
					n T	PEA	Γ	÷		1	1				┝		<u> </u>									-								
2	1		ļ		۲۱		-	Org	janic	, BI	ack			2	ļ			-								4								
	 '	\vdash				CLAN	,					- F .	v		┝		ß						-4			-								
4		L			CL to) -	Roc	:kv.	Silty	. Dar	k	20-25%	4	⊢						\sim	$ \rightarrow$	-+			-								
	2	\geq			с⊢		,	Bro	wn,	Low	to j			4	┝			ø								-								
6	-							Me	dium	Plas	tic //			6	_											-				ŀ				
i i						ENID	05	чO	۱ ۳ Թ) 51		der			 			-								-								
8	ł					EIND	Or	nOi	16 @	5		YCK	.p	8	_	-	<u> </u>									4								
															 											-								
10														10	_											4	1							
													r r r			-	+																	•
12														12	┢		ļ									-								
		ł											1				1							\rightarrow		4								
14														14	 											4								
															<u> </u>					<u> </u>					·····	4			1			•		
16														16	L									_		4			ļ					
													ļ			4_	_		 	ļ						-								
18														18	 			_								_	1					1		
			l													_		<u> </u>	L.		 					4	1							
20														20	L_	_	ļ		ļ		 	↓				-								
																	<u> </u>	_	ļ	 	 	↓				-	ł					1		
22				1										22	_			_	ļ	 	ļ					_			1		1			
														1					ļ		ļ									1				
24														24			<u> </u>	1			ļ					4								
		1																									<u> </u>	1		1		<u> </u>		

÷

E	. W	<i>I</i> . В	RO	OK	ER	8 A	SSOCIATES	S LTI).	DRILL	но	LE	REP	ORT			[DEPA	ARTI	MENT MA	OF CKE	PUNZ	BLI IE	C V HIC	VOR SHW	KS	, CAN	ADA	2 82
	BL NG	• • •	FIEL	D EN	IG:	LAB C	DATE DRILLED 30	/1/734R	PHOT	0 NO: A-277	74-8	<u>6 (</u>	HAINAG		841 TAT	+ 47	Blac	k Sni	1100	OFF	SET	ELE	V				TES	T HOLE	
0.10	1 81		>				Texonia	1001	Q	ICE			<u> </u>				0100		000		GRA	IN-S	IZE		>	Y	MILE	B,C,S	NUMBE
FTH (13	щщ	w	OVER	ANCE	ED	SOIL	DESCRIPTION		GROU	DESCRIPTION	ETH ETJ	0=	NATER	CONTE	NT ((% OF	DR	WE	GHT)	,	A	-	Ş	VEL	ENSIT	ENSIT F)	689	с	2
90	SAMP NUMB	SAMPL	% REG	ENE TI	UNIFI SOIL S				ROZEN		DEI (FE	0=1	UE COI	LASTIC	(70 ;	, UF 3		.E VU .IQUID LIMIT	LUME	,	C V0	5	N 10	6 GRA	WET D	CRY 0		REMARKS	 5
			0		PT	SILT	- Peaty		1.				20	40		<u>60</u>		80	100	0 100 1	70	70	70	70		_			
2					to		Black, Org	anic		V . -40%														:					,
~	1	\leq			OL											୍													
4						SILT	Dal David			V 2007	4						¥-				{								
	2	\square			CL	(IILL)	- Dark Brown Sandy, Cla	i, Grav iyey,	elly	V -20%			-45	+	-+		Þ	+											
6							Low Plastic				6			┼─┼	-			-			1								
8			L								8				Z]								
						SILT	- Grey,							4			_				$\frac{1}{2}$								
10	3					ered	Clay, Mor	e Shale	F	NB	10		-6-	$\left\{ - \right\}$					$\left \right $		ł								
			· .		CL	Suciel	With Depti H	ı, ard	1					<u> </u>							1						-		.*
12	-	1					- Mottled to	16-			12										1	ļ		ļ					
14											14							_	 			Ì							
							<u>^</u>					┞──┼	-#	┢╌┝					$\left - \right $		{	ļ							
16							- Grey				16								$\left - \right $		{								
10	4										10		1								1								
10						End of	Hole @18'				1 10				\square					:									
20											20			+ +	-+		_		$\left \right $		-	ĺ	ŀ						
										1				$\left\{ - \right\}$	-+				+	···##	1								
22											22			+					+		4								
24											24]	1							
		l	ĺ																				1	<u> </u>	L	I			

•

	E. W	. В	RO	OKE	ER	8	ASS	SOCI	ATES	LT	D.	DRILL	но	LE	RI	EPC	DRT	F			DE	PAF	RTN		OF CKE	PU	BLI	C W		RKS IAY	CAN	ADA	
DWM	B	. 1	FIEL	DEN	IG:	LAB	DAT	E DRIL	LE07/2/	/73 AIF	PHOT	O NO: A2286	51-13	4	CHA	INAG	E	1859) + I	2.1				OFF	SET						TEST	HOLE	
СКД	NR	М	TEC	H :		DY	RIG	May	hew 50	0 su	RFACE	DRAINAGE	Well	Dr	aine	3	VEC	SETA	TION	Blo	ick	Sprue	e		GRA	ELE	V: 17 E						
			ž	3	ಕ						DAN0	ICE											- 1		ANA	LYSI	s		цтγ	111	MILE	B,C,S	NUMBER
ΞĒ	J S	ω.	OVEF	ANCE	ED SYNB	so	ון נ	DESCRI	PTION		P R	DESCRIPTION	PTH		= WA3 = ICF	CON	CONT	'ENT T (%	(%) (% OF	SAM	RY Y PLE	VOLL	IME)		AY	Ŀ	AND	AVEL	C F.)	DENS C.F.)	689	С	3
9 B	AMP UMB	TYPE	BE	NET	DIL .						NITS		a E			PL	LAST	IC				ID			- v	8	8	6 GF	ж Р Ч	Υ ^R Ο	R	EMARKS	
			%	e 2	ő						132			<u> </u>	2	°	4	0		<u>, 1</u>	60		100	100 4	70	70	70	70					
					PT	PEAT		Med	ium Bro	own, Fi	ibrou	\$		 					· · · ·														
2						CLA	1 -	Med	ium Bro	own,		V	2		<u>a</u>							_			1								
	1	\geq						Silty	, 			10-15%		_				19-							{								
4	ľ							mea		sherry			- 4	┢──	+		<u> </u>	<u>{</u>					-+-	<u></u>	1								
	2	\geq			CI							NB					l ø								1	ļ							
6											F		6	-	+	ļ	⊬-								4			ļ	ļ				
			1	9										-		-	⊬						-+		1			Ì.					
8	ł										ł		6	╉──	+	+/	1												ļ				
															┼╌╸	H	+												Ì				
10	3		j									1	10	• 	+	ŀ¢-	<u> </u>								1			·	ļ				
					1		-	Gre	y, Silty	у, 						++-	+	<u> </u>							1								
12	-							ivieo		asticity	ļ		12	: 	+	 -	1	<u>+</u>	1				t-	<u> </u>	4		ļ						
						•					1			\vdash		++		1		 	<u>}</u>		-†		1								
14											ļ		14	·	1	╂╌╂╌		†	<u> </u>								Į						
	1	ļ									Ì	V	-	—	+	††	<u> </u>	1							1			ļ	·		1		
16	1	1]						20-25%	16		1	0	\square	1	1				-								ļ		
	4	k	1	Ì											\top	\mathbf{T}										ļ			1				
16			╞───	+		ENID	05	HOL	F 181		-		BI	'	-	1.6	1									1		1					
								TIOL																									
20	1					ļ							20												4				1				
														, E																			•
22	1												"							1										1			
						1							24												_			1					
24	1	1										· · .		1															1		L		

~

																																~	
E.	W.	BR	200	KE	R	8 A	sso		TES	LTC).	DRILL	HO	LE	R	EPO	DR1	•			DE	PA	RTM	ENT MA	OF CKE	PU NZ	BLI IE		VOF	RKS	, CAN	IADA Page 1	of 2
DWN:	BL	F	TELD	EN	G:			DRILLE	0 6/2/7 v 500		FACE	DRAINAGE We	-134 -11 D	rain	CHA ad	INAG		846	+ 08	.9 Ble	ick S	Spri	ce	OFF	SET	ELE	v:				TES	T HOLI	^E 245
					T			the year		100.	9		T	Ī											GRA	IN- S	IZE				MILE	B.C.S	NUMBER
EF.			VERY		M BOL	SOIL	DES	CRIPTI	ON		OF GROUI	DESCRIPTION	EF	0	WAT	ER (CONT	ENT	(% 0	FD	RY W	ÆlG	нт)		ANA	LYSI	s o	1 2	VSITY	VSITY	680	5	1
OEP (FEE	N BE	E E	RECO	IS TA	L SY						TS ZEN		DEPI		ICE	CON	ITEN	T (%	OF	SAM	PLE	VOL	UME)		CLA	SILT	SANI	GRAV	P. 0.	190 -	007		
	5 z S		% %	RES	505				_		FRO				2	рі 0	LASTI LIMIT 40	c	60		1 LINU 1 LINU 80	D T	100	1001	%	%	%	%	ĭ ĭ ×	580		REMARK	S
		F		1		CLAY	-	lack/	Organic		F	NB								- 1	Τ												
2					ł			~	c . r .] ,]						N.B	ank of	Donnelly
	ן י	\Box		k	21	CLAY	- (Grey,	Silty n Plasti	city	υ	Unfrozen				9	Þ.														KIVEF		
							- 1	vieu i osi		City			4																				
	, k					SILT	- (Grev	Clav-S	i 1+																					-		
6	- †	~				(Weat	h- 1	.ow to	Mediu	m			6			ľ																	
					CL	ered	. I	lastic,	, Wet					Ĺ												:							
8				t	0	Spall	9) 	Nator	ontorin	- H-			8	ļ																			
				ſ	-		- ,	varer	emering	y no																				1			
10	3	\neg									F	NB	10	ļ								_											
	T	_												L											4								
12			i										12	<u> </u>											-								
		F										† .									_	\rightarrow			4				1				
14	ļ			ļ		SHAL	E - (Grey,	Clay-si	lt,			14	ļ											-					ļ			
					сн			Shale,	, vver, Plasti	c															4								
16					CL			,		•			16	 							_				-			ľ					
	1]																_				4		i			İ			
18						-							18							·					-			1					
		ļ														-					\rightarrow				-		ļ	1					
20					ļ								20												-				1				
			1																	-					-			1		1.			
22				1									22	<u> </u>								-			-								
																H			-	{					-				1				
24	-	- +-	- +	-+	+						+ -		- 24	┼──							-+				4								

			•												_															~		
E	E. W	I. B	RO	ок	ER	8. A	SSO	CIATES	LTC).	DRILL	нс	LE	R	EPC	DRI	-			DEF	AR'	TME	ENT MA(OF CKE	PU NZ	BLI IE			RKS AY	, CAN	ADA Page 2	cof 2
DWN	BL		FIEL	DE	NG:		DATE DI	RILLED $\frac{6}{2}$	3 AIR	PHOT	0 NO:A22816	<u>- 134</u>	4	ÇНА	INAG	E]	846	+ 08	.9				OFF	SET	1					TEST	HOLE	A 1 5
CRU				<u> </u>				aynew 500	1500	O	DRAINAGE W		rain	ea		VCU	EIA		Bla	<u>ck Spr</u>	uce_			GRA	ILLE			1			<u> </u>	245
IIC			ERY	US NOL	4BOL	601	DEEC	OIDTION		ROUN		1.0		: WA1	TFR C	ONT	FNT	1% (DE D	RY WF	иднт	,		ANA	LYS	S		E	ыту	MILE	8,C,S	NUMBER
JEPT FEET	M B E A	2.2	ECO	TRA STAN	SY	3012	DESC			e u o		FEF	۵.	ICE	CON	TEN	т (%	OF	SAM	PLE V	OLUN	E)		۲¥.	i L	AND	RAVE	DEN	C F.)	689	S	1
	SAI	SAN Y	*	PENE	SOL					FROZ		1-2			PL	AST:	c ۲			LIQUID				0%	9/-	0/	- 5 - 0/.	Law Sw	08Y (Р.	F	EMARKS	
		<u> </u>					·				· · · · ·	+				4	<u> </u>			<u>00</u>		100	100+	/0	/0	/0	/0					
						CLIAIT			.1.														·.	4								
26						JUAL	: - Gr Sh	ale, Drv. L	ow			26							-					ł						[•
	4	\bigtriangleup					PI	astic, Soft								÷						+								Ì		
28												28		9																I		
				·	сы																+	1		ļ								
30					(CL							30						+				-						1		İ		
-											· ·										1											
32	5											32		T				\neg			+	1						ļ				
	•	\geq	· ·							F	NB			Ŷ								1										
34												34												1							•	
35											a a stationar	76																				
		•										30																				
38	6											30		ļ																		
		>										30		Ĭ												:						
40												40																		1		
												"																				
42								·				42																				
																					_									-		
44												44-	 								-	<u> </u>		l								
													┝								_	<u> </u>		ļ								
46	-											46										_										
													\vdash	1							_	<u> </u>		ļ								
48		>				End of	hole @	48'				48		6										ł						1		
												L										1										

ang yang panta sinta sana sana sana sana sana s

																													· ••		
	E.V	V. B	RO	OK	ER	8 A	SSOCIATES	LTD.		DRILL	но	LE	R	EPC	ORT	·	. <u></u>		DEF	ARI	ME		OF	PU	BLI	C V	VOF	RKS	, CAN	ADA	of 2
DW	v BL		FIEL	DEN	VG:	LAB I	DATE DRILLEL 6/2/	3 AIRPH	IOT	0 NO: A22861-	-134		СНА	NAG	 E:	1848	8 + 2	7.4				OFF	SET			1110			TEAT		
CKI) N	١M	TEC	H		DY	RIG Mayhew 500	SURFA	ACE	DRAINAGE We	T Dr	aine	d		VEG	ETAT		Blac	ck Sp	ruce				ELE	v :				1231		246
			,	2	ر ا				R	ICE													GRA	IN- S	ZE		<u> </u>	>	MILE	B,C,S	NUMBER
EP			VER	NCE	0 N	SOIL	DESCRIPTION		5 28	DESCRIPTION	EP	0	WAT	ER C	ONT	ENT ((% 0	F DF	RY WE	IGHT	}		*		6	ц.	NSIT (NSIT	689	S	2
059	M PL	MPL APL	RECO	E T R/	11.1E			51	E N		DEP.	0	ICE	CON	TENT	r (%	OF	SAMP	LE V	OLUM	E)		CLA	SIL	SAN	GRAV	D D L	P. C.F			_
	SA	S. ⊢	8	PEN	5 S				E E					۶L ۱	ASTIC	` -			LIQUID		00	100+	%	%	%	%	ЦЩ — Ж	, ⁸⁰	. 8	EMARKS	
⊢	1	+			РТ	PEAT	- Medium Brow	n		······································				<u> </u>			Ť		Ť			100 +		_							
							- Woody	F									+												South I	3ank of	
2	1	K		 		CLAY	- Darle Brown S	11412		NB	2					\rightarrow				·	+								Donnel	ly Rive	r
		\vdash				CLAT	Some Organic	s,						\geq	$\dot{\leftarrow}$						+										
4	\mathbf{I}	ļ			C1		Gravel Partic	les,			4					\checkmark															
	2						Medium Plast	icity								[\geq														
6			<u> </u>	L			- Traces of Fin	e Sand			6	L					4				_										
						SAND	– Light Brown																								
Ι.							- Fine, Silty																								
°	1														Λ																
	3	<u> </u>		1	SM										7																
10	Ĩ										0			9						-	1										
		-					- Grov Clay	2 5:1+				 		\uparrow		+					1										
12	1	[JUMEE	Shale, Drv.	Soft	1	· ·	12			H			†	-+			+						ļ				
1														/				-+-		+											
14					SH	а 2 2					14	<u> </u>									+					ł					
				(CL)							<u> </u>	/																		
16	\mathbf{I}								Ì		16			· .									1								
		1	ļ								1										ļ										
18	4	$ \vdash $									18		6			· · ·					<u> </u>										
	.																										ļ				
20							· · · ·				20																				
20]			20.								1					ļ							
					·			1															Ţ								
22	1										22	1						-			1		1					-			
																					1		1								
24	1			<u>†-</u>						· ·	24	<u>† †</u>						-+			+		1								

*

·.

•

			•						-			,												·						~		
	E.W	I. B	RO	OK	ER	8 /	455	SOCIA	TES	LT).	DRILL	нс	LE	RE	PO	RT			DE	PAF	RTN		OF CKE	PU NZ	BLI E		VOF	KS	, CAN	ADA Page	2 of 2
DWN	BL		FIE	D E	NG:	LAB	DAT	E DRILLE	D: 6/2/		PHOT	O NO: A2286	1-134		CHAI	AGE	1848	+ 27	.4	N -1.	<u> </u>		OFF	SET				· · · · · ·		TEST	HOLE	244
		<u>km</u> 		/ <u>n</u>		<u> </u>	THIS	Mayhe	ew DUU	1 [307	9	DRAINAGE V			n <u>ea</u>	`			<u>•· </u>	SIGCK	Spri	uce_	·	GRA	IN- S	IZE				MILE	ACS.	
EF	ыĸ		VERY	NCE NCE	N BOL	soi	LC	ESCRIPT	ION		OF	ICE DESCRIPTION	EF	0	= WATE	RCC	NTEN	т (%	OF	DRY 1	WEIGH	нт)		ANA	LYSI	s	ц.	VSITY .)	usity)			0
0EP	AMPL	AMPLE	RECC	NE TRI	IL SI						ITS DZEN		0EP		= ICE		ENT STIC	(% OF	SAN		VOLU	JME)		CLA	21רב	SAN	GRAV	PCF	Y 0E	087	2	2
	on Z	s,	8	38	°°						L IN			<u> </u>	20	- Li	40		5 0		ат Т	100	100+	%	%	%	%	3	ă	R	EMARKS	
	5	\leq				SHAI	LE -	Grey,	. Clay	& Si	l)			-4	╡		<u></u>			$\left \right $												
26								Shale	, Dry,	2011			26	\$			_	_					· · · · · · · · · · · · · · · · · · ·									
																			+	$\left \right $												
28			i		ісці								28						1			\neg										
30	6	\leftarrow									F	NB	1 30																			
32		ļ					·						32	<u></u>	┨												÷					
														-		_+	_			$\left - \right $				Ì								•
34													34	H	+																	
							-								 -				1					ŀ.								
36													36	\$ †			-		1					-								
38	7	\leq	<u> </u>	 				·					38	\Box	ŀ																	
						ENID			201				7		1.			_					·									
40						LIND	Or		30				40	,	┟┈┟					$\left \right $												
															┼╌╌┼					-								-				
42													42	<u></u>	┼──┼			-														
			ĺ														-							1								
													44]								
46													46	;					ļ													
														 						$\left - \right $												
48													48	∦	$\left\{ - \right\}$					$\left - \right $												
		Ļ	i	·	L I.			<u></u>			1	L			<u> </u>	_	<u> </u>	_ _	1	LL				L	I		/	L				
																														•		

E	E. W	. B	RO	ок	ER	8	ASSOCIATES	LTI).	DRILL	но		ER	EP	ORT	-			DE	PAR	TM		OF XE	PU NZI	BLI E	C V HIG	VOF	RKS	, CAN	ADA Page	1 of 2
DWN	B	-	FIEL	D E	NG:	LAB	DATE DRILLED 7/	2/73 AIR	рнот	0 NO: A22861-	134		Сни	LINAG	E: 18	352 -	+ 19.	.2 DI		-		OFF	SET T						TEST	норд	
CKD	. N	ĸм	TEC	н: 	r	DY	RIG: Maynew 30		FACE	DRAINAGE VYE			neu		VEG	ETA	TION	Dic	ICK 3	shine			GRA	ELE			<u> </u>			1414	
-			RΥ	δw	BOL				OUNC	ICE			- 112A		CONT		107 1		DV 1	PEIGH	T١		ANA	LYSI	S		λ	111	MILE	B,C,S	NUMBER
EET)	R F B F B F B F B F F F F F F F F F F F F	ц Т w	COVE	TAT	IED SYM	SO	IL DESCRIPTION		5 g	DESCRIPTION	EET)	17)=wa ∖=iCE	CON	TEN	сачт Т (%	0F	SAM	PLE	VOLU	ME)		LAY	Ē	Q N D	AVEI	C EN	C F.)	689	S	3
ē.	SAM	SAMF TYF	% RE	PENET RESIS	SOIL				LIMITS		05			P 20	LASTIC LIMIT	۰,	60)	LIQUI LIMI BO	ID IT	100	100+	。 %	ہ %	%	5 %	WET (P	DRY (P.	R	EMARKS	
					PT	PEAT	 Medium Brov Fibrous 	wn					_	 																	
2-	1					CLAY	Y - Medium Bro	wn to	1		· 2	┢		<u> </u>	┝─┤	\rightarrow			-+												
							Grey, Sand	ly	F	NB		\vdash	_	1	╞╧╾┥		\rightarrow	$ \sim$		-+-							ļ				
4					ML to		(coarse), so	ome			4	┢		-		4											Į				
	2	\geq			CL		Clay to Cla Some Shale	yey, Froa-				-	+	+9	F																
6	-						ments, Low	v			6	┢─		$\dagger f$					-+		- -										
			• •				Plastic					-		∦—	++																
8.											6	┢	17	4			+														
	2			ŀ			- Shale Frag	mente					± 7	<u>+</u>														ĺ			
10	5	\sum					- State Hug	inein j			10	-	-19-	+							_		1								
				ł						1 1 1				1	11								1								
12-	1										12	T]								1.
]	ŀ							
14											1.4																				
																											ł				
					сн	SHA	IE- Grev Clay	~Sil+	1												_										
J.A.	4				511		Shale				18																				
	-				(CL)				۱۲ ا	INB														1	-			1			
20								•			20	Ļ														1			1 · · ·		
														<u> </u>									┥				1				
22	l				ļ						22	·		1									4								
															 								4								
24	l			╄ -	╡	 			╡	<u> </u>	24	Ļ			$\left \right $				- +			<u></u>	4				[
		· ·	[1		1				1	1	Į	11										1	1	1		1				

. •

.

1997 - 19

8	E. W	. В	RO	OK	ER	8	AS	soci	ATES	LT	D.	DRILL	HC	LE	RE	POF	रा			DE	PAF	RTM		OF CKE	PU NZ	BLI IE	C V HIC	VOF	RKS	, CAN	ADA Poge	2 of 2
DWN			FIEL	D E	NG			TE DRIL	LED 7/2	2/73 AIF	PHOT	0 NO: A22861	-134	Irain	CHAIN ed	AGE:	18 FGET	52 +	19.2	ack	Soru	~P	OFF	SET	FLF	<u>v:</u>				TEST	HOLE	WVPL 9
Chu			2	z	6			• may		<u> </u>	GND	ICE			<u></u>	I					0010			GRA ANA	IN- S	IZE IS		٤	٤	MILE	B,C,S	NUMBER
EPTH FEET)	196.A	5	ECOVER	TRATIC	FIED SYMB	S	SIL	DESCRI	PTION		S OF EN GRO	DESCRIPTION	EPTH EET)	0	= WATE = ICE C	R CO	NTEN' ENT (r (% % OF	OF C	RY V	VEIGH VOLU	T) ME)		LAY	L1	AND	RAVEL	DENSI'	DENSI C.F.)	689	S	3
02	SAN	SAM	*	PENE	SOIL						FROZ		2			PLAS					10 1 T			%	%	%	- %	ж Е З	Υ ⁸⁰	F	EMARKS	
			<u> </u>										†	<u>+</u>		-		1		80		100	100+				<u> </u>					
	5	\vdash				SHA	LE -	- Gre Shal	y, Clay e	/-Silt				19			-							1				ŀ				
26								onai	C				20											1								
28													28	\Box]								Тара
					SH										 																	
30	6	\vdash											30	⊢ţ																		
					(CL	,					F	NB		┝╌┤										-								
32													32		┠──╂-										1							
				ľ										\vdash					$\left \right $					-								
34													34	+	┝╼╌┼╸	-			$\left - \right $									ļ				
															$\left \right $					-+				ŀ	1							
36				ł	· ·							· ·	36	it	╞╌╾┾╴								· · ·	1								
	7		1															1					<u></u>	1								
38												· · · · · · · · · · · · · · · · · · ·	38	¦ - -€										1								
						ENI	0	- HOL	E 38']								
						-																						·				
42													42	<u></u>				4														
										•																		}				
44													44	ļ				<u> </u>									·					
															╞		_							┥		1						-
46													46		┝				<u> </u>					4					ļ			
															╏╾┤╴				╂]						
48													48											1								
i				المسيسا	·									L	L			<u> </u>	I	L		t		<u>ا</u> ــــــ	I	1	I	÷	<u>. </u>	<u> </u>		

* · · · · · · · ·

1		I		•]			-		1	-																	
E	E. W	. В	RO	OK	ER	8a A	SS	OCIATES L	۲D.		DRILL	нс	LE	R	EPO	DR'	г			DE	PA	RTM	ENT	OF	PU	BLI	C V HIC	NO	RKS	, CAN	ADA Pog	elof 2
DWN	BL		FIEL	D EN	iG:	LAB	DATI	DRILLED. 27/2/734	IRPH	IOT	0 NO: A22861	-133		СНА	INAG	E: {	<u>я</u> т -	+ 22	.1				OFF	SET						TES	HOLE	
CKD	NR	<u>m</u>	TEC	н: 		JK	RIG	Mayhew Is		ACE a	DRAINAGE Go	od I				VEG	SETA	TION	· B10	ack	Spru	ce		GRA	IN- S			<u> </u>				NUMBER
-			ERY	LON	BOL		~	C COURTION	u	ROUN		120		= WA1	TER (CON1	ENT	(%	OF D	RY	WEIG	HT)		ANA	LYSI	S	िल	SITY	SITY	MILE	0,0,0	NUMBER
FEET	MPLE MBER	33	ECOV	TRAT STAN	SYN	SOIL	υ	ESCRIPTION		EN C	0200	FEET	۵	= ICE	CON	TEN	т (9	6 OF	SAM	PLE	VOL	UME)		CLAY	SILT	SAND	BRAVE	DEN PC F	C F N	689	S	4
	SAI	SAN	%	PENE	SOLN					FR02		12			Pi I	AST	^{ic} ⊢				UID AIT D	100	1004	%	%	%	%		PRO 2		EMARKS	6
			<u>† </u>		РТ	PEAT	-	Black					-	T	ľ	`	ľ –		Ĭ	Ť	Ĭ								1			
					to		-	Fibrous					4]						Donne	lly Rive	er
2.	1	\leq	1		OL		-	Silty			V-5-10%	_							ø]						Crossi	ng	
						CLAY	-	Medium Brown,	Som	e		^						\angle														
4	2	\leftarrow	-			SILT		Sand, Trace Gro	rvel								\swarrow							22	57	17	4					
6	-				CL	(TILL)	-	Low Plasticity			V 10-15%	6				Ľ	ļ															
														<u> </u>	\downarrow	Ĺ								4						ļ		
8												6	_		\downarrow		ļ							-								
			ļ											_	4		ļ							$\frac{1}{2}$						1		1
10	3	\vdash		ŀ		SILT	-	Medium Brown				10		4	 	-1	ļ						, ·	-								
		`	1			(Wea-		Clayey						1	ļ	ļ	-							-								
12.					ML	Shale)	Low Flasheny				12	_					·						-	ŀ	ļ	1			1		
İ					to								 		┨───	<u> </u>	 	ļ						-								
14					CL				F	=		14	+		+		-							-				Ì				
	4	\leq							1					┼∲-	<u> </u>		-	_					···· · ····	-								
16							-	Grey			NB	16	<u>}</u>	+			 							4			Ì	ļ				
		ļ											-	╂╂╍			<u> </u>							1								
18												18	الج	\parallel		†								1					1			
			<u> </u>						-				\vdash	#-				1	<u> </u>		 			4					1			
20	5	\square				SHALE	-	Grey, Silty-Cla	y,			20	+	-17	1	—	†		<u> </u>	<u> </u>				1			1	1				
				1	SH		-	weathered, sort						11-			<u> </u>							1								
22	1				ken							22	:+	11-	1	1		1	1					1		-						
															1		1]								
24			† –	1							· · ·	24	1		T									1								

. 2

) (m) (m)

	E. W	<i>I.</i> E	RO	ок	ER	8	AS	SOCI	ATES	LT).	D	RILL	нс	DLE	R	EPC	ORT		<u> </u>	DE	PAR					BLI E	C V HIG		IKS IAY	, CAN		e 2 of 2
DWN	BL		FIEL	D E	NG	LAB	DA	TE DRILL	ED 27	/2/731R	рнот	O NO:	A2286	1-13	3	CHA	NAG	e: 184	1 + 22	2.1		<u></u>		OFFS	ET						TEST	HOLE	
CXD	N	<u>rm</u>	TEC			JK	RI	<u>s May</u>	hew	SUF	FACE			ood			. <u> </u>	VEGE		4 : E	lack	Spruc	e		GRAII	V- SI	ZE		*	>	MILE	B,C,S	NUMBER
HE	R F F		OVER	ANCE	ED	sc	HL.	DESCRIP	TION		C OF	DESCR	IPTION	HL	0				IT (%	OF I		WEIGHT)	ŀ	ž	-	ę	IVEL	ENSIT F.)	ENSIT F.)	689	S	4
5	SAMP	SAMP	% RE(PENETI RESIST	UNIFI SOL						LIMITS FROZEN			0E (FC		- ICE 21		ASTIC		5An			100	100 +	ರ %	5 %	v %	% GR/	WET D (PC	DRY D	R	EMARKS	
	6				SH	SHA	ALE.	- Grey Wea	y, Silt thered	y-Clay , Soft	F	N	3.			þ																	
26					(CL)									26					_														
28	′	$ \ge$	}											28		6										-							
30			Ì			ENI	0 0	F HOLE	. @ 28	3'				30																			
																				+	$\left\{ -\right\}$					ł							
32														32																			
34														34																			
7.0																				<u> </u>													
30														30							$\left - \right $												
38														36	, 		_				$\left \cdot \right $												
40														40																			
			:																_														
42									·		ľ	:		42	2																		
44														44						<u> </u>													
46														46																			
		ŀ																	·														
48														48	3																		
									•	•														-									
																	~																
							:																	-									

int aint and t

E	W	. в	RO	ок	ER	8 A	ss	OCIATES LT	D.	DRILL	но)L	EF	EP	OR	Г			DE	PAR	TM	ENT MA(OF XE	PU NZ	BLI IE	C V HIC	VOF	RKS	, CAN	ADA Pa	ge 1 of 4
DWN	BL		FIEL	DE	NG	NRM	DATE	DRILLED27/2/73 AI	PHOT	O NO: A22861	-133	3	Сн	AINA	GE: Tver	184	6 + 3	33.9		<u>.</u>		OFF	SET	EI E					TEST	HOLE	
		В				JK 1	RIG	Maynew 130		DRAINAGE GO	<u>oa</u> t		<u> </u>	·····		SETA		BIC		opruc	<u>e</u>		GRA	IN- S	IZE			[MILE	BCS	NUMBER
±2			/ERY	TION	M BOL	SOIL	Di	SCRIPTION	PE NOR	ICE DESCRIPTION	±2) = ₩4	TER	сомт	ENT	(%)	OF D	RY W	EIGH	т)		ANA	LYSI	S		SITY)	151 T Y)	IN1C C	0,0,0	
	MPLE	APLE YPE	RE CO	ETRA	L SY				TS SEN		DEPT FEE	1	∆= ici	e co	NTEN	IT (9	6 OF	SAM	PLE	VOLUI	ME)		CLAY	SILT	SANC	GRAVI	P.C.F.	P. C.F.	689	5	5
	SA NU	4 ⊢	8	PEN	55				L IMI					F 20	LAST.	,,c ⊷			- LIQUI - LIME 80	D T	100	100+	%	%	%	%	E ~	DRY CRY	F	EMARKS	5
					PT	SILT	-	Organic																							
,					to		-	Black to Dark Bro	wn 🛛	14 5 100	2		4													-			~		
	I	\geq	<u> </u>		PL			Fibrous, Woody	.	V-3-10%	-				ļ			\checkmark	∍		_								Donne	lly Kiv ba	er
4	:					CLAY	-	Grey	F	V- 25-30%	4	L			_		\square													.9	
	2	\leq			CL		-	Silty Law Blacktathy		(very thin				+ 4	\neq	[,	
6							-	Low Flashcity		iuyers)	6	┢		++							_										
		-										-		\downarrow	+	<u> </u>											[
8											8	+		1-	+																
					SH	SHALE	E	Grey, Silty Cla	у	NIR]		1/		<u> </u>	<u> </u>					-	· · · · ·							_		
10	3	\geq	ł		(CL			Shale, Sandy, Lov Plasticity Weath	<u>_</u>	110	0	t	-19-	┢┙	¥							·	31	41	28						
								ered, very Soft				F		1	1	1															
"21								-			12	Γ																			
											14]																	
``	4														-																
16							-	Grey, Silty-Clay			16	ļ	Щ.	-		L									ļ						
	-							Soft, Weathered				-				<u> </u>													:		
18					ын ССО						18	+		+									{								
	-											+											1								
20	D	\geq									20	+		+	-					-+	+		1	ļ							
		ļ										-		+-	- 						-+		ł				ļ	l			
22											22	-		1	1.	1			-		-		1	1			1	ļ			
24											204		-									·····	1								
											_ ~ 4	ľ				ŀ]						L		

in state some some some

•

· · ·

	E. W	<i>I</i> . В	RO	oĸ	ER	8 AS	SOCIA	TES L	TD.	DRILL	нс	LE	R	EPO	RT			DEF	PART	MENT	OF CKE	PU NZI	BLI E		VOF	RKS	, CAN	ADA Pa	ge 2 of 4
OWN	BL	- \ 9	FIEL	D Et	VG		TE DRILLE	ED27/2 /7	AIRPHO	TO NO: A2286	1-13	$\frac{3}{to S}$	СНА	NAGE:	EGEI	846 +	- <u>33.</u>	9 Izak	C	OFF	SET	5151					TEST	HOLE	
Chu			120			<u> </u>	o mayn			E DIVANDE O	T			<u>_</u>		41101	<u>р р</u>	ICCK	spruci	e	GRA	IN- S	IZE					200	NUMBER
II C			/ERY	TION	E BOL	SOU	NESCOIPT	TION		ICE DESCRIPTION	I T C	0	= WA1	ER CO	NTEN	т (%	OFD	RY W	EIGHT)	ANA	LYSI	S		SITY	SITY			NUMBER
TEE1	MBER	ы Ч ч ч	ECO	TRA'	IFIED SYI	3016	DESURIE I		5		FEET	۵.	= ICE	CONT	ENT	(% OF	SAM	PLE V	OLUM	E)	LAY	ILT.	AND	RAVE	DEN	DEN C.F.)	689	S	5
	SAI	SAN T Y	ж Ж	PENE	SCN				1111		100		_	PLA LII	STIC H				2		0%	%	%	9 9/2	4. 7 a	0RY (P	ล	EMARKS	
-						SHYLE	- Grov	Siltur Cl			+		2	<u>^</u>	40		<u>°</u>		'	00 100 1	<u> </u>	~	~	~~			· · · · ·	-	
	6	\geq				JUNEL	- Grey Shale	, Low Pic	uy Isticity				9-							†									
26					сн		Soft,	Weathere	d		26	 																	
				(CL)																1								
28											28										1								
	-															· · · · · ·													
30	1	\vdash	{								30		9			-			-		1								
						.*		•	F	NIP											1								-
32				5					'		32								-		1.								
																				1									
34		\vdash									34										1								
	•	\vdash									· ·		0							1									
36											36										1								
															-	-			•		1								
38											38					-													
	9												ľ							1	1								
40											40												· .						
42											10																		
1									ľ		40]								-
مه	•	:]								
											4]								
46											46		ľ .																
											"																		
48										└───	40																		
Ľ																													

E	E. W	I. B	RO	ок	ER	8. 4	ASS	OCIA	TES	LTC).	DRILL	нс	LE	REI	PO	RT			DE	PA	RTM	ENT MA	OF CKE	PU NZ	BLI IE	C V HIG	VOF	RKS	, CAN	ADA Page	e 3 of 4
DWN	BL		FIEL	DE	NG	NRM	DATE	DRILLE	27/2o	73AIR	PHOT	O NO: A22861	-133	3	CHAIN	AGE	184	6+3	3.9				OFF	SET	E 1 E					TEST	HOLE	
CXU		I I	120	н		JK	RIG	Mayhe	ew	ISUR	PALE	URAINAGE G					VEGEL	ATION	BI	ack	Spru	ice		GRA	IN- S	IZE				MIL 5	BCS	NUMBER
EF			VERY	TION	M BOL	sou	DE	SCRIPT	10 N		OF	ICE DESCRIPTION	E E	0	- WATE	RC	ONTENT	(%		NRY I	NEIG	ι Τ)		ANA	LYSI	s	5	ISITY)	ISITY)		0,0,0	NUMBER
DEP)	MPL	MPLE YPE	RECO	ETRA	VIFIE L SY						TS ZEN		DEPT (FEE		= ICE C	ONT	ENT (% OF	SAN	IPLE	VOL	JME)		CLAY	SILT	SANG	GRAVI	PC.F.	P.C.F.	689	S	5
	ΰž	S +	8	PEN	şoc						L IMI				20	PLA		6	0			100	1004	%	%	%	%	×E'	DR)	F	EMARKS	;
		Γ																														
50	10	k				SHAL	E -	Grey,	Silty	-Clay			50	ļ										1	ļ							
								Soft	, LOW	FIGSIIC	iiy,			L										-								
52											F	NB	52															-				
					ѕн											\rightarrow																
54					(CL)								54			-+								1							•	
	11	\triangleright													₿- -	+		+		-				1								
56				ļ									56	1										1								
58		ļ											58]								
															┨┣-								· .	4								
60	12	${\color{black}{\frown}}$	1										60	 	k									4								
																								-				-				
62													62	–				+						{								
											ļ					-+		+						1	1	-						
64	1.2]										64					+						1								
	13	\vdash																						1								
00													00]								
68												1	68	Ļ		-																
														<u> </u>				_						4		1						
7,0		\leq											70	+			_	1						\mathbf{H}	ļ							
														-			_				+			-								
72		- -	 		┼┤		·				-		72	\vdash			_	-						1								
		<u> </u>			·							· · · · · · · · · · · · · · · · · · ·			<u> </u>	d		•	•		. <u> </u>			•			.	.				

~

E	E. W	. B	RO	OK	ER	8	AS	so	CIAT	TES	LT	D.	DRILL	но	LE	R	EPO	RT			1	DEP	ART	MENT	OF	PU N7	BLI		VOF	RKS	, CAN	ADA	e 4 of 4
DWN	BL		FIEL	DE	NG.	NR/	N DA	ATE C		027/2	2/73AIF	RPHOT	O NO: A22861	-133	3	СНА	NAGE	:	184	6+	33.9	?		OF	FSET						TEST	HOLE	
CKD	LA	B	TEC	:H :	<u> </u>	JK	RI	<u>G N</u>	Mayher	w	SU	RFACE	DRAINAGE GO	<u>od 1</u>	to S			VEGE	TATI	ON	Bla	ck Sp	oruce	;	GRA	ELE	V: 375			1			T
			ž	Nou	5 Sol							OUND	ICE							~ ~		~	IOUT.	、	ANA	LYSI	S		1	111	MILE	B,C,S	NUMBER
EPTH EET)	PLE	2.5	COVE	TATI	SYMI SYMI	S	DIL	DES	CRIPTI	ON		N CF	DESCRIPTION	EPTH EET)		= WA I = 10 E	CONT	TENT	(%	76 U	AMPI		OLUM	, Ε)	LAY	1	AND	AVEL	DENS C.F.)	DENS C F.)	689	S	5
• •	SAM NUM	SAMF	6 RE	ENE 1	UNI							ROZE		[ā.			PLA	ASTIC							0/	0/	0/-	5	ET C	08Y (P.	F	EMARKS	5
			6												┼	2	<u> </u>	40		60		80		00 100	+ 70	170	70	70					
						SH/	LE	- 0	Grey,	Silty	~Clay								+	-+-		_			-	İ							
74	•							S	hale,	Low	Soft	F	NB	74					-+-			_		+	-								
	16	\geq						ı	lusife	, , ·	5011						-+						+		1	ļ							
76					SH									76						-					-								
				(CL)															-		-			1	-							
78														78	<u> </u>				1						1								
	17	<u> </u>																							7								
80			1]										1 80		1																	
		Į								C:14	. C l			82											_								
02								- 0	hale.	Low	Plasti	city,							_					ļ									
84					SH			S	oft			1		84		-				_			- <u> </u>	ļ	_	}							
					(CL)																		_ <u>_</u>		_			1					
86	[1		86																			
														ļ											-								
88	18	\geq		<u> </u>										88	Ļd	,						_			-				Į				
						EN	DO	F H	OLE	88'					-										-						ļ		
90														90	+	<u>+</u>									-								
																		-+							-								
92	{													92	+	+		-+							-		1		}				
																1 .									-								
94	1													94		+		-						1	-					1	1		
																1							\top										
96	1													96	1										-								

E	E. W	И. В	RO	OK	ER	8 A	SSOCIATES LI	D.,	DRILL	нс)L	E R	EPC	RT			DE	PAF	RTM	ENT MA(OF CKE	PU NZI	BLI IE	C V HIC	VOF	RKS	, CAN	ADA Page 1	of 2
DWN	BL		FIEL	D EN	NG	NRM	DATE DRILLED27/2/73A	RPH01	O NO: A22861	-133	3	СНА	INAGE	18	45 + 2	1.2		<u> </u>		OFF	SET	E1 E1		.,			TEST	HOLE	
СКО		<u>B</u>	TEC	:н 		JK Ti	RIG Mayhew S	JRFACE	DRAINAGE GO	od t	to T		1	VEGE	TATION	- BI	аск	Sprud	ce		GRA	IN- S	IZE			[MILE	B.C.S	NUMBER
II C			/ERY	TION	MBOL	SOIL	DESCRIPTION	0F ROUN	ICE DESCRIPTION	E E			TER C	ONTE	IT (%	OFC	RY V	NEIGH	(T)		ANA	LYS	s	11	VIII (VSITY	(00	c,c,c	4
DEPT (FEE1	MPLE	APLE YPE	4E COV	ETRA	IFIED SYI	2012		TS O		DEPT			CON	TENT	(% ÖF	SAM	IPLE	VOLU	JME)		CLAY	י זור	SAN	GRAV	P C F	P.C.F	089	3	0
	A S N	SA	*	PEN	S UN			LIMI FRO				2	۹۲ ۲۵	ASTIC		10			100	100+	%	%	%	%	× ×	DR	F	EMARKS	
2	1				PT	PEAT	 Black to Dark Brown Fibrous (Fine) 		V-5-10%	2	2							6	•								Donne	lly Rive	er
4	2					S ILT (TILL)	 Dark Brown, Clay Sandy, Trace of Gravel, 	ey,		4			.9	-					. :								Crossii	ig	
6 8					SM		To Gravelly Low Plasticity		∨-0-5%	6 8	5 #4 8		ľ																
10	3					SILT (Weath ered Shale)	- Grey, Some Cla - Low to Medium Plasticity,	y.		10	2																		
14	4		-		ML to		 Weathered, Very Soft Shale Fragm Throughout 	ents		14	4																		
18	cor				CL		- Clay-silt, trace		NB	18	8									······	27	66	7	-					
20	e 6						of sand			20	╞																		
22 24					 	SHALE	- Grey, clay-silt, weathered, low medium plastic	to		22	2			•															

•

. مە

E	E. W	<i>I</i> . B	RO	OK	ER	8	AS:	SOCIATES	LTC).	DRILL	HO	LE	R	EPC		-			DE	:PA	RTI		OF CKE	PU NZ	BLI IE	C V HIC	VOF SHV	RKS	, CAN	ADA Poge	2 of 2
DWN	<u>BL</u>	B	FIEL	D EI	NG			TE DRILLED 27/2/	73AIRI	PHOT	O NO: A22861	-133	}	Сн	INAG	E: 1	040 5141	+ 2	1.2	le	5		OFF	SET						TEST	HOLE	
		Ť		1		31		Widynew												<u>ack</u>	501	Jue		GRA	IN- S	IZE						
ITC			ERY	NOI U	190	\$0		ESCRIPTION		ROUN	ICE DESCRIPTION	IIC	6	= WA	TER (ENT	(% I	DE D	RY I	WEIG	нт)		ANA	LYSI	S		718	51 17	MILE	B,C,S	NUMBER
FEET	4PLE 4BEA	374	ECO	TRA'	5YN	30		ESORIF HOR		0 U 9 N		EPT EET	۵	= ICE	CON	TEN	т (%	OF	SAM	PLE	VOL	UME)	LAY	11	AND	AVE	C EN	C.F.)	689	S	6
1 ~	\$A1 NUI	SAN	*	PENE	SOL					ROZ		°2			PL	ASTI	ر ^c								8 0/	8 0/	ē	1	Ϋ́,	A	FMARKS	
┝			ļ.							1.				K i	20	4	<u>, 1</u>	- 60	<u>,</u>	80	<u> </u>	10(0 1004	70	70	%	70	Ĺ_	-			
	7	\leq	1			S HA	LE -	Grey, Clay-s	silt,				<u> </u>	þ —	 									ł								
26								low to Medi	um			26		╢──	$\left \right $									-								
								Plasticity	S					∦		•								ł								
28		<u> </u>						•				28	ļ	-				\rightarrow					· · · · · · · · · · · · · · · · · · ·	4								
			ļ											 																		
30	8	\leq										30-	<u> </u>	6										4								
														 				·														
32												32		┨																		
Í					SH								ļ	<u> </u>					[
34					1CL							34	L	Ц_																		
	9						·	·	_	_	2.0			<u> </u>								\square										
36			1				• -	 Grey, Silty- Shalo 	Clay		NP	36	L	↓																		
							_	• Weathered											·													
38							-	Soft				39																				
																			_													
40	10											40																				
														\llbracket																		
42							-	· Grey, Silt-C	lay			42] .								
								Shale, Weat	hered] i								
44								Soft		F]								
														_									<u></u>	1								
46																								1								
												+6									$\neg \uparrow$			1								
40	11	\leq]			\top							1								
-*0						END	O OF	HOLE @ 48'				48		1							·			1								

. .

•

•

																												~		•
E	. W	. в	RO		ER	8 AS	SOCIA	TES LI	D.	DRILL	HO -133	LE	RE		RT 18	43 +	28.6	DE	PA	RTM	ENT MA	OF CKE	PU NZI	BLI IE		VOF	≀KS ∕AY	, CAN	ADA Page	1 of 2
CKD	LA	В	TEC	:H :		JK RI	G Mayh	ew S	JRFACI	E DRAINAGE GO	od t	o S			VEGE	TATI	ON: B	lack	Spru	JCe			ELE	V:						
II.			ERY	CE	BOL	SOU	DESCRIP		DF	ICE	*:	0	WAT	ER CO	ONTEN	NT (9	6 OF	DRY V	VEIG	HT)		GRA ANA	IN-S	S	<u></u>	ISITY)	ISITY)	MILE	8,C,S	NUMBER
OEPT (FEET	SAMPLE UMBER	AMPLE TYPE	RECOV	NETRA' SISTAN	UNIFIED	3012	DESCRIP		NITS O		DEPT (FEE1	۵.	ICE	CONT	ENT	(%)	OF SAN	APLE	VOL	UME)		CLAY	SILT	SAND	GRAVI	ET DEN (P.C.F.	RY DEN (P.C.F.	689	S	7
	~~~~	S	%	39	ŝ				55				20	LI	MIT 40		60	U.M	ι <del>τ</del> 	100	100+	%	%	%	%	3	ā	R	EMARKS	, 
					PT	PEAT	- Black											┼┼				+						Donne Crossi	lly Rive na	er
2	ĩ				ΟL		- Silty	03		∨_0-5%	2	<b>A</b>							0			ļ							.9	
			}													$\mathbf{r}$	-													
4	2					CLAY	- Silty						0	$\triangleleft$	1							4		ļ						
6	-				CL	(TILL)	- Medi - Low	um Brown Plasticity			6		$\left  \right\rangle$				_					-								
							- Grav	elly					-					┼╌┼				{								
8						· · ·	– Sandy	/			6	<b> </b>		$\uparrow$				┼╴┼			· · · · ·	1			1					
	3	_			M	SILT (Weath-	- Grey	, Low Plast Clay	icity F	NB				_\								]								
	•		ł		to	ered		,			"			_Å								<b>I</b> .			ĺ		G			. 1
12						Shale)					12			/				$\left  \right $				-								
													- /					+		_		+			1					
14											14				-	1						1	1							
	4	$\geq$				r					16		Î									] .								
["]																						-			1			ļ		
18				l							18	<u> </u>										-								
	E			-												+		+-+				-								
20	5	$\geq$									20	<u>+</u>	9									1					1			
22		•									22																			
																						-								
24				╄ —					-+ -	+	- 24	$\left  - \right $						+			•	-								
L		L	L	1	L							1			1					<b>_</b>		.L	I	1	L		<b>_</b>	1		

1

E	. W	. B	RO	OK	ER	8 AS	SOCIATES	LT	).	DRILL	HC		E REF	POF	T			DE	PAR	TM		OF CKE	PU NZ	BLI IE	C V HIC	VOF	RKS	, CAN	ADA Page 2	of 2
CKD:		R	TEC	<u>.D Ел</u> :Н :	NG:		G: Maybow	//JAIR	PHOT	O NO: A22861	-133	3	CHAIN		184 5657	3 + 28	.0		C		OFF	SET	515	<u>.</u>				TEST	HOLE	
				İ		<u></u>	- waynew			Unannou G		<u>  </u>	<u> </u>				DIC	<u>ick</u>	spruc	e		GRA	IN- S	IZE		<b></b>				
I C			/ERY	TION	KBOL	SOU	DESCRIPTION		Roun	ICE	1.0		) = WATER		ITENT	1%		RY W	FIGHT			ANA	LYSI	S	<u> </u>	È.	ΠΥ	MILE	B,C,S	NUMBE
FEET	MBLE	3.4	ECO	TRA STAN	IFIEC SYI	3016	DESCRIPTION		S S S		EPT		S= ICE C	DNTE	NT (S	% OF	SAMI	PLE	VOLUN	ME)		LAY	Ē	AND	AVEI	DENS C.F.)	DENS C.F.)	689	S	7
	N N	A L	*	PENE	N I S				FROZ	· · ·	102	·		PLAS	тю т				D T			0/.	0/.	57 0/	8 0/	L d	γRQ	5	EMARKS	
											╉╍╍╍	+	/	<u> </u>	40	<b>60</b>		80		100	100+	/0	/0	70	76					
	6	$\geq$	<u> </u>			SHALE -	- Grev. Silty,	Some				-	<del> </del>		+		+													
26							Clay, Low	••••••			26	5 <b> </b>	┼┨╼╌╏╾╸			╉╍╍╌┼╴		-+												
							Plasticity,					-	┼╂───╂──	+		<u> </u>	<u> </u>			+	·									
28					SH		Weathered				28	╞┼─	┿╂──╂──			┼─┼														
	_			(	CL)		,		F	NB	ľ	$\vdash$	╫╌┠╼		-		-+													
30	1										30	°∲	ᠹ┥──┤─	·   .		╞─┼	-+													-
			1			J	•					-	┼┼╌╴┼╺╸	-	1															
32-											32	*	╫─┼─			┟──┼														
												-	╫──┼╴		+	┝╌╌┼														
34											34	<b>I</b>	╫─┤─																	
												-	╫──╂─			╏╌╌╂								•.						
36					ļ						36	;	╂┼──╂─	+	+	╉──╉														
												-	╫──┼─		+	╞╾╌┼	$\rightarrow$													
38	8	$\rightarrow$									38	┝──	<b>╞┼</b> ─┼─		-+	<u> </u>	-+													
						END OI	f hole @ 38'					$\vdash$		+	+	┞─┤╴	-+													
40	[										40	┝──		+	╂	┠──┼╸														
														+		┝──┝														
42		Ì									42	<u>-</u>																		
														+																
44		1									44-	┢				┟														
												┢	+	+		┟╌╌┠														
46		1									46-	┢			+	-														
												-		+ '		<b>├</b> ──- <u> </u> -				+										
48											48		+			╞	_	-+												
l					[						L	1		_	1			<u> </u>												

E	. W	. B	R0		ER IG:	8 A	SSOCIATES		). РНОТ	DRILL	HO -133	)LE		OR GE	Г 1	844 -	L + 33				CKE SET	NZ		HIC	SHM	AY	, CAN	ADA <u>Page</u> г носе	<u>1 of 2</u>
СКО	LA	3	TEC	H :		JK I	RIG Mayhew	SUR	FACE	DRAINAGE God	od to	<u>o S</u> 		VE	GETA	TION	Blac	<u>k Spr</u>	uce		GRA	IN- S			Ι.	<u> </u>	MILE	B,C,S	NUMBE
DEPTH (FEET)	MPLE IMBER	MPLE Y PE	RECOVERY	ETRATION STANCE	NIFIED L SYMBOI	SOIL	DESCRIPTION	-	TS OF ZEN GROU	DESCRIPTION	DEPTH (FEET)		= WATER		TENT	(% 0 6 OF 9	SAMPL	E VO	GHT ) LUME	:)	CLAY N	SILT	SAND	GRAVEL	T DENSIT	P.C.F.)	6 <b>89</b>	S	8
	S N	¢\$	*	PEN	Soc				I NI J				20			60		10010 LIMIT 80		0 100+	%	%	%	%	-iu ∽ ≯	å	F	EMARKS	\$
2.	3				OH to MH	CLAY	<ul> <li>Organic, Black</li> <li>Dark Brown, I</li> <li>Clayey, Silty</li> </ul>	to Fibrou	s,	V-10-15%	2			•						0145%							Donne Crossir	lly Rive 19	er ·
6	2						·				6			<b>-</b>		<b>Ⅰ</b>				6102 2	-								
8	3				CL	CLAY (TILL)	<ul> <li>Medium Brown</li> <li>Silty</li> <li>Low Plasticity</li> <li>Some Sand &amp;</li> </ul>	Grav	el F	NB	8																		
12	core					SILT (Wea- thered Shale	- Grey - Clayey - Med. Plastic				14																		
16	00r¢				сі		- Clayey - Medium Plasti	c		V-0-5% (≈1/8") Iayers	18					-													
20 · 22 ·						CHAIT	Course Weather		-	NB	20																		

DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY Page JROOKER & ASSOCIATES LTD. DRILL HOLE REPORT Page 2 of 2 NRM DATE DRILLED 28/2/78AIRPHOTO NO: A22861-133 CHAINAGE: 1844 + 33 FIELD ENG OFFSET DWN BL TEST HOLE SURFACE DRAINAGE Good to S RIG: Mayhew JK VEGETATION: Black Spruce ELEV CKD LAB TECH GRAIN- SIZE OF GROUND NUMBER MILE B,C,S MET DENSITY (PC.F.) DRY DENSITY (P C.F.) PENETRATION RESISTANCE UNIFIED SOIL SYMBOL ANALYSIS ICE RECOVERY DEPTH (FEET) Sample Number Sample DESCRIPTION O = WATER CONTENT (% OF DRY WEIGHT) DEPTH (FEET) SOIL DESCRIPTION GRAVEL CLAY SAND S 689 8 SILT △=ICE CONTENT (% OF SAMPLE VOLUME) LIMITS FROZEN PLASTIC LIQUID * % REMARKS LIMIT LINIT % % % 20 60 100 + 100 4 SHALE - Weathered, Grey, SH Silty, Clayey 26 26 . . 28 28 (CI) 5 NB. F 30 30 32 32 34 34 36 36 6 38 38 END OF HOLE @ 38' 40 40 42 42 44 44 46 46 48 48-

`

	E. W	V. E	BRO	OKE	ER	8 A	SSOCIATE	ES LT	D.	DRILL	нс	DLE	REF	POR	r			DEP	AR	TMENT	OF CKE	PU	BLI	C V HIC	VOF	RKS	, CAN	ADA Page	1 of 2
DWI	BL		FIE	DEN	G	NRM	DATE DRILLED	8/2/73 AI	RPHOT	TO NO: A22861	-133	- W	CHAIN	AGE:	Off	Line	Bla	al S		OF	FSET	FIF	V:				TEST	HOLE	
		<u>\B</u>	120			<u>J</u> K _ ]	his Waynew	130	2	105									1000	5	GRA	AIN-S	IZE		>		MILE	B,C,S	NUMBER
PTH EET)	1		COVERY	RATION	IED SYMBOI	SOIL	DESCRIPTION	i	V GROU	DESCRIPTION	PTH ET)			CONTEN	TENT	(% ( 6 OF	OF DE	RY WE		() (E)	A V	5	Q	AVEL	ENSIT	DENSIT C.F.)	689	s	9
ŏĒ	SAMP	SAMP	% RE	PENET	SOIL				LIMITS FROZE		96 6		20	PLAST	ic	60		LIQUID		100 100	5 • %	5 %	%	*5 %	WET (P.O	DRY ( (P:(	f	EMARK	S
2	1				PT to OL	PEAT	– Black, Fi Silty	ibrous,		∨-30-40%	2			۵						62	8					-	Donne Crossi	lly Riv ng	ег
4	2				OL	ORGA	NIC SILT - Medium I	Brown		∨-25-30%	4			<u> </u>						C1229									
6					CL	SILT (TILL)	- Medium Clayey, Plasticity	Brown, Low		N.B.	6														-			•	
10	3								F	∨-0-5%	10	<u>A</u>											- 			67			
14	4			(	SH CL)	SHALE	E – Grey, C – Weathere – Soft	layey d		NB	14		· / · · ·									1							
18				(	to CI)						18																		
20	5				-						20																		
22											22																		
24		-	+	+ -					+ .	+	- 24	$\left  - \right $									-								

ant gang hand dawa dawa gang annin dawa dawa dawa gang d

~

•

	E.V	V. E	BRO	ок	ER	8	AS	so	CIA	<b>LTE</b>	S L	D.	DRILL	нс	)LE	R	EP	OR	<u>۲</u>			DE	PAF	RTN		OF CKE	PU NZ	BLI IE		NO	RKS	, CAN	ADA Paç	ge 2 of 2
DW	N: L		FIE	DE CH:	NG	NRA IK		TE D	May	ED.20, /hew	/4/78A s	IRPHO JRFAC	TO NO: A22	361-13 Good	33   to	<u> сн</u> / W	AINAC		Of SE TA	F <u>Lin</u>	e Bla	nck	Spru	ce	OFF	SET	FLF	V:				TEST	HOLE	
	1			,			<b>-</b>					g	105		T	<u></u>	·	<u> </u>								GRA	IN- S	IZE			<u> </u>	MILE	B.C.S	NUMBER
H.		Ē	OVER'	ATIO	YMB0	S		DES	CRIP	TION		GROU	DESCRIPTION	E E	0	= WA	TER	CONT	ENT	(% (	DF D	RY 1	NEIGH	IT)				0	_ چ	NSITY	NSITY	490	c,0,0	0
061	AMPI	AMPL	REC	NETR	UNIFI IL S			÷				STS DZEN		0EP (FEE		= ICE	: COI	NTEN	IT (%	OF	SAM	PLE	VOLU	JME)	)	CLA	SIL	SAN	GRAV	7 0E	P C.F	007		
	, ¹ 2	ς γ	*	3 8	ŝ							LIN			ļ		20	LIMIT	<u> </u>	60	)		ЧТ )	100	100 -	%	%	%	%	3	ð	F	EMARKS	; 
					5Н	SH	ALE	-	- G	rey,	Claye					 	ļ									-								
20	-				(CL to			-	• W	'eathe	ered	F	N8	26	;	-									·····	4								· [
					CI)													<u> .</u>								-								
20	6	$\vdash$	╞──		<u> </u>							<u> -  </u>		= 28	ı <b>├</b> →											-								
						ΕN	DO	FΗ	IOLE	: @ ;	28'						+									-								
30	<u>ין</u>													30	 		+	+							· <u>-</u>									
																	+	+																
32														32	<u>+</u>	1	†	1				+				1				ł				
																1	1																	
³	1													34		ľ																		
3				ļ										1 76												]			ŀ					
		1														·										]								
30		1												36	<b>_</b>	ļ		ļ																
																	ļ						$\perp$							ļ				
4														40	ļ		<b> </b>	-																
																		ļ								4			-					
42												1		42	<b> </b>							-+												
											÷					.   .	<u> </u>								· · · · · · ·									
44														44	+		+				-+		_		<u> </u>									
																	+						+	+		ł								
46	1	l	2											46	1		†	<b> </b>			-+	-+				1								
															<b> </b>	<u>†</u>	†									1								
48														48	<u> </u>	<u>†</u>	†						-+	+		1								

ی ب

Γ	E.V	V. E	RO	окі	ER	8	ASS	OCIA	TES	LT	D.	DRILL	нс	LE	RI	EP	ORT				DEF	PAR	TME		OF CKE	PU	BLI	C V HIC	VOF	RKS	, CAN	ADA Page	1 of 2
DW	N: E	BL	FIEL	DEN	IG:	NRM	DATE	DRILLE	±028/2	73AIF	PHOT	TO NO: A22861	-13	3	СНА	INAG	E:	Off	Line	Blo	ick S	DELLO	· •	OFF	SET	FIF	·····				TES	HOLE	
	<u></u>					71			ynew		2	DRAINAGE: C					VEG		10111	010			. <del>.</del>		GRA	IN-S	IZE		~	>	MILE	B,C,S	NUMBER
HTA			OVER	ATION	ED SYMBOI	so	IL DE	SCRIPT	ION		OF	DESCRIPTION	PTH ET)	0	WAT	ER (	CONTE	ENT (	% 0	F DF	RY W	EIGH"	T) ME)		× ×	-	ç	IVEL	ENSIT	ENSIT	689	S	10
06	SAMP	SAMPL	% REG	PENET! RESIST	UNIFI SOIL S						LIMITS FROZEN		DEI (FE		2	0.00	LASTIC	(76	60 60				100	100+	ರ %	5 %	%	% ся	WET D (P.C	08Y 0 (P.C	l	EMARK	3 5
2	1				PT to OL	PEA	T - blo - sil	ck, fi ty, clo	ibrous ayey			∨- 35-40%	2											£367	•				- F		Donne	illy Rive ossing,	<b>ЭГ</b> .
6	2				CI	CLA (TILI	Y- me L)- sil - lov	dium k ty v plast	orown ticity				4			ĵ			>	<u>·</u>						:							
8											F	NB	8													a mar a féir an dan dhidh an féir an dif féir a féir an an tha							
12	3					SHA	LE - g - v - s	rey veather oft, lo	red w pla	sticity			12																				
14					SH								14	<b>_</b>				_									2						
16	4				(CL	)							16	-																			
16	-				:								18																				
20	5	K											20	<b> </b>	 																		
22													22			<u></u>					_									1			
24	-	-	+	+							<u> </u>	 	24														1						

~

	•					_				·					-																<b>x</b>	
E	E. W	I. B	RO	ОК	ER	8 A	SSC		SĽ	TD.	DRILL	нс	LE	R	EPC	ORT	-			DEP	ART	ΓME		OF CKE	PU	BLI IE	C V HIC	NOF	RKS AY	, CAN	ADA Poge	2 of 2
DWN	: В	L	FIEL	.D EI	NG:	NRM	DATE	DRILLED 2	8/2/734	IRPHO	TO NO: A228	51-13	33	СНА	INAG	E	0	ff Li	ne				OFF	SET						TEST	HOLE	
CKD	L	AB	TEC	:H: 1		JK	RIG	Mayhew	s	URFAC	E DRAINAGE: (	Good	to :	5		VEG	ETA	TION	81	ack Sp	bruce			0.00	ELE	V		1				·
			۶.	Now	ğ						ICE													ANA		S		۲	1	MILE	B,C,S	NUMBER
EET)	Pin Bin Bin Bin Bin Bin Bin Bin Bin Bin B	س ب	COVE	TATI	IE0	SOIL	DES	SCRIPTION		S O	DESCRIPTION	PTH (ET)		= WAT = ICE	ER C	ONTI TEN	ENT T (%	(% ( . 0F	OF D Sam	RY WE. PIF VI	IGHT DI IEM	) F)		X	5	0 R	<b>VEL</b>	ENSI	ENSI F.)	689	S	10
õË	SAM	TYP	a a	ENET	S CNI					MITS		105			PL	ASTR	。 。			ופטוס		-,		ರ	5	5	5	5	Υ. 20.4			<u>.</u>
			8	ā ŭ	ŝ					5 2				2	<u>د</u>	.IMIT 40	<u>,</u>	60		* LIMIT 80		100	100+	%	%	%	%	3	°	H	LMARKS	·
		ľ				CHAIF	_	Grav																								
26	1				SH		-	Weather	ed	-	NID	26									· [	ļ										•
						)	-	Low Pla	sticity	r	ND		ļ			· -						ļ										
28		$\triangleright$										28	<u> </u>	<b></b>																		
						END (	OF H	IOLE @ :	28'			]											··									
30-												30									+		. <u></u>									· .
	-																					·										
32-												32										<u> </u>										
																					-	ļ										
34												34	ļ									<u> </u>										
																					ļ	<u> </u>										
36												36									1											
																					_	<u> </u>					Í					
38-							•					38									-											
																						ļ										
40												40										<u> </u>					]					
						÷																										
42												42	ļ									<u> </u>										
																			-		<u> </u>											
44												44	i									<b>_</b>		Į		ŀ						
															<b> </b>						<u>  </u>											
46												46									<u> </u>							ļ		l		
													<u> </u>								<u> </u>	<b>_</b>		ł				1				
48												48	ļ									╂		ļ				[		í		
					Ĺ						L	1																				

un sent and and and and and and a

E	E.W	I. B	RO	OK	ER	8.4	ASS	OCIAT	ES LTI	<b>)</b> .	DRILL	но	LE	RE	EPC	RT			D	EPA	RTN		OF CKE	PU NZI	BLIO E	C W HIG	VOR	KS	, CAN	ADA Pag	elof2
DWN	BL		FIEL	DEN	IG:	NRM	DATE	DRILLED	28/2/73AIR	PHOT	O NO: A22861	-133	- SE	СӉАІ	NAGE	VECE	Off	Line	BI 4		SPRI	OFF	SE T irch	FLEY					TEST	HOLE	
CKD		<u>.</u> 	TEC	H			RIG	Waynew	1507	PACE	DRAMAGE OU					VEGE							GRA	IN- S	ZE				MILE	B.C.S	NUMBER
×c			VERY	TION	MBOL	SOIL	DF	SCRIPTIO	N	OF	ICE DESCRIPTION	ΞĒ	0=	WAT	ER C	ONTE	NT (9	6 OF	DRY	WE1G	HT)		ANA		s al	EL	NSITY	NSIT)	(00		1,1
DEPT	MPLE	YPE YPE	TE CO	ETRA	IFIEC	0010			•	TS NEW		DEPT	۵=	łCE	CON	τεντ	(% (	FSA	MPLE	VOL	UME)		CLAY	SILT	SAN	GRAV	P.C.F	P.C.F	689	5	11
	S D	SAI	%	PEN	NO S OF					LIMI'				20	թե լ	ASTIC		60		NIT BO	100	, 100 <del>+</del>	%	%	%	%	×E (	a N	R	EMARKS	
-			1	1	РТ	PFAT		Black.	Fibrous		V- 30-40%																		Donne	lly Rive	er
2					•••							2																	Crossin	g	
1	1	$\leq$			GP	GRAV	/EL -	Greyis	h Brown	ļ		-				·			_				ļ								
4					to		_	Sandy,	Silty			4		-4																	
	2	${\color{black}{\frown}}$	1		GМ			Poorly	Graded	-		ĺ		-6																	
6	1		1			SILT	-	Grey,	Clayey			6								$\left  \right $	<u> </u>		ļ								
						to SHAT	F _	Low Pl	aticity	F	NB									+											
8	ł					JUAL	<b>-</b> -	LOW II	usitetty	·		8		-++	_			+-													
					ML												+		-				1								
0	3	$\leq$	1	1	to sн							10		-\$			<u></u>						1.				ļ				•
					(ML	)												+-	+	11											
12	t	]	Į									12							1				1								
														ŀ									]								
14							-	With V	Veathered			14											]	l							
16	4	$\vdash$	1					Shale,	Soft			16		Ĭ				_						1			ļ				
				-														_					1								
18			l									18					$\square$	_	-				4								
		ļ										1											-								
20	5	${}$	<u> </u>			<u></u>				-	1	20				-+			_		┝╼╾╇						1				
			Ĩ			SHAL	c -	Silty	Soft, Low														+								
22					SH			Plastic	ity			22	-							+	$\left  \right $		1			ĺ	ļ				
	ļ				to														+				1								
24	1	F -	1-	<del>†</del> -	(ML)					+	+	24	<u> </u>				-+-		+	+			1								

~

at mat mat 1

.

DWN: BL СКО: LA	L			OK	ER	8 A	SSOCIATES	LTC	).	DRILL	HO	LE	REF	POR	т			DEP	ARTI		OF CKE	PU NZ	BLI	C V HIC	VOR	KS	, CAN	ADA Pog	ge 2 of 2
	A D		FIEL		IG:		DATE DRILLED 28/4/	SUR	FACE	O NO: AZZEOI	-133		HAINA	AGE:			Blac	k Spr	ice 8	Birch	SET	FIF	V:	·			TEST	HOLE	
H			20	z	ъ Б	<u>, 1 v</u>	ing indynew	1301	GND	ICE								c opr			GRA	IN- S	SIZE		٤	2	MILE	B,C,S	NUMBER
AP FE		Ĭ	ECOVEI	STANCE	IFIED SYMB	SOIL	DESCRIPTION		S OF EN GRO	DESCRIPTION	FEET)	0=1	NATER	CON CNTE	FENT IT (%	(% 0) % OF S	F DR	Y WE	GHT )	}	1 AY	i.r	AND	RAVEL	DENSI	DENSI C F.)	689	S	11
SAI			% в	PENE	SOIL				LIMIT FROZ	*	63		20	PLAST	¹⁰	60		LIQUID LIMIT SO	10	0 1004	%	%	%	%	WET (P	087	R	EMARKS	3
					SH	SHALE	- Grev. Clayev	, &													4								
26					(CL) to		Silty, Soft, L	.ow	F	NB	26																		
28 6		4			(ML	)			•		28		,	_															
						END C	of Hole @ 28'						_						++										
30											30		_	_							1								
32											32				.			_											
-																	+												
34											34			_				_		· · · · · · · ·									
36											36					-			+-+	······	-								
38		ĺ									38																•		
								:																					
40											40																		
42											42						-												
																			+		1								
**											44-			_							1								
46			´								46								┼──┼		{								
48											48																		

E	E. W	. в	RO	ок	ER	8.	AS	SOCIATES	LTC	).	DRILL	нс	LE	R	EPO	ORT	-			DE	PAF	RTM	ENT MA(	OF CKE	PU NZ	BLI IE	C V HIG	VOF HW	RKS AY	, CAN	ADA	
DWN	BL		FIEL	DE	NG	NRM	DAT	TE DRILLED	73 AIR	PHOT	0 NO: A22861	-133	3	CHA	INAG	E: LVEG	184	8 +	27.4	<u>+</u>			OFF	SET	FIE	V:				TEST	HOLE	
CKD	<u>LA</u>	в		.m	Γ.	<u>JK</u>	Rig	Maynew	1301	PACE	UNAINAGE GO			<u>+</u>				11011						GRA	IN- S	IZE	<u> </u>	2	5	MILE	8,C,S	NUMBER
EE	a د ۲	ш	OVERY	ATION	V MBOL	soi	ι (	DESCRIPTION		OF GROU	DESCRIPTION	EE	0	= WAT	ER (	CONT	ENT	(%	OF D	RY ¥	YE1GH	T)			LTSI	\$   0	ų	F.)	NSIT	689	S	12
DEP (FE	UMBE	AMPL	REC	NETR	INIFIE					HTS DZEN		DEP (FEE		= ICE	CON	ITEN LASTI	т (% с.	6 OF	SAM	PLE	VOLU ID	IME)		CLA	SIL	SAN	GRA	ET 05	20 Z			12
	v z	Ś	8	22	~ 0 N					IJ.ĸ.		ļ		2	0		0	6(	0	LIM1 80	T	100	100+	%	%	%	%	3	ă	F	EMARKS	; 
					PT	PEAT	-	Black, Fibro	us,				L																	Donne	lly Rive	er
2	,				to Ol			Silty, Some & Gravel	Clay		V-10-15	2	_																	Crossi	ig i	
	1	$\geq$	<u> </u>										<u> </u>					$\mathcal{P}$						-								
4						SAND	> -	Medium Brow	∾n,			4	┢				A							1								
	2	$\leq$			SM	;		Silty, Some	d, Clav.			ĺ	┣			+	$\leftarrow$				-+-		······································	16	33	51	-					
6											V-0-5%	6		+		1/1																
					1								<u> </u>			/								1								
8-									•			6	<u> </u>		1						-		<u> </u>									
	3	<u> </u>													7									1		ł						
10.	Ŭ	->	 	····			E _	Grou Siltu	Clav			1 '0			9	ŀ								].								
1.2.					SH	JUAL		Weathered	ciuy,			12												].								
"					(CL)	-					NB													ł					1			
14												14	Ļ												Ì		1			2 2		
																								ł								
16-												16	ļ	+										4								
i.			ļ			-								- -																ĺ		
18-	4	$\vdash$	<u> </u>									81	+	6		-								-								
			.			END	OF	HOLE @ 18'												+				1				ĺ				
20												20	+											1				ļ	1			
													-	1										1								
22												22	t	1					-					1	1							
24												24		1										1								
24.												24		1										]								

~

and and find the set that the set the set

E	W	. В	RO	OKE	ER	8	ASS	SOCIATES LI	D.	DRILL	нс	LE	REI	POR	۲		[	DEPA	RTM		OF CKE	PU NZ	IBLI IE	C V HIG	VOF SHV	RKS VAY	, CAN	ADA	
DWN	BL		FIEL	D EN	G	NRM	DAT	E DRILLED 28/2/73A	RPHO	TO NO: A2286	1-13	3	CHAIN	AGE	1849	+ 80.1	9			OFF	SET	-				·	TEST	HOLE	
CKD	LA	<u>\В</u>	TEC	:н: 1 — Т		JK	RIG	Mayhew S	JRFAC	E DRAINAGE: G		to r T	<u>۱.                                    </u>	V	LGETA	(TION)	BIGC	ik spi	uce		684	LLE	17 F		<u> </u>			· / ·	
			RY	ຮູ	ğ				UNDO	ICE									·		ANA	LYS	IS	<b>.</b>	È	Ł	MILE	B,C,S	NUMBER
PTH EET)	36.8	ωu	COVE	RATI	SYME	so		ESCRIPTION	0.8	DESCRIPTION	PTH ET		= WAFEF = ICF C	CON ONTE	NT (°	(%)0FS			DENE)		AY.	5	Ň	AVEL	ENS	ENS	689	S	13
95	SAME	TYP	Ŭ.	CNET SIST	E E				NITS		E E		- 102 0	PLAS	דו <b>כ</b>		L					-S	v s	5	13.0	Å.		CHADY	
			*	a a	Ň				58		ļ	ļ	20	L 1M1	40	60	· ·	60	100	1004	%	%	%	%	*	<u> </u>		CMARKS	,
					PT	PEAT		Black Fibrous				ļ															Donne	lly Riv	er
2					to		-	Silty		V-5-10%	2	<u></u>	ļļ								1						Crossi	ng	
	1	$\geq$			он		-	Clayey		L						0	V.				ļ								
										V-35-40%	ه ا	L			a					<del></del>									:
	2	-				CLAY	-	Dark Brown																					
	<u></u>	$\vdash$					-	Silty			] _	[																	
<b>[</b> ]								Medium to High			ľ							1						1					
								Plasticity													]								
8											°	1			ŀ	$\square$													
			-					Stitu Clay Tea							$\mathbf{X}$						33	57	10						
10	3	$\vdash$			го СН		-	of Sand, Medium	F	NB	10			17							1 00		1.0		1		•		
					<b>~</b>			to High Plasticit							1						1								
12											12	<u>†</u>	<u> </u>  -	7				-	<u>├</u> ┣		1								
			1									<b> </b>	17	/	-			-		<u></u>	1								
14-							_	Grevish Brown			14	+	$\vdash$	-		┼┼					1	ļ							
	4	$\geq$										$\vdash$	19	-†-		<u> </u>					1								
16									ļ		16	<u>†</u>	-/-			┟╌╴┼													
													++					_ <u></u>			1								
18					_	сцин		Creat Classor			18	+	+++			╉──╁-				_	1								
						JUNE		Weathered, Soft								+		-			-								
20	5	$\leq$	1		SH						20	+	∲		-	╀╌┼	-+-				4								
					(CL)							$\vdash$	∦			╞	+		<u>  </u>	· · · · ·	+	1		1		[			
22											22	:+				╉╍┈┢╸					-								
												-	+		_	+-+			+-+	<del>.</del> .	-								
24		┝ -	+ -	┥ <u>─</u> ─				· ·	-		- 24	+				+					┥	.							
L		L	L						1	_l,		J					1				L		1	1		I	L		

~

<b>[</b>												I				<u>-</u>		r		050	A D .	TRAC					<u> </u>			CAN		<u></u>
E	E. W	I. E	BRC	OK	ER	8, /	ASS	IOCI.	ATES	S LT	D.	DRILL	HO	LE	REP	POR	T l			UEP	AR		NI MAC	CRE	NZI	IE IE	L V HIG	NOL SHM	(RS /AY	, CAN	ADA Page (	2 of 2
DWN	BL		FIE	LD E	NG:	NRM	DAT	E DRIL	LED 28,	/2/73 Alf	<b>РНО1</b>	TO NO: A22861	-13	3 [	CHAINA	GE	849	+ 80	.2				OFF	SET						TEST	HOLE	
СКО	LA	<u>B</u>	TE	CH :		JK	RIG	May	hew	SU	RFACE	DRAINAGE: G	pod	to N		VE	GETA	TION	Ble	<u>ack S</u>	pruc	e			ELE	V:						·····
			Ϋ́	N U	or						ONNO	ICE												GRA	IN-S	IZE. S		۲	7	MILE	B,C,S	NUMBER
DEPTH FEET)	MPLE	PLE PLE	ECOVE	STATS	IFIED	SOII	LD	ESCRIF	PTION		LS OF	DESCRIPTION	FEETH	0=	WATER		IT (9	(%) 6 OF	OF DE Same	RY WE PLE V	IGHT OLUN	IE)		CLAY	פורד	AND	RAVEL	DENSI C F.)	DENSI C.F.)	689	S	13
	A N N U	SAN	8	PENE	SOIL						LIMI1 FR02				20	PLAST LIMIT		60	 }	LIGUID LIMIT 80		100	100 +	%	%	%	%	PET P	Å d	R	EMARKS	•
			-	1			_								T	T	<u> </u>	ΓŤ	T			1										
	6	$\vdash$	4		SH	SHAL	.E -	Grey	y, Cla	iyey S-fi				9		-					<u> </u>											
26							-	wea	rnerea	, 2011			26			-					+	1										
																- <u>†</u>					+											
28													28			-†			+		+	-										
	_										F	NB									+											
30	7	$\geq$										_	30	fi	<b></b>			┝╼╌╊			+											
																					+	_										
32		-											32				<u> </u>															
																				·												
34													34							_	+											
		Í																														
36													36				<b> </b>		-+			-		·								
													1			-			$\rightarrow$													
38	8	$\geq$	-										38				 															
						END	OF	HOLE	: @ 38	B'							L															
40													40			_	L															
													1			_																
42													42			_																
											l																					
4													44																			
`													1																			
46													40						T													
<b>[</b> ]										•			46			1					-	1										
																1					1-	+								•		
64													48			-†	<u> </u>	†			-	-+										

in the second second second

• •

Γ	E.V	V. B	RO	OK	ER	8,4	455	OCIATES LTI	<b>)</b> .	DRILL	но	L	E	RE	EPC	DRT	-			DE	PA	RTI		OF CKE	PUI NZI	BLI E	C V HIG	VOF HW	KS AY	, CAN	ADA Page 1 a	of 2
DW	N: BL		FIEL	D EM	NG:	NRM	DATE	DRILLED 28/2/73AIR	рнот	0 NO: A22861-	-133	}	Ţ	CHAI	NAG	E	183	53 +	87.8	3	<u> </u>		OFF	SET	<b>F</b> L <b>F</b> L					TEST	HOLE	
СК		∖ <u>₿</u> T	TEC	:н : Г	<u> </u>	JK _	RIG	Mayhew SUF	RFACE	DRAINAGE GO	od t		Ν			VEG	ETA	TION	510	аск	Spru	JCe		GRA	IN- SI	ZE						
			ERY	N N	BOL				SOUN				<u> </u>	WAT	F <b>P</b> (	ONT	ENT	1%	OF D	87	WEIG	нт)		ANA	LYSI	S		SITY	sitγ	MILE	B,C,S	NUMBER
EPTH	PLE	ы Б С С	COV	TRAT	FIED SYN	SOIL		ESCRIPTION	0 8 5 N 0	DESCRIPTION	EPT)		- د ۵-	ICE	CON	TEN	т (%	5 OF	SAM	PLE	VOL	UME	1	LAY.	111	AND	RAVE	DEN C.F.	DEN C E C	689	S	14
0	SAM	SAM	× ×	PENE	NN SOIL				ROZE		02				PL	ASTI	c				UID NIT			8	%	%	°	¥61 (P	γ80 Υ	R	EMARKS	
-						DEAT		Disal	5.			┢		- 20	<u></u>		。 	60	<u>,</u>		<u> </u>	<u>'</u>	0 100+	~	~		~					
					РТ	PEAL	-	Fibrous		N 15 000		┢																		Donnel	lly Rive	er
	1	K	+	•	to		-	Clayey		V-15-20%	2	+-				5							,					1		Crossir	ng	
			2		OL		-	Silty							-1																	
4				<u> </u>		CLAY		Grevish Brown	1		4	+-			$\neg$							+										
	1	$\vdash$				•••••	-	Low Plasticity					-															<b>.</b>				
e	1						-	Silty		V- 5-10%	6	t	۵					•						1				ŀ				
												F												1								
8					~ -			<b>Č</b> I			°	Ī																				
		-	-				-	Sandy from 9' to 11'			_ [	Γ			Ţ																	
	13			ĺ								Έ			Ĭ									].								
											12																					
1 "									F		1				<u> </u>																	
											14				f																	
	1	$\mathbf{k}$	-							N10				_6		[													ĺ			
10			×	ļ						IND -	16	Ļ		4		I								4								
						SHAL	E -	Grey, Clay-Silt,				-		$\square$										-			ļ	ļ				
н								Some Sand			18	ı												-								
					SН		-	Weathered, Soft				$\vdash$	_											-								
20	5		1		(CI)		-	Med.Plasticity			20	╀			<b>}</b>	<u></u>								30	57	13	-		]			
								-				F				<u> </u>								-			1					
2	2										22	:+-	-+										<u></u>	-					ļ	,		
												-				<u> </u>								+								
24	4	-	+ -	+-	+				+	<u> </u>	24	┢	-+-								<u> </u>			4					1			

<u>م</u>

•

																																	<b>~</b> .	
	E. W	<i>і</i> . В	RO	ок	ER	8	ASS	30C	IATE	S	LTI	<b>).</b>	DRILL	НС	LE	R	EPO	ORI	F			DE	PA	RTM		OF CKE	PU NZ	BLI IE		NOF	RKS	, CAN	ADA Page 2 c	f 2
DWI	E BL	0	FIEL	D E	NG		DAT	E DRI	LLED Z	8/4/7	3 AIR	PHOT	DRAINAGE G	1-13	3 to N	CHA	INAG	E:	18 18	3 <u>53</u> +	<u>87</u> ,	.8 lack	Spr	1100	OFF	SET	EI E	<u>v:</u>				TESI	HOLE	
		<u>)</u>	1.00	<u> </u>		71			ynew_		1001	9	DIANNAGE C			<u>.</u>		1.423		11.071			- 14	000		GR/	VIN- S	IZE		1		MIL F	acs	NUMBER
EF			VERY	I TEON	¥80L	soi	L 0	ESCR				OF	ICE DESCRIPTION	EF	0	= WA'	ren +	CONT	ENT	(% (	OF D	RY	WEIG	HT }		AN/	ALYSI	IS	L ا	ISITY (	ISITY			NONDER
0 EP1	MPL	APLE YPE	RECO	ETRA	VIFIE L SY							TS		0 E P 1		= ICE	CON	TEN	т (%	6 OF	SAM	IPLE	VOL	UME)		CLAI	SILT	SANC	GRAV	90 L	90	689	5	14
	9 ž	₹S	8	PEN	soc							FRO				2	. 위 20	LASTI LIMIT 4	° ⊷ ∘	60	, ,	⊣LIQU LIM BC	110 111 0	100	100+	%	%	%	%		280	F	EMARKS	- Ç
						SHAI	.E -	Gr	ev. C	lav-S	ält.	Ι		T												}	Τ							
26					SH	••••		Sor	ne Sar	nd	,			26																				
					((1)		-	We	athere	ed, S	oft	F	NB				ļ									ĺ								
28	6	$\leq$	ļ						<u></u>					= 28	6	ļ	ļ									ł								
						END	OF	HO	LE @	28'						ļ	<b> </b>								·	4								
30														30	<b> </b>		ļ	_								ł			ł					
	1																									ł				1				
32														32	<u> </u>	ļ																		
																	<b> </b>			+								ļ						
34														34														İ						
															·												[	ŀ	,	l				
36														36						┝━╍┥														
																<u> </u>	<u> </u> -									1		ŀ						
38														38	<b> </b>																			
															<u> </u>	1										1								
40	1													40	+	1										1								
															<u> </u>											1								
42														42	1		1									1								
44																										1			ł					
"																																1		
46														46																		·		
																<u> </u>													]					
48														48	<b> </b>	<b> </b>	ļ								<u>.</u>	1								
L															1	1										I I		1						

																																		· · · · · · · · · · · · · · · · · · ·
	E. V	V. E	RO	OKE	R	8 A	SS	OCIA	TE	S L	rd.		DRILL	НС	LE	R	EP	ORT	<b>r</b>			DE		RTM		OF CKE	PU NZ	BLI E	C V HIC	NOF	RKS	), CA	VADA Page	1 of 2
DWI	<u>∦ B</u>		FIEL	DEN	G	NRM	DATE	DRILL	EC 28	/2/73	IRPH	OT	0 NO: A2286	1-13	3	CH	INAG	E:	Of	f Lir	ne p	lack	5		OFF	SET				· · · · · · · · · · · · · · · · · · ·	<u> </u>	ΤΕ	T HOL	E
		<u>Ab</u>			T	JK [		Iviayi	new			1	URAINAGE: G	1	10			VEC	JE I A	TION		nack		UCe		GRA	IN- S	IZE		1		1		
IIC			ERY	N HOL	BOL	801	05					ROUN	ICE DESCRIPTION			= WA	TER	CONT	FNT	(%	OF 0	RY 1	NEIG	нт)		ANA	LYSI	s		۲۱۶ -	SITY	MILE	B,C,S	NUMBER
PEET	MPLE	314	ECOV	STAN	SYN	3016	UE	SCRIP			5	ENG		FEET	2	S= ICE	CON	NTEN	т (%	6 OF	SAN	IPLE	VOL	UME)		CLAY	זורד	AND	RAVE	DEN	OEN C.F.)	689	S	15
	A S N	SAN	ж	PENE	SOIL						LIMIT	F R 0 2					Р 20	LASTI LIMIT 4	°, 0	6	0		10 1T	100	100+	%	%	%	%	WET (P	08Y (P		REMAR	(S
2	1				PT	PEAT	-	Black Fibro	< SUS				∨ <b>-</b> 10-15%	2									0					-				Don Cros	nelly R sing	iver
4					ОН	CLAY	-	Medi Orgo	ium B inic,	Brown Silty			V-5-10%	4	Ę	<u> </u>			~		~									- 				
6					SM to SP	SAND	) - - -	Medi Fine Dens	ium B , Sili e	brown ty				6					Ĭ										-					
8						CLAY	-	Unife Grey	orm vish E	] Brown,				8																				
10	3						-	Low	y (fii Plast	ne), si icity	F	F	NB	10																				
12					CL									12																				
14	4													4															-					
16														16	<u> </u>																			
18	4													18																				
20	5													20			¢ —																	
22														22									-											
24			ļ				<u> </u>	<u> </u>				_		24	F																			

•

· · ·

Device BL         FIELD ENG         NIME DECLEGE/2///AMR/POTO NO.         Decide Table         Contract Content (% of Support Tool Block Spruce         TEST         HOLE           Cont LAB         Test         Solution         Solution <td< th=""><th>E</th><th>. W</th><th>/. E</th><th>BRC</th><th>ок</th><th>ER</th><th>8 A</th><th>SSOCIATES</th><th>LTI</th><th>).</th><th>DRILL</th><th>HC</th><th></th><th>RE</th><th>PO</th><th>٦F</th><th></th><th></th><th>DE</th><th>PAR</th><th></th><th>r oi Ack</th><th>E P</th><th>UB ZII</th><th>LIC</th><th>C V HIG</th><th>VOF</th><th>RKS AY</th><th>, CAN</th><th>ADA Poge 2</th><th>2 of 2</th></td<>	E	. W	/. E	BRC	ок	ER	8 A	SSOCIATES	LTI	).	DRILL	HC		RE	PO	٦F			DE	PAR		r oi Ack	E P	UB ZII	LIC	C V HIG	VOF	RKS AY	, CAN	ADA Poge 2	2 of 2
1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1     1 <th>DWN</th> <th></th> <th>A R</th> <th>FIE</th> <th>LD E</th> <th>NG</th> <th></th> <th>DATE DRILLED28/2</th> <th>2//JAIR</th> <th>PHOT</th> <th>DRAINAGE</th> <th>-13</th> <th>to 1</th> <th></th> <th>IAGE:</th> <th>FGET</th> <th>ATION</th> <th><u>не</u> : В</th> <th>lack</th> <th>Spruc</th> <th>0</th> <th>FFSE</th> <th>F</th> <th>FV</th> <th></th> <th></th> <th>-</th> <th></th> <th>TEST</th> <th>HOLE</th> <th></th>	DWN		A R	FIE	LD E	NG		DATE DRILLED28/2	2//JAIR	PHOT	DRAINAGE	-13	to 1		IAGE:	FGET	ATION	<u>не</u> : В	lack	Spruc	0	FFSE	F	FV			-		TEST	HOLE	
Line         Bit         Description         big         Description         End         Description         Descripion <thdescription< th="">         Des</thdescription<>	CAD			1	1	T	<u></u>	do Maynew	1001	9		T	T ^{io} I	11.					IUCK	50100		GF	AIN	SIZ	E						
1000000000000000000000000000000000000	ŦĊ			(ERY	Ne u	1901	501	DESCRIPTION		ROUN	ICE DESCRIPTION	IIC		= WATE	RCO	NTEN	т (%	OF D	RY W	EIGHT	)	A	NALY	SIS			SITY	SITY	MILE	6,0,5	NUMBER
26     33     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2     4.2	FEET	19LE 18ER	22	E C O	TRAT	SYA	5010	DESCRIPTION		5 5 5 2		EPT	Ď	= ICE	CONTI	ENT	% 0F	SAM	PLE	VOLUN	IE)				AND	<b>RAVE</b>	DEN C F)	DEN: C.F.)	689	S	15
26     CLAY     - Gray-Brown, Sondy (fine), slity, Low Plasticity     F     NB       26     CL     SHALE     - Weathered, Clayery, Gray     7       32     7     SH     CL       34     Gray     30       36     8     END OF HOLE @ 38'       40     40       42     40       44     46	03	SAN NUN	₩¥5	* *	PENE	SOL				ROZ		°2			PLA	STIC ⊨				D r					0/	ē 0/	иЕТ <р	08Y (P.	R	EMARKS	
28       CL Y       - Grey-Brown, Sondy (fine),silly, Low Plasticity       -       28         28       6       -       -       -         30       SHALE       -       Weathered, Clayey, Grey       30       -         34       -       -       -       -       -         36       -       -       -       -       -         38       -       END OF HOLE @ 38'       -       -       -         40       -       -       -       -       -         42       -       -       -       -       -         44       -       -       -       -       -         46       -       -       -       -       -		<u> </u>		Ť	+					1		+	+	20		40		<u> </u>	- 00		100 10	2+ 7	<u> </u>		~	70		-			
26     CL     Sondy (fine),silty, Low Platicity     F     NB     26       30     SHALE     - Weathered, Clayey, Grey     30			-				CLAY	- Grey-Brow	n,																						
28     6     F     NB     28       30     30     30       32     7     3H       34     36       36     8       40     40       42     40       44     40       46     48	26							Sandy (fine	e),silty,	, ,		26	;				+			·		_									
28       6       1       NB       28       1       1         30       5HALE       Weathered, Clayey, Grey       32       1       1       1         34       5H       5H       1       1       1       1       1         36       6       1       34       1       1       1       1         36       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1       1 <t< td=""><td></td><td></td><td></td><td>ļ</td><td></td><td></td><td></td><td>Low Plastic</td><td>CITY</td><td>E</td><td></td><td></td><td><b> </b></td><td></td><td>-+-</td><td></td><td></td><td></td><td></td><td></td><td></td><td>_</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>				ļ				Low Plastic	CITY	E			<b> </b>		-+-							_									
30     31       32     7       34     34       36     34       36     36       38     END OF HOLE @ 38'       42     44       44     45       48     48	28	6	$\leq$	Ţ							NB	28										_			ĺ						
30       30       30       30         32       7       34       32       34         34       34       34       34         36       36       36       36         38       8       END OF HOLE @ 38'       36         42       44       44       44         44       44       44       44         44       44       44       44										Ì			<u> </u>	├ / -	_+																
32     7     SHALE     - Weathered, Clayey, Grey     32       34     34     34       36     38       38     END OF HOLE @ 38'       40     42       44       46       48	30					+				-	-	30		_/ -			. <b> </b>														
32     7     5H     Grey     32     34       36     36     36     36       38     END OF HOLE @ 38'     38     38       40     42     44       42     44       48     48			ł				SHALE	- Weathered,	, Claye	у,		1		/													-				
34     34     34     34       36     36     36     36       39     8     END OF HOLE @ 38"     38       40     40     40       42     40     40       44     46     44       45     46     48	32	7	${\succ}$			L.,		Grey				32		6			-				<u> </u>										
34     34     34       36     36     36       30     8     END OF HOLE @ 38'       40     40       42     44       44     44       46     48		-		1		БН ГСГ								$ \downarrow \downarrow \downarrow$								_		l							
36     36     36     36       40     40     40     40       42     44     44       44     44       46     48	34											34	ļ	↓↓			-				- <b> </b>										
36     36     36     36     36       38     9     38     9     38       40     40     40     40       42     44     44     44       46     48     48     48															_	_	-				ļ										
38     END OF HOLE @ 38'     38     40     40       42     44     44     44       46     48     48	36		[	1								36	ļ.		$- \downarrow$	_															
38     8     58     38     40       40     40     40     40       42     44     44       46     48																															
40     40     40     40     40     40     40     40     40     40     40     40     42     44     44     44     44     44     44     44     44     44     44     44     46     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     48     <	38	8	$\leq$									38		4		_				_											
40     42     40     42     42     42     42     44       44     46     48     48     48     48     48     48							END C	F HOLE @ 38'				7		Ĩ.																	
	40										· .	40													1						
																													1		
	42				[					[		42																			
44     44     44     44       46     46     46     46       48     48     48																															
	مە						-																		Ì						
	**				Ì																										
48 48	46											100												}							
48 48																								1					8		
																	-														
	-10											48																			

~

	E. W	<i>I</i> . E	BRO	ок	ER	8	ASSOC	ATES	LTD		DRILL	нс	DLE	REI	20F	RT.		·	DE	PAR	TME	ENT MAC	OF XE	PUI NZI	BLI E	C W HIG		KS	, CAN	ADA Page	1 of 2
DWI	I BL		FIE	LD EI	NG:		DATE DRI	LED28/2/7	73AIRP	нот	0 NO: A22861	-133		CHAIN	AGE	(	Off Li	ine				OFF	SET	<b>F</b> 1 <b>F</b> 3					TEST	HOLE	
СКС		<u>.в</u> Т	TEC	эн: 1	··	JK	IRIG May	hew		ACE	DRAINAGE TOI	<u>r to</u>				EGEI	ATION	BIC	CK 3	pruce	3		GRAI	IN- SI	ZE						
			ERY	N U	BOL			07101		ROUN		-		= WATER	۰۵ <b>۲</b>	NTEN	T (%	OF D	ay w	FIGHT	• •		ANA		s		SITY	SITY	MILE	8,0,5	NUMBER
FEET	APLE	22		TRAT	5 ED	50	IL DESCRI	PTION		8 8 0 8 8 0	DESCRIPTION	EPTI	Δ	= ICE C	ONTI	ENT (	% OF	SAM	PLE	VOLUN	NE)	-	CLAY	Ę	AND	RAVE	DEN: C F.)	C F)	689	S	16
100	SAN	SAN	: • *	PENE	NNI SOIL					FROZ		° =	•		PLA: LIN					D T			%	%	%	° %	WET (P	Υ ^{RO} 9	ค	EMARKS	;
		<u> </u>	+-					· · · · ·				+	+	20			6	<u>^</u>	- 80	1	100	100+	~~	~	~	~					
						PEAT	-	Reddish	Brown				<u> </u>		-	-	+									1			Donnel	ly Rive	er .
2	1	$\vdash$	-		PT		<del>-</del> *	Fibrous			V-20-25%	2		1-6	+.	<u> </u>					+;	775%							Crossin	g	
															-+	-+						†									
4					to							4	· 🛉 🗕				1				+	788%									
	2	$\vdash$													- -		-				Ť	1									
6	1				OL							6	1	+ +			1				-	/									
																_	-														
8	1				ł			<b>C</b> 11.				8					-					$\neg$									
	2	-	-				-	Silty		F											420	2%						,			
10		$\vdash$				CLAY	< -	Grey, S	Silty,			1 10									<b>1</b>										
12					}			Low Pla	stic			12								1											
																										:					
14											NIR	14					$\square$				_										
	4	F	-												4																
16		$\vdash$	Y						1			16	1	↓	_																
					ļ									<u>   </u>	_		-														
18												18		┇	-																
					1	ĺ							-	┟╴╿																	
20	5	$\leq$	J				-	Boulder				20		┥┤ᢤ	→						_										
														+			+				_										
22	-				1							22	<u>!</u>	/		_															
														┼-/ -							-+										
24	1			·   ·	╆							24	· <del> </del>	+/+					-+				ł					ļ			
L	i	i	J	.L	J	i			l		l	_L					<u> </u>	<b>ل</b> ــــــــــــــــــــــــــــــــــــ	Ļ				<u> </u>	L	L	L	t	i	L <u></u>		

▲ . .

DWN BL     FIELD EVO     NRMI DATE Defluce262/V/74 ARPHOTO NO: A2280-133     CARMAGE OF ILDE     Of FIELD EVO     TEST HOLT       COD     LAB     TECH     JK     Ride Moyhew     SURFACE DEALINGE Foir to NE     VEGETATION     Block Spruce     ILEV     TEST HOLT       Cod     LAB     tech     JK     Ride Moyhew     SURFACE DEALINGE Foir to NE     VEGETATION     Block Spruce     ILEV     MILE 8.C.S.       Solu     DESCRIPTION     State Content for or Sample volume)     State Content for or Sample volume)     State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State State Sta	2	R	R	8	8	AS	ss	ос	1A1	ΓE	S	Ľ	ΓD.	•	DRILL	нс	LE	F	REP	OR	T .			DE	ΞΡΑ	RTN		OF CKE	PU NZ	BLI IE	C \ HI	NO	RK WA	S,CA	N/		ige 2 of
Image: Section of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of the program of t		<u>.</u>		1				DRI	LLE	D28	\$74	/73A		HOT	O NO: A22861	-13	3		AINA	GE		<u>f Li</u>	ne	I			OFF	SET	<b>F</b> 1 <b>F</b>					- 71	EST	HOLE	
Line       United       Solu       DESCRIPTION       B 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Ţ		.]		<u> </u>	10	.0	1410	yne	w		~	T	ş	Diventeder Fo			<u> </u>		1.**				аск		uce	·····	GRA	IN- S	IZE		1	1	1	-	805	MUMOED
100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100     100 <td>5 5</td> <td>NBQ.</td> <td>MBQ</td> <td></td> <td>so</td> <td>IL.</td> <td>DE</td> <td>SCR</td> <td>пртв</td> <td>ON</td> <td></td> <td></td> <td></td> <td>GROUI</td> <td>ICE DESCRIPTION</td> <td>EF</td> <td>0</td> <td>= W/</td> <td>TER</td> <td>CON</td> <td>TENT</td> <td>(%</td> <td>OF 1</td> <td>DRY</td> <td>WEIG</td> <td>HT)</td> <td></td> <td>ANA</td> <td>LYSI</td> <td>s</td> <td>1 =</td> <td>ISITY</td> <td>ISITY</td> <td></td> <td></td> <td><u> </u></td> <td>INUMOEN</td>	5 5	NBQ.	MBQ		so	IL.	DE	SCR	пртв	ON				GROUI	ICE DESCRIPTION	EF	0	= W/	TER	CON	TENT	(%	OF 1	DRY	WEIG	HT)		ANA	LYSI	s	1 =	ISITY	ISITY			<u> </u>	INUMOEN
** *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *         *		i S	E S											SEN		DEP'		= IC	E CO	NTEN	IT (9	6 OF	SAN	APLE	VOL	UME)		CLAY	SILT	SANG	GRAV	105		689	<u>'</u>	S	16
6       SHALE - Grey, Silty-Clay, Weathered, Soft         28       SH         30       7         32       SH         34       SH         36       SH         38       END OF HOLE @ 38'         44       44         44       44		°°	ŝ											FRO					20	LIMI			0		0/D WIT 0	100	100+	%	%	%	%	WE!	- 60	-	RI	EMARKS	;
26     Weathered, Soft     F     NB     26     Image: Soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of the soft of th				ç	на	IF	_	Gr	ev	SH	ltv-	-Cla						V														Ţ	<b>—</b>				
28     SH (CL)     F     NB     28     Image: CL     Image: CL       30     7     Image: CL     F     NB     28     Image: CL       32     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       32     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       32     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       34     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       34     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       34     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       34     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       34     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       36     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       36     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       38     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL       40     Image: CL     Image: CL     Image: CL     Image: CL     Image: CL				2		هة بير		We	athe	erec	d,	Soft	1			26	, 	Ĩ.	_		ļ		<u> </u>							<b>n</b>							
28     30     7     F     NB     28																		<u>  </u>		<u>+-</u>	ļ	 	ļ														
30     7       32     34       34     34       36     34       36     34       36     34       36     34       36     34       36     34       36     34       36     34       37     34       38     END OF HOLE @ 38'       40     40       42     44       44     44				l										F	NB	26	<b> </b>		<u> </u>	+																	
30       7         32       34         34       34         36       34         36       36         38       END OF HOLE @ 38'         40       40         42       40         44       44         46       46	1	]	1														⊢			+																	
32     32       34     32       36     36       38     8       40     40       42     40       44     44       46     40																30		<b>b</b> -	+		<b> </b>																
32     32       34     36       36     36       38     8       END OF HOLE @ 38'       40       42       44       46																		╢	+	+	<b> </b>																
34     34     34       36     38     8       38     END OF HOLE @ 38'       40     40       42     44       44     44       46     46																32	1		†	+	<b> </b>		<u> </u>														
36     38     8     END OF HOLE @ 38'     38     9     1     1       40     40     40     1     1     1       42     44     44     1     1     1       44     46     46     1     1     1																		1	1	1																	
36     36     36     36       38     END OF HOLE @ 38'     38     38       40     40     40       42     40     40       44     44     44       46     46																54																					
38     END OF HOLE @ 38'       40     40       42     40       44       46																36														-							
38     8     38     38																				<u> </u>	<u> </u>												ĺ				
40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     40     <	_												$\downarrow$		······	38	<u> </u> (	<b> </b>	-														ĺ				
				E	ND	0	)F	HOI	LE 🤇	@ 3	38'						┝			<u> </u>							· ·· ·· ·· ·										
42     42     42     42       44     44     44     44       46     46     46																40					<u> </u>																
42     42     42     42       44     44     44     44       46     46     46																		┢	+	+																	
																42	†	+-		+	<u> </u>											Í					
																	<b> </b>	<b>†</b>		+																	
46 46																44																					
																46																					
		ĺ	ĺ																																		
																49	<u> </u>		1	<u> </u>																	

ung unite same same same same same unite and same unite a

~
																															•	
	E. V	V. B	RO	OKI	ER	8 A	ss	OCIATES	LTC	).	DRILL	но	LE	R	EPO	ORT				DE	PA	RTM		OF CKE	PU NZ	BLI	C V HIC	VOF	RKS IAY	, CAN	ADA Page	l of 2
DWI	₩BL ELA	B	FIEI	D EN	NG:	NRM IK	DATI RIG:	E DRILLED27/2/7 Maybew		PHOT	O NO: A22861	-133 od ti	<u> </u>	CHA	INAG	E I VEG	838 ETA	+ 35 TION	5.3 Bla	ick S	Spru	ice	OFF	SET	ELE	V: .				TEST	HOLE	
		Ī	, <u> </u>	z	Ļ					Q.	ICF					L					<u> </u>			GRA ANA	IN S	IZE S		7	٤	MILE	B,C,S	NUMBER
EET)	9 1 8 8 8	ب ب	COVER	RATIO	IED SYMBC	SOIL	D	ESCRIPTION			DESCRIPTION	CPTH EET)		WAT		CONT	ENT T (%	T (% OF DRY WER % OF SAMPLE VO		WEIGHT) VOLUME)		AV	A LI ON		AVEL	DENSI1	DENSI7 C.F.)	689	S	17		
5	SAME	SAMP	% RE	PENET RESIS	SOIL					LIMITS		Ĕ.			с	LIQUID LIMIT 60 60 IG		100	100+	5 %	5 %	3 %	5 %	WET 0%		F	EMARKS	; ;				
					PT	PEAT	-	Black, Fibrous Silty	5,		V-10-15%			<u>A</u> -	<u> </u>					-										Donne	lly Rive	er
2	1					CLAY -	-	Medium Brow	1,			2				<u>ę.</u>														Crossir	ıg	
4						(TILL)		Silty, Medium Plasticity	ı			4																				
	2			- -	CL		-	Organics near	Тор		V-:0-5%		A			þ							<u></u>									
6	1											6				1				-†												
8			 									8			1																	• .
						SILT	-	Medium Brown	۱,					-/	<u> </u>																	
10	3	$\leq$				(Weath ered	-	Plasticity, Soft	t,	F		10		-\$-									· · ·									
12					м	Shale)		-				12												1								
					to			-																								
14					CL		-	Grey			NB	14																			.*	
31	4	$\geq$										16	· ·	9										]								
														<u> </u>																		
18	-											18		<u> </u>	<u> </u>					┝──╋				-								
20	5		┟──	1		SHATE		Weathered G	irev	1		20			<u> </u>									1					1			
			1		SH		_	Silty, Clay,	Hard				$\mid \downarrow$				ļ							$\left  \right $								
22					(CL)							22	╉─┤				ļ							4								
24		-	-  -									- 24																				

	E. V	V. B	RC	ок	ER	8 AS	SSOCIATES	LTC	).	DRILL	нс	LE	RE	EPO	RT			DE	EPA	RTN		OF CKE	PU NZ	BL IE		NOF	RKS	, CAN	ADA Poge 2	of 2
DWI	DWN: BL FIELD ENG		NRM	ATE DRILLED27/2		PHOT	0 NO: A2286	<u>1–13:</u>	3	CHAI	NAGE	<u>: 18</u>	<u> 338 +</u>	35.3	}	·		OFF	SET						TEST HOLE					
CXL	<u>) L</u>	<u>48</u>	TE	;н: 1	<u> </u>	JK R	IG Mayhew	SUR	FACE	DRAINAGE G	ood-	to S		<u>l</u> _	VEGE	TATIO	N	Black	: Spi	ruce		1	IELE	V:		T		·		
ITC			ERY	CEN	BOL	5011			ROUND		-		WAT	FR C		ат (%	OF	084	WEIG	нт)		GRA ANA		SIZE IS T	T	×1	117	MILE	B,C,S	NUMBER
DEPT (FEET	AMPLE	APLE VPE	RECOV	ETRAT	L SYN	SUL	DESCRIPTION		15 0 ZEN G		DEPTI	۵.	ICE	CONT	ENT	(% 0	F SAP	MPLE	VOL	UME)		CLAY	SILT	SAND	GRAVEI	DENS C.F.)	DENS CF)	689	S	17
	Šź	Å. Å.	*	PEN	2 0 C				L INI F RO				20	ףנג נו ו	NIT 40		60		UID AIT 0	100	1004	%	%	%	%	₩ EI	280 7	R	EMARKS	
1	4	K		1		CUALE	- Crow Silky	Class				$\Box$																		
	1	$\vdash$				JUALE	- Grey, Silly Weathered	Ciay,		NR							1	$\square$		-1		1			ł					
26	1				SH		- Harder		F	140	26			-+					····			1								•
					CL)		That def								- <del> </del> -		+	┟──┤												
28								<u></u>		·····	28				_ <del> </del>			╂∔				{			1					
						END C	)F HOLE @ 28'	۱ . :									+	┨↓				4		1						
30											30							ļļ				4								
										1																				
1 20															1							]								
1 32	1										32						1	1				1		ł			.			
											· .				Ť	-	1-					f								
34	4	ļ		}						•	34					-+		┼──┤		···		1								
		1																+			·····	4.		}						
36											36	ļ										Į								
																_			]			1				1				
3.0											70					1					•									
1~	Ί										30											]								
																1	1				<u>.</u>	1								
40											40						+	<u>†</u>												
	1										1	$\vdash$					+	$\left\{ -\right\}$												
42	1		[								42						·	+				4								
																		-					1.		Ì	1				
44											44.																			
40													T																	
"											46			t-			1					1								
l												<u>├</u>	+				+	<u>†</u> †				1								
48											48	╞──┤					+	┟╍╍┥			<u> </u>									
				t					1 1			1 I	1		1		1	1		1		1	1		1	1	1			

-



FIGURE

<u>-1</u>

SAND GRAVEL CLAY SILT FINE MEDIUM COARSE #200 #100 11/2" #60 #50 #16 #10 #8 #40 #30 #20 1<u>/</u>2" %" #4 m 100 100 90 90 ĩ 80. 80 70 70 60 60 PERCENT SMALLER 50 50 40 40 30 30 20 20 10 10 0 0 I I I TT 11 50.0 10.0 20.0 005 .020 .100 500 1.00 .010 050 200 2.00 5.00 00 .00 GRAIN SIZE IN MILLIMETERS PROJECT MACKENZIE HIGHWAY JOB NO. E-517 DATE APRIL 5/73 SAMPLE NO. 689-5-5 SHALE, SILTY CLAY, SAMPLE DESCRIPTION SANDY n DEPTH **BROOKER & ASSOCIATES** 

FIGURE

C-2

## GRAIN SIZE DISTRIBUTION



FIGURE

<u>-3</u>

**GRAIN SIZE DISTRIBUTION** 



GRAIN SIZE DISTRIBUTION

FIGURE C-4



FIGURE C=5



GRAIN SIZE DISTRIBUTION

FIGURE C 5

JOB No. _____E-517

BORE		NATURAL	Atte	erberg Li	imits		MECHANICA		s	2011				
HOLE	DEPTH	WATER CONTENT	WL	Wp	PI		M.I.T. CLAS	SIFICATION	J)	CLASSIFICATION	REMARKS			
	feet	%	%	%	%	% CLAY	% SILT	% SAND	% GRAVEL	(UNIFIED)	-			
689-s-4	5		34.2	20.6	13.6	22	87	17	4	CL				
689-S-5	10		32.8	20.1	12.7	31	41	(28)		CL	· .			
689-S-6	18-20					27	66	7	0					
689-S <b>-</b> 8	5		SOLUE	LE SU	LPHATE	s - 0.52	% - pH =	6.5 SEVE	RE CONCEN	TRATION				
689-S-12	5					16	33	51	0	SM				
689-S-12	5	· ·	SOLUI	SLE SU	LPHATE	S - NEGL	GIBLE -	pH = 6.5						
689-S <b>-</b> 13	10					33	57	. 10	0					
689-S-14	20					30	57	13	0					
						-								
											·			
	L	.L	L	L	L	L	ł	1	1	L.,				



C-7

EBA ENGINEERING CONSULTANTS LTD.

ا تعد

Lief with suit and while and and i

. . .

·

-