

000035

THE ASSOCIATION OF PROFESSIONAL ENGINEERS OF ALBERTA PERMIT NUMBER P 2 4 5 ELMER W. BROOKER & ASSOCIATES LTD.

MACKENZIE HIGHWAY

GEOTECHNICAL EVALUATION

VOLUME XXII

BOSWORTH CREEK CROSSING

MILE 631.6

MACKENZIE HIGHWAY

Submitted To:

GOVERNMENT OF CANADA

DEPARTMENT OF PUBLIC WORKS

CONTRACT NUMBER A10/73

FILE NUMBER 9305-52-37

DECEMBER, 1973

TABLE OF CONTENTS

		raye
۱.	INTRODUCTION	1
11.	GEOTECHNICAL DATA AQUISITION	1
	2.1 Field Testing 2.2 Laboratory Testing	1 2
111	SITE CONDITIONS	3
	3.1 Surface Features 3.2 Subsurface Conditions	3 4
	3.2.1 Stratigraphy of North Valley Wall 3.2.2 Stratigraphy of South Valley Wall	4 5
١٧.	CONCLUSIONS AND RECOMMENDATIONS	6
	4.1 Foundation Types 4.2 Foundation Design	6 7
	4.2.1 End Bearing Piles 4.2.2 Friction Piles	8 9
	4.3 Negative Skin Friction 4.4 Frost Heave of Piles 4.5 Subgrade Considerations on Center Line	13 13 15
	4.5.1 North Valley Wall and Creek Bank 4.5.2 South Valley Wall and Creek Bank 4.5.3 Flood Plain Area	15 17 17
	 4.6 Settlements and Required Fill Thickness 4.7 Slope Stability Considerations 4.8 Drainage Considerations 4.9 Cement Type and Corrosion Considerations 4.10 Additional Studies 	18 19 20 20 21
۷.	LIMITATIONS	21
LIST	OF REFERENCES	23

D-

APPENDICES

APPENDIX	A .	Drawing No. A-1 Key Plan Drawing No. A-2 Site and Borehole Location Plan Drawing No. A-2a General Terrain Legend Drawing No. A-3 Plates 1 and 2 Drawing No. A-4 Centerline Profile and Stratigraphy Drawing No. A-5 Cross Sections and Stratigraphy
APPENDIX	B	Borehole Logs - 689-C-4 - 632-S-1 to 12, inclusive
APPENDIX	C	Drawings No. C-1 to C-5 Grain Size Distribution Curves Drawing No. C-6 Summary of Results

I. INTRODUCTION

As part of a geotechnical engineering study, carried out from Mile 725 to Mile 632 of the proposed Mackenzie Highway, a number of major river and stream crossings, including Bosworth Creek were investigated in detail. The general site location is indicated on the Key Plan, Drawing No. A-1, Appendix A. Details of the investigation, site conditions, geotechnical data and recommendations pertinent to the development of the creek crossing, are reported herein.

This work was carried out for the Government of Canada, Department of Public Works, and was authorized by Contract Number A10/73, File No. 9305-52-307.

II. GEOTECHNICAL DATA AQUISITION

2.1 Field Testing

The evaluation of subsurface conditions has been based on field data obtained from 13 boreholes, drilled at the locations shown on Drawing No. A-2, Appendix A. Of the 13 boreholes drilled, one was drilled as a center line borehole (Borehole 632-C-4), in conjunction with the general route evaluation, and the remainder (Boreholes 632-S-1 to 632-S-12, inclusive) were located and drilled specifically to define subsurface conditions at the crossing. Detailed borehole logs are presented in Appendix B.

All boreholes were drilled with a track mounted Mayhew 500 rotrary drill rig, using a continuous air return circulation system. Boreholes advanced with this drill rig generally averaged about 4-3/4 inches in diameter. Borehole penetration ranged from 9 feet to 86 feet, and averaged 39 feet in depth. Sampling consisted of representative bag samples, obtained at depths of $2\frac{1}{2}$, 5, 10 and 18 feet below ground surface in the center line borehole, and at depth intervals of about 5 feet, below a depth of 5 feet, in the special boreholes. Undisturbed samples were not obtained at this site because of equipment limitations.

2.2 Laboratory Testing

Laboratory testing was carried out on the disturbed soil samples to determine the natural water content profile, Atterberg limits, grain size distribution, soluble sulphate concentration and organic content of the subsoil. The moisture content tests were undertaken in the field laboratory of Elmer W. Brooker & Associates Ltd. (EBA), while all other testing was confined to the EBA Edmonton laboratory. In addition to the laboratory testing outlined above, all samples were visually classified in both the EBA field and Edmonton laboratories. Soil classification was based on plasticity according to the extended Unified Classification System (1)* and on textural classification according to U.S. Engineers Department (2) textural classification triangle.

Frozen ground was classified according to a modification of the NRC system for describing permafrost (3). The modification was necessary because the disturbed nature of the sample did not permit full usage of the NRC system with respect to describing the form of excess ice. The system used retains the main symbols V and N for visible and non-visible ice, respectively, and the modifying symbols B and F for well bonded and poorly bonded non-visible ice, respectively. Excess ice quantities were estimated from visual observations.

The results of laboratory tests are presented on the borehole logs (Appendix B) where applicable, and on grain size distribution curves, Drawings No. C-1 to C-5, inclusive, Appendix C. Drawing No. C-6, Appendix C, presents a summary of laboratory test results.

^{*} Numbers in parentheses refer to List of References presented at the end of this report.

III. SITE CONDITIONS

3.1 Surface Features

The proposed Mackenzie Highway crosses Bosworth Creek at Mile 631.6 of the highway, approximately 3 miles northwest of Norman Wells. Drawing A-1, Appendix A, is a key plan of the Norman Wells-Bosworth Creek area which shows the relative location of major features in the area. Drawing No. A-2, Appendix A, presents a detailed site plan. Plates 1 and 2, of Drawing No. A-3, Appendix A, are photographs which show the crossing as it appeared on June 7, 1973.

Bosworth Creek drains the area between the southwest side of the Discovery Ridge of the Norman Range and Kee Scarp. In the spring and after major storms, considerable volume of water is channeled through the Bosworth Creek system into the Mackenzie River. However, in the summer the flow rate of Bosworth Creek is relatively low. The creek has a well developed flood plain (AFP), shown on Drawing No. A-2 and Plates 1 and 2 of Drawing No. A-3, Appendix A. The flood plain is almost 280 feet wide at the crossing, which is the narrowest point within this reach. Except for periods of peak flow, the main channel probably is less than 50 feet wide.

The valley walls containing Bosworth Creek are steepest on the southern bank where they range from 5 degrees to 16 degrees (9% to 29% grade). On the north bank the slopes range from 5 degrees to 11 degrees (9% to 19% grade). These low to moderate slopes are expected to be stable except for surface creep. The banks bordering the flood plain, where active erosion occurs, are steeper than the valley walls. These banks are susceptible to caving due to undercutting or scour by stream action. Rip rap will be required to stabilize and protect the banks during periods of maximum runoff. The surface profile along the proposed highway center line is presented in Drawing A-4, Appendix A. At the crossing, tree cover consists primarily of thick spruce, some of which are 40 to 50 feet in height. Locally, there are a few birch and in the flood plain a few small aspen have grown.

3.2 Subsurface Conditions

Based on observations from the boreholes, inferred stratigraphic sections have been compiled and are presented as Drawings No. A-4 and A-5, Appendix A. The generalized center line stratigraphy noted at the site is summarized in the following subsections.

3.2.1 Stratigraphy of North Valley Wall

	Material Description	Approximate Average Depth Below Existing Grade (ft)	Approximate Range of Thickness (ft)
PEAT	dark brown, silty, NB (Borehole 632-5-5 only)	0 - 1.5	0 - 1.5
GRAVEL	sandy to silty, medium grained gravel, NF, moisture content (m/c)=5% to 10% (Boreholes 632-S-2 and 632-S-3 only)	0 - 3.5	0 - 4
CLAY	light brown to grey below 7', silty with some sand to silty sand layers, NB to V-7%, (m/c)=285 to 36% (Boreholes 632-S-1, 632-S-2 and 632-S-3 only)	3.5 - 18.3	0 - 18
CLAY TO SILT (TILL)	generally clay till becoming a silt till with depth, grey, gravelly to cobbly, low plasticity, V-7% to NB, some unfrozen material, (m/c)=10% to 20%, locally to 32% (All boreholes)	0 - Depth of Penetration	Not Established

CLAY non-gravelly, silty, V-trace, (m/c)=15% to 20% (Borehole 632-S-2 only) 49 - Depth of Penetration Not Established

The following additional information, which may influence design or construction decisions, was also obtained during the investigation at the subject site:

- 1. The maximum depth of borehole penetration was 86 feet.
- 2. Unfrozen material was found in Borehole 632-C-4, extending from 10 feet to the bottom of the hole (18 feet); in Borehole 632-S-1, extending from 10 feet to the bottom of the hole (38 feet); in Borehole 632-S-2, extending from 25 feet to 49 feet, and in Borehole 632-S-6 (center of creek), extending to the depth of penetration (9 feet).
- 3. A potential source of seepage was found in Borehole 632-S-1 where a silty sand layer was encountered at a depth of 10 feet, which is the top of the unfrozen material.

3.2.2 Stratigraphy of South Valley Wall

	Material Description	Approximate Average Depth Below Existing Grade (ft)	Approximate Range of Thickness (ft)
SILT	light brown, clayey, trace of gravel, (m/c)=18%, NB (Borehole 632~S-11 only)	0 - 3	3
CLAY	light brown to grey, silty, low plastic, local traces of sand and gravel, NB to V-10%, (m/c)=25% to 45%	0 - 23.5	7 - 30+
SAND	light brown to grey, poorly graded, medium grained to gravelly, NF, (m/c)=8%_to 18% (Boreholes 632-S-7, 632-S-8 and 632-S-9 only)	16.0 - 33+	Min. 12 to 13

E-517

SILT (TILL)	clayey, some gravel, low plasticity, light grey, NB, (m/c)=8% to 18% (Borehole 632-S-7 only)	20 - 39	19
CLAY	grey, silty, low plasticity, V - trace to unfrozen (m/c)= 8% to 24%	39 - Depth of Penetration	Not Established

The following additional information, which may influence design or construction decisions, was also obtained during the field investigation:

- 1. The maximum depth of borehole penetration was 85 feet.
- 2. Unfrozen material was found in Borehole 632-S-7, extending from 50 feet to 68 feet, and partially frozen material extended from 68 feet to the bottom of the hole (85 feet). Borehole 632-S-11 revealed partially frozen material from 13 feet to the bottom of the hole (28 feet). Borehole 632-S-12, similarly revealed partially frozen material from 14 feet to the bottom of the hole (30 feet).
- 3. High ice content material was found in Borehole 632-S-10, where 40%-50% visual excess ice was recorded at depths of 10 to 11 feet from the surface.

IV. CONCLUSIONS AND RECOMMENDATIONS

(Borehole 632-S-7 only)

4.1 Foundation Types

The following foundation types are believed to be feasible for a bridge structure at the subject site. At present, preference has not been given to one of the suggested systems, as final selection of a foundation system should be determined in conjunction with economic and structural design considerations.

- 1. Driven Steel H-Piles
- 2. Closed End Pipe Piles driven in pre-bored holes
- 3. Timber Piles driven in pre-bored holes

4.2 Foundation Design

The major factor affecting the design of pile foundations at Bosworth Creek is the noted occurrence of irregularly distributed unfrozen zones within the subsoil. Generally the near surface subsoils are frozen adjacent to the creek, where bridge abutments will most likely be founded. However, an unfrozen zone was noted at greater depth in one of the boreholes (Borehole No. 632-S-7) near a potential bridge abutment location on the south creek bank, and unfrozen zones were detected beneath the river flood plain and in several other boreholes on both sides of the creek. Unfrozen material was encountered in seven of the thirteen boreholes drilled at the crossing site.

As there does not appear to be a definite predictable distribution of frozen and unfrozen subsoil, it is believed necessary that the design of pile systems be carried out assuming thawing of frozen soil may occur and/or unfrozen soil presently exists. Consequently, allowable pile bearing capacities must be determined on the basis of available end bearing support, and/or available skin friction support of existing subsoil material in the unfrozen state. The existence of frozen zones is considered justification to preclude the use of dynamic pile formulae as a rational approach to the determination of pile capacities. However, placement of piles through pile driving techniques will likely be the most expedient.

Because of a lack of data, with respect to soil strength and depth to a bearing surface, pile designs presented herein are largely based on empirical data, and must be considered, only preliminary in nature. Confirmation of the design parameters presented herein through additional field and/or laboratory testing is considered necessary.

The recommended foundation types listed in Subsection 3.1, may be designed in accordance with the following preliminary design parameters. However, it is stressed that the following recommendations are presented without any knowledge of proposed highway grades, geometrics, or bridge design, at the proposed crossing site. Consequently the recommendations presented may require reconsideration when these factors become known.

4.2.1 End Bearing Piles

It is considered that the only positive method of foundation support, that will permit relatively high loads without excessive settlements, at the Bosworth Creek crossing, is an end bearing pile system, achieving support on bedrock existing beneath the site. However, due to equipment limitations the maximum depth of drill penetration was 86 feet, with bedrock not being encountered.

Based on a review of bedrock elevations, noted within some borings in the Norman Wells area; it is believed that shale bedrock may be expected to be encountered at a depth of about 130 to 140 feet, below existing grade at the approximate abutment locations of the proposed bridge crossing. At this depth, support is readily attainable through the use of steel piling. It is recommended that consideration be given to the use of end bearing piles for bridge foundation support. However, determination of bedrock depth and properties at the locations of bridge abutments and piers is a necessary prerequisite to the determination of a final design pile capacity. It is believed that this could be readily achieved through the use of drilling equipment available locally in the Norman Wells area.

For preliminary design purposes, it is believed that consideration should be given to the use of closed end pipe piles to provide end bearing support in bedrock. It is recommended that piles with a minimum nominal diameter of 12 inches and a minimum weight of 65 pounds per foot be used. Although the design length of the piles has to be confirmed on the basis of additional field drilling, it is believed that a pile length of about 140 to 150 feet should be considered for preliminary design and estimating purposes.

Installation of pipe piles will require the use of both drilling and pile driving equipment. It is recommended that the piles be installed in pre-bored holes having a diameter of about 95% of the pile diameter to permit a snug fit. The pile holes should be prebored at least 5 to 10 feet into the bedrock and the piles should be driven to at least the full prebored depth. A minimum driving energy of 24,000 foot pounds is recommended. Steel H-piles are presently believed to be less feasible as preboring would result in loss of lateral support and installation without preboring is anticipated to meet with high resistance. Confirmation of this however, could be achieved through the driving of test H-piles.

A preliminary design load capacity of about 170 kips may be used for the foregoing recommended pipe pile section, if the piles can be driven to 'refusal' in bedrock. It is considered that'refusal'will constitute a penetration of less than 0.1 inch per blow, measured over the last foot of driving with the recommended pile driving energy. It is recommended that pile driving records be kept for all piles, for immediate review by the geotechnical consultant. A pile load test is also recommended prior to, or at the outset of, pile installation to confirm the load capacity of the piles and permit a correlation to the driving records.

4.2.2 Friction Piles

Based on available geotechnical information at the Bosworth Creek crossing, it is believed that a significant probability exists for the successful installation of piles at the site, achieving their load carrying capacity primarily through skin friction between pile and embedding soil. However, the present lack of specific information with respect to the strength of the insitu soils in an unfrozen condition, permits only a preliminary estimate of the load carrying capacity of friction pile types.

Confirmation of the suitability of friction piles, presentation of more detailed pile designs, and more precise estimates of pile capacities can only be made if detailed geotechnical information of subsurface deposits is obtained at the site. It is believed that this information could be readily obtained through the use of drilling equipment locally available in Norman Wells.

Alternatively, the following preliminary pile design parameters may be used for preliminary design and estimating purposes, with the final design to be confirmed on the basis of field installation records and load testing.

a. Driven Steel H- Piles

As a guide to the establishment of a preliminary pile design, it is recommended that standard H-piles 60 feet in length (below existing grade), with a minimum nominal size of 12 inches by 12 inches, and a minimum weight of 53 pounds per foot (CBP124), be considered for preliminary design purposes. It is believed that the suggested pile section can be driven, with an energy of 24,000 foot pounds to the full length of the pile. It is believed that piles driven to these specifications will permit an allowable static design load of 65 kips to be used. Although preboring is not considered necessary for the installation of steel H-piles through frozen ground, at this site, it may be desirable in very hard seasonally frozen ground and thick granular fills to ensure the alignment of the driven pile section. This will be particularly true if very long sections are to be driven.

It is essential that the embankment fill be placed to final grade, before the piles are driven or pre-bored, in order to prevent damage to the pile and to ensure proper compaction of the fill, which will limit negative skin friction loads on the pile. On site inspection and supervision of the driving of test piles or the initial piles of the foundation system is considered absolutely necessary in order to establish the final design bearing capacity. It is also considered essential that a pile driving record be maintained for all piles. The driving record of all piles should be reviewed as is practical, by the geotechnical consultant, to ensure the design intention has been realized.

ь.

Prebored Driven Closed End Steel Pipe Piles

Steel pipe piles, installed in prebored holes, may be used for foundation support. The prebored hole size should be 85 to 90 percent of the outside pile diameter to ensure a 'snug' fit, and should extend the full length of the intended pile penetration. It is essential that the fill be placed to final grade before the piles are driven or pre-bored in order to prevent damage to the pile and ensure proper compaction of the fill, which will limit negative skin friction loads on the pile.

For preliminary design purposes, it is recommended that closed end pipe piles with a minimum length of 60 feet (below existing grade), a minimum nominal diameter of 10 inches, and a minimum weight of 40 pounds per foot be considered. It is believed that the suggested pile section can be driven, with an energy of 24,000 foot pounds to the full length of the pile. It is believed that piles driven to these specifications will permit an allowable static design load of 50 kips to be used. Driven piles must penetrate to at least the full pre-bored depth. As for steel H-piles, inspection of the driving of test piles, or the first few piles of the foundation . system, is considered absolutely necessary to confirm or alter the design bearing capacity recommended herein. A pile driving record must be kept for all piles for immediate review by the geotechnical consultant.

E-517.

c. Pre-bored Driven Timber Piles

For preliminary design purposes, it is recommended that No. 12 Douglas Fir timber piles, with a minimum length of 60 feet (below existing grade), be considered for foundation support. The piles should be pressure treated with creosote and should have a minimum creosote retention of 12 pounds per cubic foot.

It is essential that the fill be placed to final grade before the piles are driven or pre-bored to prevent damage to the pile and to ensure proper compaction of the fill, which will limit negative skin friction loads on the pile. Prebored holes should have a maximum diameter equivalent to the pile tip diameter to permit a snug fit, and should extend for the full depth of anticipated pile penetration. If excessive driving resistance is encountered, overboring of approximately the upper half section of the hole may be required. Details of the overbore should be determined in the field, on the basis of driving records obtained from test piles.

If the suggested pile section can be driven, with an energy of 24,000 foot pounds, it is believed that an allowable static design load of 35 kips may be used. Piles must penetrate to at least the full prebored depth.

Field inspection by qualified personnel is considered necessary during the preboring and driving of test piles or the first few foundation piles, to establish or alter the preliminary design capacity and method of installation recommended herein. A driving record should be kept, for all piles installed, for immediate review by the geotechnical consulant.

E.W.Brooker & Associates Ltd.

4.3 <u>Negative Skin Friction</u>

The effect of negative skin friction, on individual piles and pile groups, will be dependent upon the occurrence and magnitude of thaw settlement within both the fill surrounding the piles and the natural subgrade material. At the subject crossing site, it is considered that all subgrade materials, which are not presently unfrozen, are thaw unstable and significant subsidence can be expected on thawing. Consequently, significant negative skin friction effects can be anticipated in these materials if thawing is allowed. Substantial negative skin friction effects will also be mobilized in any road grade fill surrounding piles, if loss of subgrade support occurs.

It is extremely difficult to accurately predict the anticipated total magnitude of negative skin friction loads, on any pile or pile group that may be installed at the subject site. Negative skin friction develops due to the downdrag effect of the soil around the pile as it thaws and consolidates. At potential abutment locations, it is believed that about 10 feet of near surface natural soil may thaw as a result of construction and could contribute to negative skin friction effects on thawing. Table 4.3.1 presents representative values for the negative skin friction in typical soils (4).

At the Bosworth Creek site the thickness of fill will significantly effect the depth and rate of thaw wherever the soil is presently frozen. If significant amounts of frozen material degrades then settlements of 1 to 3 feet are possible, within approach fills to the proposed crossing. Sub-grade settlements will be maximum if construction occurs in late summer and minimum for late winter construction.

4.4 Frost Heave of Piles

Frost heaving of piles can occur as the active layer freezes each winter. During the cold winter months the surface soils freeze and bond to the pile.

TABLE 4.3.1

NEGATIVE SKIN FRICTION OF UNFROZEN SOIL FOR PILE DESIGN

(After Woodward Lundgren And Associates, 1971) (4)

Description of Soil Categories Design Negative Skin Friction $P_{z} = 30d (X^{2} + 2HX)*$ Clean sands and gravels with little or no silt or clay. Typically: GW, GP, SW, SP Silty or clayey sand and gravel mixtures 700 PSF with considerable amounts of silt and clay. Typically: GM, SM, GC, SC, SF 800 PSF Moderately plastic to highly plastic inorganic clays. Typically: CL, CH 350 PSF Non-plastic to slightly plastic inorganic silts and lean clays. Typically: ML, MH Organic silts and clays. Typically: OL, OH 150 PSF

* Load developed on that portion of a pile embedded in a granular stratum.

- P = Load developed, lbs.
- d = Diameter of pile, ft.
- H = Depth of overburden to top of granular stratum, ft.
- X = Length of pile embedded in granular stratum, ft.

E-517.

In soils containing silt and clay, this shallow surface adfreeze exerts a heaving force on the pile which must be resisted by the load on the pile, the available adfreeze bond in the permafrost, and/or the skin friction of the soils which are unfrozen or have consolidated during the summer.

The design of a pile in permafrost is controlled by the embedment required to support the applied load. However, it is necessary to check the design to ensure a factor of safety against seasonal frost-heaving. In general it has been found that a slightly deeper pile embedment is the most feasible means of resisting undesirable frost heaving stresses. Suggested design stresses for general permafrost soils are presented in Table 4.4.1 (4).

4.5 Subgrade Considerations on Center Line

4.5.1 North Valley Wall and Creek Bank

As indicated in Subsection 3.3.1, the northern banks and upper slopes at Bosworth Creek are primarily a clay to silt till overlying a considerable thickness of clay at depth. Locally, an abandoned channel exists, which parallels the present channel, approximately 450 feet to the north. A thin layer of gravel overlies approximately 15 feet of clay in this abandoned channel. Estimates of the visual excess ice were typically lower than 10% except in seasonally frozen near surface material.

Although no shear strength data for thawed or frozen soil at the site is available, qualitative evaluation of the shear strength of the various strata can be made from visual observations, ice content estimates, moisture content profiles and classification test results. Based on these factors, it is concluded that relatively low shear strengths can be expected for the till. The clay in the abandoned channel will probably have a very low shear strength and may become unstable if allowed to thaw quickly. Generally below a depth of 15 to 20 feet, the natural moisture content is lower and the soil possesses greater shear strength.

TABLE 4.4.1

FROZEN SOIL ADFREEZE BOND STRENGTH FOR PILE DESIGN

(After Woodward Lundgren And Associates, 1971) (4)

De	sign Category	Applicable Cri	teria	Design Adfreeze Bond Stress for Frost
		Segregated ice Wa Condition of	ter Content Soil, (%)	(PSF)
1	- above average soil-ice condition	No visible ice, <1%	15 15 - 40	5000 4000
11	- average soil-ice condition	Little visible ice, 1 - 10%	15 15 - 40	4000 2000
111	<pre>- below average soil-ice condition</pre>	Occasional visible ice, 11 - 20%	15 15 - 40	2000 1500
IV	- poor soil-ice condition	Some visible ice, 21 - 35%	40 15 - 40	1350 1350
V	- very poor soil- ice condition	Considerable visible ice, >35%	40 Any	900 700

¹ Applies only for soils containing 5% or more of silt or clay size particles.

E-517

÷.,,,

 $\frac{1}{2}$

4.5.2 South Valley Wall and Creek Bank

The surface stratum of the southern bank of Bosworth Creek on center line is characterized by high moisture content, low to moderate ice content, alluvial clay. The clay is expected to have a low shear strength if it is allowed to thaw. Underlying the clay, between approximate elevations 360 feet and 375 feet is a low moisture content, generally poorly graded, sand stratum. The sand is expected to have a moderate to high shear strength and is likely to be the most stable stratum at the Bosworth Creek site.

4.5.3 Flood Plain Area

The river flood plain and its relationship to the present creek can be seen in Plates No. 1 and No. 2, Drawing No. A-3, Appendix A. Borehole 632-S-6, which was drilled approximately in the center of the flood plain, was unable to penetrate more than 9 feet because of free water flowing through the creek bed gravel, which resulted in sloughing conditions within the borehole.

The maximum vertical and horizontal extent of the creek bed gravel could not be ascertained. However, it is believed that the gravel underlies the entire flood plain and may grade into the sand stratum located in the south bank and valley wall. The presence of the gravel indicates that high stream velocities, at peak runoff, may cause significant scour and erosion.

The significant feature revealed by Borehole 632-S-6 was the presence of free water within the gravel. It is probable that this water will be flowing in the subsurface gravel all winter and therefore, it may contribute to a potential icing problem for winter construction and maintenance.

4.6 Settlements and Required Fill Thickness

A lack of detailed information with regard to ice contents, and a need for sophisticated testing and detailed computer analyses, make it impossible to accurately predict thaw settlement of fill, on frozen materials with excess ice contents. Therefore, only qualitative estimates of thaw settlement can be made at this time. Based on visual estimates of excess ice content, it is believed that total thaw settlement of about 0.5 to 1.0 feet can be expected beneath fills placed during winter, where the soils are presently frozen. This estimate assumes partial thawing, but does not take into account normal consolidation settlement of the unfrozen material due to the surcharge effects of the road bed fill. In the case of peat soils, normal consolidation settlement can easily reach 50 percent of the original thickness of the deposit; and can, as with thaw settlement, occur fairly rapidly. If a summer construction program is carried out settlements of up to 3 feet are believed possible. The higher settlements are due primarily to the rapid consolidation of the naturally thawed subgrade.

On the basis of the forgoing discussion, it is considered that the conventional northern construction practice of placing fill material directly on the organic subgrade is desirable at this site. Fills for bridge approaches should be constructed with allowance being made for the occurrence of thaw subsidence, if sufficient thickness of fill is not placed to preserve the frozen material. Allowance for expected subsidence can be made by either providing extra fill to compensate for the anticipated settlement or to upgrade as subsidence occurs, or both. A thickness of dry, non-plastic granular fill material of 6 feet is considered to be the minimum thickness recommended for road grade construction over frozen subgrade materials at Bosworth Creek. Local fine grained materials such as silts and clays are not considered suitable for abutment of approach fills. The thickness of road grade material required to prevent degradation of the permafrost can only be predicted after detailed theoretical analysis, which is considered to be beyond the scope of this investigation. It is recommended that fill placement should be carried out during the late winter period to minimize thermal disturbance, and possible detrimental disturbance to the existing ground cover and slopes occasioned by the construction equipment. Snow clearing should be carried out prior to all fill placement. Placement of the fill

E.W.Brooker & Associates Ltd.

should be carried out through end dumping with subsequent spreading by dozing equipment. A minimum initial lift thickness of 2 feet is suggested. Depending on construction completion schedules, placement of fills may be staged for several seasons or carried to completion as construction progresses.

4.7 Slope Stability Considerations

No evidence of recent slope instability was detected on either valley wall near the site of the river crossing. As indicated in Subsection 3.1, the valley walls are steepest on the southern side, where they range from 5 degrees to 16 degrees. On the northern side, slopes range from 5 degrees to 11 degrees.

Preliminary slope stability calculations, using assumed shear strength values for thawed materials and the known slope configuration, revealed adequate factors of safety with respect to sliding. Consequently, it is considered that approaches can be constructed on both sides of the river, on the proposed alignment, in comparative safety with respect to slope stability. However, it is recommended that excessive fill thicknesses be avoided near the crest of the slopes. In addition, cutting or excavating of slope material is not recommended and desired grades should be achieved solely through placement of fill. Placement of fill directly on underlying organic layers should be carried out.

Observations of vegetation cover, adjacent to the channel banks at the crossing, reveal that some slumping of channel banks likely occurs under the influence of channel erosion. Consequently, it is considered that rip-rap protection of the existing defined channel, upstream and downstream of the bridge crossing, may be necessary to protect the overall stability of the crossing site. Bridge abutments should be set as far back from the channel banks as is practicable. Fine grained fills should not be used for subgrade construction on the flood plain as they may be eroded during times of peak runoff.

4.8 Drainage Considerations

Approach fills will concentrate runoff water on slope, along the upslope side of the fills, therefore, it is considered essential that considerable effort and care be given to minimizing erosion on the slope parallel to the fill. Every effort should be made to preserve the vegetal-lining of all designed water courses. Wherever this is impossible, coarse gravel should be used as channel lining. Transverse flow breakers should be provided at frequent intervals to reduce the rate of runoff along the fill and thereby reduce the potential for erosion by running water. However, ponding of water adjacent to fills should be discouraged as ponded water will act as a heat source for rapid degradation of permafrost. It will also tend to reduce the shear strength of the adjacent subgrade soil and road grade fill, unless the road grade is very granular. Spacing of the flow breakers will become apparent in the field when drainage courses and gradients become accurately defined.

Culverts may be required if any fill is placed over the flood plain, because of the potential for flooding in spring and icing and flooding in the winter.

4.9 Cement Type and Corrosion Considerations

Two representative soil samples were tested to determine their soluble sulphate concentration. Positive soluble sulphate concentrations of 0.14% and 0.16% were determined from the tests. Based on these results, it is considered that Type I, Normal Portland Cement will be adequate for all concrete in contact with the subsoil. A minimum 28 day compressive strength of 3000 pounds per square inch is recommended for all concrete forming foundation elements. Further soluble sulphate concentration tests are recommended.

For steel pipe piles, extending above grade or above water level, corrosion protection may be achieved by painting or encasement with concrete. In this case, the protective coating should extend to a minimum distance of 2 feet

below final grade or minimum anticipated low water level, whichever is deeper. In the case of the pipe piles, protective coating should be provided on the interior of the pipes to prevent possible corrosion. If practical, this may also be achieved through filling of the piles with concrete.

4.10 Additional Studies

In order to more accurately assess such factors as insitu shear strength, thaw subsidence, and slope stability, it would be desirable to obtain additional detailed geotechnical information at the site. Such items as acquisition of representative undisturbed samples of the various soil types, a thorough study of existing local slopes, refined field and laboratory tests to determine shear strength and thaw subsidence factors, and a refined theoretical analysis of these factors, constitute the additional detailed geotechnical information that is considered to be of value.

In addition to the desirability of obtaining further detailed geotechnical information, it is recommended that consideration be given to establishment of a series of closely supervised and documented pile driving and pile load tests. Although preferable, these tests need not be carried out at actual bridge crossing sites, but may be carried out in areas and materials that would be representative of general foundation conditions at most of the proposed bridge sites. Such tests would provide valuable design data on which future designs of pile foundation systems could be established.

V. LIMITATIONS

The forgoing recommendations have been prepared based on our knowledge of existing conditions at Bosworth Creek and the proposed highway crossing. This knowledge has been derived from visual, physical and analytical considerations of existing soil and slope conditions, which were obtained from our field investigation. The findings and comments presented are believed to accurately reflect conditions as they are known to exist.

E.W. Brooker & Associates Ltd.

E-517

Page 22

However, due to the general nature of the study, the findings cannot be considered to be a comprehensive assessment of slope and foundation conditions at the crossing. Should conditions be encountered other than described herein, the geotechnical consultant should be contacted so that recommendations may be evaluated in light of new findings.

Respectfully Submitted,

EBA ENGINEERING CONSULTANTS LTD.

FΝ Neil R. MacLeod Balanko, P. Eng. Lawrence A. ENG

Garry R. Gilchrist, P. Eng. NRM:LAB:GRG:sjw

LIST OF REFERENCES

- 1. Yong, R.N. and Warkentin, B.P., 1966, Introduction to Soil Behavior, The MacMillan Company, New York.
- Means, R.E. and Parcher, J.V., 1963, Physical Properties of Soils, Charles E. Merrill Books Inc., Columbus, Ohio.
- 3. Pihlainen, J.A., and Johnston, G.H., 1963, Guide to a Field Description of Permafrost, N.R.C. Technical Memorandum 79.
- Woodward Lundgren & Assocaites, 1971, Results of Pile and Anchor Installation and Load Tests and Recommended Design Procedures. Trans Alaska Pipeline System, (Unpublished).





TERRAIN LEGEND

Symbol	Terrain Type	Physiographic Features	Materials Description
AFP	Active Flood Plain	Exposed bars in stream or river channel	Sand and gravel in high energy streams to silt and sand in low energy streams
AMP	Alluvial Meander Plain (Mackenzie River Meander Plain)	Flat plain often with sand dunes on it	Sands and silty sands stratified or channel deposits
OW	Outwash Plains Deltas	Tabular bodies	Sand and/or gravel
RKM .	Ridge-and-Knoll Moraine	Drumlinized till plain Rolling large linear features	Molded basal till low plastic silty-clay till
	Symbol AFP AMP OW RKM	SymbolTerrain TypeAFPActive Flood PlainAMPAlluvial Meander Plain (Mackenzie River Meander Plain)OWOutwash Plains DeltasRKMRidge-and-Knoll Moraine	SymbolTerrain TypePhysiographic FeaturesAFPActive Flood PlainExposed bars in stream or river channelAMPAlluvial Meander Plain (Mackenzie River Meander Plain)Flat plain often with sand dunes on itOWOutwash Plains DeltasTabular bodiesRKMRidge-and-Knoll MoraineDrumlinized till plain Rolling large linear features

Topstratum Phases (Associated with Terrain Types)

Df Thin (0 - 10 feet) of drift over bedrock surface

PT Mixed bog and fen peats in post glacial ponded depression

SL Slopewash or solifluction features. Topstratum of ice-rich poorly sorted silty clay and silty sand to gravel

WM Wave modified, mainly a thin sandy to gravelly washed layer over till

Complexes are shown as combinations to two terrain types with or without phases that pertain to the parent type.

Terrain symbols are modified from Canadian Gas Arctic Study Limited Terrain Study for this area.

Drawing No. A-2a

E.W.Brooker & Associates Ltd.



PLATE No. 1

Bosworth Creek Crossing. The cut line is the highway center line. North is to the left of the plate (June, 1973)



PLATE No. 2

Bosworth Creek Crossing Note the width of the main channel and flood plain. North is to the left of the plate. (June, 1973)

Drawing No. A-3





9 (<u>*</u> (

1	E.V	V. E	BRC	OK	ER	8	AS	SOCIATES	LTI	D.	DRILL	нс	LE	R	EP	OR	Γ			DE	PAR	TM	ENT	OF	PU	BL	IC V	NOI	RKS	, CAN	ADA	
DW	N: Al	.8	FIE	LD E	NG	NRM	DA	TE DRILLED11/3	773 AIR	рнот	O NO: A2276	7-1	52	CHI	UNAG				0. /		<u></u>		MAG	CKE	NZ		HIG	iΗν	VAY	مدر مدر مان م		
CKI	B) <u>.</u>	TE	СН		TJ	RIC	3: Mayhew	SUF	RFACE	DRAINAGE FY	celle	ant S	to	Cre	LIFE	<u>47</u>		U (!	<u>د اد</u>		8 D	1088	SET			<u> </u>			TEST	HOLE	
										0	<u>_</u> _	1	T T			-		1.011			- 30		n un	6.0.4	ELE	V:	<u>417</u>	<u>م`</u>	T		<u>, </u>	
1 -			ĘΨ	le R	2					l. No	ICE										- 00			ANA	LYSI	S		~	×	MILE	B,C,S	NUMBER
1.1	12.5	<u>ب</u> ر ا	S S	AN	35	so		DESCRIPTION		5 8	DESCRIPTION	1 E	0	WA	TER	CONT	ENT	(% 0	F DI	RYV	VEIGHT	.)		~		6	۲, C	ļš -	1.5	(00		
105	N N	AWA T	ž	E SS		Ì				ZEN		50	Δ=	ICE	CON	TEN	T (9	6 OF S	SAM	PLE	vorńi	AE)		CLA	11	NN.	1 à	20	00	032		4
L		"	*		- °	-				E E		1		_	P	LASTI Limit	C			LIQU	10 IT			~	~	~	0	5	μĘ.		EMARKE	
		1	1	1	1	CLAY	/				V 5-10%	┿╼╼	 1	2	1	<u> </u>		<u>60</u>		80		100	100+	70	70	%	%	Ľ.,	Ľ			
		ŀ	\$	1		min		It Brown]	V . J-1076	ļ	6		 																	
2	1.	F	-			、==,	′ _	Silty				1 2	\square		i																	
	ļ •	\vdash	4				_	Low Plasticit	v			⁻		I	9							1										
4	1		ĺ		CL		-	Gravelly	<i>,</i>		NB ·	1										-	···									
		\leftarrow	-									4							-+-													Í
	 [∠]	\vdash	ļ									i :	╞╌┨			┥─┤																
5	1		[6	┟──┤						_										[]			
	ſ	ŀ		ł											/																	
8		F						•																	I							1
Į											-	ן י										1-										
										F	•			-								+					· [
10.	3							•		11		10			-						_ <u> </u>											
					CL		-	Grey		۲ (
12-					to		-	Silly				12			-1			<u> </u>						1								
							-	Low-Med. Pi	astic		Untrozen						-	•		1				[
14																						1										
												14-							-+-			+										
						•										<u> </u>	-+					<u> </u>										
16 -												16				\downarrow													·			
		<u> </u>																														
18	4	\geq	$ \longrightarrow $																			1										
						END	OF	HOLE 18'		· · · · ·		! "°T				*						1					[· -			
20														-+					-+-			╉										
20			·							•		20-																				
					1	•								_											ł						-	•
22												22		·							ŀ		1						-			
	·	Į	- 1												T		Τ							1			. 1		- 1]
24												ľ				-	-+		-+-			1										
- [24	-+		-+	— <u></u>	-			-		\vdash										
					_																	1				- 1						

•

												-γ			<u>.</u>			· · · ·														Page 1	of 2
ow	E. 1	W. 1	BR(KE	R 8		SS	OCIAT	ES LT	D.	DRILL	H	DLE	R	EPO	OR	r			DE 	EPA	RTI		OF CKE	PL ENZ	JBL IE			RKS VAY	, CAN	ADA	
СК	D BI	<u>D</u>	TE	СН		TJ	(7V) 5 F	RIG	Mayhe	W SU	RFAC	E DRAINAGE: Ex	<u>- 1</u>	<u>52</u> lent i	ICHA to S	INAG		1903 ETA	+ 5	<u>0 (E</u> : Thi	<u>ST.)</u> In Sp	ruce	20 -	0FI - 40'	SET	- 	201	East	01		TEST	HOLE	
İ			2	z		5	_				QN	ICE	T	Τ			·					••••			GR/	AIN-	SIZE	570.	ř	1		805	
EPTH			COVE	RATIC	IED I	SYNB	SOIL	DE	SCRIPTIO	N	0F GROI	DESCRIPTION	E	ļ	= WAT	ER	CONT	ENT	(%	OFC	RY	WEIG	нт)			ALYS	15	15	NSITY	NSITY		0,0,0	IN OWNER
105	SAM	SAME	2 2	ENET	UNIT CESTS	20 20					NITS		130	^د	= ICE	CON	LASTI	т (% с	o OF	SAM	PLE LIQU	VOL #D	UME)	ł	C.A	SL	SAN	GRAV	1 06	30	632	S	
-	┿	+	+		+-								+	<u> </u>	2	<u> </u>		<u> </u>	- 6 (<u>.</u>) T 	100	100	%	%	%	%	3	ă	R	EMARKS	;
							AT	-	Lt. Brow	'n		NB		-																	Boswor	rth Cree	ek
1	1		7	·				-	Silty				2	-	a						,				1		-	-					
4			*					-	Mea. Pi Some Gr	asticity ravel (0–31	.,	v				$\overline{\}$									1								
	2		1		C			- :	Some Sai	nd	1	5 - 7%			Ŀ		7						_		34	52	12	2					
6	ľ			1				•					6	<u> </u>			1								Ţ.			–	İ				
																	\vdash								Į								
8	1												8	+		-									1								
10	3		-	I.				•	.		F					-#					-+	-+											•
	ľ	-		ļ			•	- (Grey, si	ilty sand	U] "			Î									¹ ('	8)	82	-	E .		• •	•	
12				1								Unfrozen	12	<u> </u>					\dashv														
							-								┝──┟										ļ								
14			-			1							14	╂───											4								
16	4	\vdash										:	[<u> </u>	┝╼╶┤	-/			-+	_			<u> </u>								. •		
													16			1						-†		·									
18-				-		-			<u> </u>		1		18												1								
					СГ		AY (TILL (_) Grey						/-																		
20	5	И]		.			- 3	Siltý				20		└─┼																		
22				1	[- (-)	Gravelly Some Co	/ bbles					┝──╁						-+-												
								- 1	Low Plas	ticity			22		╏					-+		-											
24		┝	╞ -	 _	↓_	∔					\perp	L	24																				
	L	L		1									- 7		li -F	T	T	T	T		T	T										•	

• 1

.

•

•

And BD Tele Tele Tele Subscription State State State State State State State	E	E. W	I. Е В	RC			8 N		SO		:S 1/2/7). РНО	DRILL	HC 7 - 1)LE 52	R CHA)RT ₅⊥_∕	903	+ 50	D (EST	EPA	RTI	MENT MA	OF CKE	PL	IBL IE	IC V HIC	VOF SHW	RKS AY	, CAN	ADA	of 2
6 CLAY (TILL) - Same U Unfrozen 0 0 00 00 0 0 0 28 CL CL CL 1 <th>(reet)</th> <th>SAMPLE NUMBER</th> <th>SAMPLE TYPE</th> <th>% RECOVERY</th> <th>PENETRATION</th> <th>UNIFIED</th> <th><u>LT</u> ;</th> <th>SOIL</th> <th>DESC</th> <th>a<u>yhew</u> RIPTION</th> <th></th> <th>LIMITS OF</th> <th>ICE DESCRIPTION</th> <th>DEPTH DEPTH (FEET)</th> <th></th> <th><u>o S</u> = WA1 = ICE</th> <th>ONTE TENT</th> <th>TATIC NT (% (% 0</th> <th>DN: T</th> <th>DRY</th> <th>WEIG</th> <th>e 20 ht) UME</th> <th><u>) - 40'</u> }</th> <th>GR/ AN/ TJ %</th> <th></th> <th>SIZE</th> <th>96.(</th> <th>WET DENSITY (PC.F.)</th> <th>DAY DENSITY (P.CF.)</th> <th>MILE 632</th> <th>B,C,S S</th> <th>NUMBER</th>	(reet)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION	UNIFIED	<u>LT</u> ;	SOIL	DESC	a <u>yhew</u> RIPTION		LIMITS OF	ICE DESCRIPTION	DEPTH DEPTH (FEET)		<u>o S</u> = WA1 = ICE	ONTE TENT	TATIC NT (% (% 0	DN: T	DRY	WEIG	e 20 ht) UME	<u>) - 40'</u> }	GR/ AN/ TJ %		SIZE	96.(WET DENSITY (PC.F.)	DAY DENSITY (P.CF.)	MILE 632	B,C,S S	NUMBER
	26 28 30 32 34 36 36 40 42 44 44 44	6 7	M M·			CL	CL (T) El	AY ILL) ND C	- Sc	IME		U	Unfrozen	26 28 30 32 34 36 38 40 42 44- 46 48																Hole (Conti	to Crool nue	ced to

																												Pag	je i of /	4
	E. W	/. E	RO	ок	ER	& ASS	SOCIATES	LTD.	DF	RILL	но	LE	R	EPC	ORT			D	EPA	RTN	MA	OF CKE	PU NZi	BLI	C V HIG		KS AY	, CAN	ADA	
CKD	<u> </u>	L <u>8</u> D	TEC	<u>.</u> D ЕІ :Н :	NG	TJ RIG	E DRILLED11/3/7 Mayhew	SURFAC	TO NO: A	22767	- 15 elle	5 <u>2</u> nt to	CHA S	NAG	E: VEGI	4903	+ 50 on: T	(EST	.) oruce	& B	OFF irch	SET	ELE	V: 2	898	<u></u>		TEST	HOLE	
			RY	N M	6			QND	10	:Е		Γ										GRA	IN- S	IZE S			<u>}</u>	MILE	8,C,S	NUMBER
DEPTH FEET)	WPLE	374	ECOVE	TRAT	SYMB SYMB	SOIL D	ESCRIPTION	S OF	DESCRI	PTION	EPTH (EET)		= WAT = ICE	ER C	CONTE TENT	NT (9	% OF OF SA	DRY	WEIG VOL	HT) UME)		X	5	QN	AVEL	DENSIT	DENSIT C.F.)	632	S	2
	SA	SAN	*	PENE	2 OL			FROZ			105		,	PL 0	ASTIC	,	6 0	+ LIQ	UID		100 4	5 %	» %	3 %	5 %	WET (P.	DRY (P	R	EMARKS	
						GRAVEL		F							Ĩ		Ĩ		Ľ	Ĩ	1004		-					Boswor	h Creel	
2	1				GМ	-	Med.				2																			
			<u>}</u>		f †	CLAY	_Silfy			· · · · · · · · · · · ·		<u> </u>	\mathbb{N}																	
	2				CL	-	Lt. Brown Silty				4			\sum																
6						-	Low Plasticity	,	-	-	6.			_		· -	_	+				ĺ								
								•	NB									+												
									· ·		6.											1								·
10	3	\leq				_	Gana				10				\vdash														•	
12						-	Grey				13							+			·· ·									
											16.																			
14-								ľ			14					+			-+											
16-	4										16			/	-+		1	1-		-+-								•		
							•				10			Д			_													
18									· .		18-																			
20	5									·	20-						_													Ĩ
	-				ML	SILT (TILL	.) Grev						[•	
22					to CL	-	Clayey	:			22.						_ _	1						-						
24					┝╺┙		Gravelly Some Cobbles				24	•		_																
		L				-	Low Plasticity								T				T	T					ĺ					

Page 2 of 4

	E.W	<i>I</i> . B	RO	OK	ER	8	AS	sc	CI	ATE	ES	LTI	D.		DRILL	нс	DLE	R	EΡ	OR	r			Dŧ	EPA	RT	MENT	OF CKF	PU N7	IBL		NO	RKS	, CAN	ADA	
DW: CKI	BC	LB)	FIEL	D EI	NG:		M DA RI	LTE G	DRILI Ma y	LED] hew	1/3/	73AIR	PHOT	O NO	A22767	7 – 1. xcel	52 lent	to S		E: VE	490 3e ta	3 + 1 TION	80 (l Thi	EST.) TUCE	& B	OF	SET	IFS F	V. 1	208			TEST	HOLE	
			ERY	ION E	BOL								ONNO		ICE	Γ				· · · ·				<u></u>				GRA	AIN - S	SIZE	<u>, ,,,</u>	Ĭ <u>-</u>	Ŀ	MILE	B,C,S	NUMBER
06PTH	MPLE	MPLE YPE	AECOVI	ETRAT	L SYN	S	OIL	DES	CRIP	TION			TS OF	DES	CRIPTION	PEETH		= WA = ICE	TER COI		T (9	(% 6 OF	OF D SAM	PLE	WEIG VOL	HT) UME)	14	LT.	AND	RAVEL	DENSIT	DENSIT	632	s	2
	Ϋź	8 8 7	*	RES	2°⊆ 2°⊆								LIM!					;	20	LASTI LIMIT	(^م ا	•	0	-+ LIQ LIK	UID #IT 0	10	0 <u>01</u> 0	%	%	%	%	¥E†	Υ # Ω Υ = `	A	EMARK	5
	6	И				S (1	ILT TLL)		~				F		NB				-																	
26		-		•	mL to			- : -	same Dry	; (25'	- 49)		Ur	ifrozen	26										-+				[
28					CL				·							28	\Box																			
30	7																		+	-							<u>-</u>									
																30		_	<u> </u>																	
32																32			-							-+										
34								•								34	\Box																			
36	8	И					•																			-									•	
														-	:	36	-																			
38															• .	38								-	_							•				
40	9	\leq														40		¢																		
42												ĺ						+						-												-
																42		1								_	····								•	
44	,	_														44-		-			+					+										
46																46																				
												-						-					-+													
46		1	1				-	_					-			48							-+			+								·		

•

										Υ <u></u>								<u></u>											roge J	
	E. W	/. E	RO	OK	ER	8 A	SSOCIATES	S LTI	D.	DRILL	HC)LE	R	EP	ORI			L)EP/			OF ICKE	PL ENZ	JBL LE	IC \ _HI	WOI GHV	RKS VAY	, CAN	ADA	
CK		<u>.u</u>	TEC		NG:		DATE DRILLED 1	/3//BAIR	PHOT	TO NO: A2276	<u>/ - </u>	52		LINAG	5E: 4	1903	+ 50	<u>(EST</u>	.)		OF	FSET						TEST	HOLE	
F	T	r	1.50	<u> </u>	1	J.	Maynew	[506	TALE	DRAINAGE: EX	Cell	ent	to S	-0	VEG	ETAT	ION	hin S	pruc	e ö.	Birch		ELE	V:	<u>398.</u>	<u>¢'</u>	~			
1			ERY	N NO	BOL				FOUND	ICE							•					GR/ AN/	UN- S	SIZE		<u>۽</u>	۲Y	MILE	8,C,S	NUMBER
0EPT	MPLE NBC	APLE VPLE	ECOV	ETRA'	IFIED SYN	SOIL	DESCRIPTION		EN CI	DESCRIPTION	EPTH FEET		= WA = ICE	CON	ITEN	ENT (T (%	% 01 0F S	· DRY Ampl	E VO	GHT.) E)	A	5	ND	AVEL]§3	SENSI	632	S	2
	S A	8 H 8 H	8	PEN RES	ų į				FR02		°Ξ			P	LASTI	°			QUID LIMIT			a a	0/	2 0/	5	5	PRY (P.	ß	EMARKS	
	-					SILT (1	TILL) – same		U	Unfrozen		<u>†</u>	ŢΤ		Ē	<u>,</u>		T	<u></u>	<u>, '</u>	<u>00 100</u>	+ ^^	<u>~</u>	10	70	<u> </u>	-			
50		\leftarrow				CLAY			F		1		<u>† †</u>			-		-	+	╉┈──	<u> </u>	-								ļ
	10				CL		- silty	L		· ·	50		†°			-+-	-f-		-			1	Ì							
52					to		Plasticity	4.		v								_		<u> </u>		- ·			ĺ				-	
`					C.		- No Gravel		ľ	Trace	52							·		 		1								
54							- Moist				54															• •				· ·
	12	И				÷		. •						L																
56											56	ļ						_]								
`												<u> </u>	╞╌┧╴			_						1	ļ							
58										•	58-	<u> </u>	┝╌┞									- `								
																			-											
60	13	\leq									60								<u> </u>			-								
					Ì							<u> </u>	\vdash									4								
62											62		┝╌╁╌					+	+			-								ł
6.1				ſ								<u> </u>									- <u></u>	-	· .	ŀ						
		$ \neg$									64					-			<u>†</u>			-								
66-	Ĭ							.			~		Î		_							1								
											00							-				1								ł
68		·									68		·								·]			•					
ļ]								
70	15	\leq									70						_										·			
										Ĩ	ļ								\square											
72	ł	- +	+	·-+	╺╺┼╴	· ·_					72			-			. 		$\left \right $			╡┃								
<u> </u>								l																						

P.

.

Page 3 of 4

	E.W	<i>I.</i> 8	RO	ок	ER	8 4	SSOCIA	TES LT	D.	DRILL	нс	LE	R	EP(ORI	-			DEP	AR	MENT	OF	PU	BLI	<u>Ç</u> v	VOF	RKS	, CAN	ADA	<u>4 or 4</u>
DWI	A I	В	FIEL	DE	NG	NRM	DATE DRILLE	011/3/73A	RPHOT	το NO: Δ22763	7 - 1	52	Сна	INAG	F	491	13 + 8	20 /	<u>ст)</u>			UNE	<u>NZ</u>	IE.	HIC	ыни	VAY			
CKD	BD		TEC	н		ŢJ	RIG Mayhe	w SU	RFACE	E DRAINAGE Ex	celle	ent to	5 S		VEG	ETA	TION	Thin	Spru		Birch	361	EL E	V. 2	08	<u>0'</u>		TEST	HOLE	
		<u> </u>	Γ.						l e		T	1					·		0000			GRA	IN- S		30.0	ř	<u> </u>		1	
I=c			E.	lo u	Ŭ B V	604	DESCRIPTI	A 1	1 SU	ICE	1		* 14/AT		CONT	ChIT	10/ ~	E 00	. we	CUT	,	ANA	LYSI	S		ž	È	MILE	B,C,S	NUMBER
	12.5	22	Ś	TAN	5 LE	3010	. DESCRIPTI	UN	0 0	Cookin Tion	151	X	- 16F	CON	UTEN.	сыл Т (%	170 U		7 WE	100001 01.0000	/ 5}	X	5	9	VEL	E NS	Su C	632	s	2
l°≈	N S	SAM	Ĕ	ENE	35				02E		155				LASTE	c.		1			- /	ರ	-	¥ S	GRA	д о Н е	20			
	ļ		*	āē					35				2	0	LIMIY 40	,	60		LIMIT		00 1004	%	%	%	%	¥	2	R	EMARKS	
						CLAN	,													7	T	1								
						CLAI	- 60004	·	r	Ver Trees										+		1								1
1 7	l	<u> </u>			1		- 201110		İ.	A-'ligce	74	1	<u> </u> _+				-+-		-+			1								
	116	\vdash	4							· ·			<u></u>						+	+	+	4								
76	1								1	Î.	76		\vdash		┼──┤			_ <u>_</u>				4								
											ł		\square							\bot										1
78	4									1	78		\downarrow							1	L									ł
						·		, •					1																	
80	17		{						·		0		Į –						Τ	1										-
											00					Ť		-		+		1								.
										•	i i		\mathbf{h}		+								1							1
82	1										82		+																	
													+		┝──┟					–	ļ									ľ
84	1					•				:	84-							_							·					
	18	$\overline{}$)														1	li +	
86											0.0					ļ				T									,	
						END		 ζι			60									-									lugged	
						1.10		,								-			+-	1-					l					
99					ĺ						88				-										ſ		•			
			Í												· · · · · ·	-+				<u> </u>										
90-											90							_	_	<u> </u>										E E
		1					• •			•													ļ	1						
92]								02												1							l l
				Ì	ļ						[]				T	T														
94			·																1	1										
	·										94					-+				+				ł						
													-+			-+			+								İ			
96											96				<u> </u>	-+			+	 										
_				_					1				- 1			- 1				1		I Í	1			- 1	- 1			

	E.۱	W.	BRC	ок	ER	8.	ASS	OCIATES	LTD).	DRILL	нс	LE	RE	PO	RT	}		D	EPA	RT	MENT	OF	PL	18Ľ	IÇ y	NO	RKS	, CAN	ADA	
DW	N: A	LB	FIE	LDE	NG N	NRM	DATE	E DRILLED3/11/	73AIRE	РНОТ	O NO: A22767	-152	2	CHAIN	AGE	40	203 -	80	/ECT			NIA	CK	ENZ		HI	H۷	YAY			
CK) B.	D	TEC	СН		L1	RIG	Mayhew	SUR	FACE	DRAINAGE EX	celle	nt to	S.		T /	ATION	 	Ck S	•/	1	Villow	Aire	l'a	20' V	Vest			TEST	HOLE	
EP			VERY	TION	MBOL	sol		SCOIDTION		FROUND										10	- 30	01	GR	AIN -	SIZE	99.(). 	Ł	MILE	B,C,S	NUMBER
LE L	14	5 8	r 5	TRA	S	30.		LICHIPTION		05	DESCRIPTION	E.		WATE	4 CO	NTENT	໌ (% ໃ	OF	DRY	WEIG	HT }			1	1.	L E	120	IS C	100	-	
100	SA	SAM	Ē	E NE	5 J					115		35	0.		ON I		70 OF	SAN	PLE	VOL	UME	}	3	S.	NVS.	X.	20	20	632	S	3
	Ĺ.		8	z z	ŝ					J K		ł –			LI					U10 1)T			1	+	0/		152	2		FUADE	
—	—			T		0.00	/= 1					<u> </u>	<u>+</u>	20		40	_		80	0		0 100 +	70	70	70	70	<u> </u>	Ľ.	^		
			1	1	GМ	GRA	VEL		1	F							ļ									F I			Banuart	h Creat	
2	ł.,	k	4		-		-	Lt. Brown	Í			2				i	!]		[DOSWOR	I Creek	·
	1.		\mathbf{r}				-	Sandy		1		-	٩							_			1 (10	29	54					
- I -		1 ?					2	Med. gravel			NF		<u> </u>				†						1				Ĺ				
1	1	L			1	<u> </u>	,	_20(iie_21(1	{	ł		4		\rightarrow			┢						4					-			1
	2			[CLAY					NB -		<u>P</u>		7	_								1							
6			1	· ·	CL			Lt. Brown			V - 0-2%	6			Ш						1		ŀ								
1		•			1		-	Silty	.			°									+		1								
1.				1			-	Low Plasticity	'Í	t					-++-	-+															
8	t	1					-	Gray				6			-#					\rightarrow	-		Į	ł							
	•														_1(_																
1 10	3						•		1														1					1			
	Ŭ	1	ן א						- 1		UR:	10			-19-				+												
		ł													-#-				+		<u> </u>										
12		·										12			-11									ł							
															11					ļ											
															11				-+	-											
1 '		k							i	1	•	14								-+							·				1
	4		4				-	Very Silty			•		-+		-	\$}								1							1
16												16				$\langle $			_ 1												-
																1															
		1		1	_	CLAY	(TIL	L)		ſ					1					-+	-			·							
"]				Ē	CL		-	Grey	1			18				-++			+												
							-	Silty				ŀ		_+_										t				ł			
20	5	\square] [. [-	Gravelly			V	20															1				
	ĺ]								Trace																				
2												1			17	1-				+	-+-				1		- {				
"		Í		[22			⊀					-+											
						Quarte	zite F	Boulder - 25'				Ļ														·			0	ite Devi	
24.												24						T		T				1						ne boul	uer
	6				BL							~ †	\checkmark		1-					-+	-+-				[Nou P	ra tor	
						END	OF H	OLE 25'					التي ال											<u>1</u>		1			INEW K	JCK DIT.	
								•						•						-											
																															-

.

.

2

				• • •		· · · · · · · · · · · · · · · · · · ·																					. 1			
DWN	E. V	V. E	BRO	OK		& ASSOCIATES L	ſD.	DRILL	н	OLI	ER	ΈP	OR	Т			DE	PA	RTN				JBL	IC HI	WOI GH\	RKS	, CAN	JADA]
CKD	BD	<u>в</u>))	TEC	H:	<u>40.</u>	TJ RIG Mayhew S	JRFAC	E DRAINAGE Ex	- I: celle	22 ent	to S	AINA	GE: VE	49 GETA	04 H	- 60 - Thi	(EST in Sp	.) Druce	40 -	OF	FSET	FL	FV:	280			TES	T HOLE		1
TH ET)	E R	ω	DVERY	ATION	N BOL	SOIL DESCRIPTION	of GROUND	ICE DESCRIPTION) = WA	TER	CON	TENT	(%	OFD	RY	WEIGH	<u></u>		GR. AN	AIN-	SIZE	309.		ITY	MILE	B,C,S	NUMBER	-
0E1 (FE	SAMPI	SAMPL	% REC	PENETR	S DIC S		IMITS ROZEN		DEPT		_= ICE	co ,		чт (9 ¹⁰ ,	6 OF	SAM		VOLL	JME)		CLAY	SILT	SAND	GRAVEL	ET DENS	RY DENS	632	S	4	
						CLAY (TILL) - Silty	F		<u> </u>			20		0	8		80	<u></u>	100	100	<u>↓ %</u>	%	%	%	*	ā				$\left \right $
2	1				CL	– Lt. Brown – Some Gravel		√. 5-7%	2				P								-						Boswo	rin Cree	ĸ	
4	2								4		<u> </u>	\mathbf{F}	1-																	
6	-								6	F		P										ĺ			ļ.				-	
. 8									8	۵																				
10	3					- Med. Brown		·	10	È											54	37								
12						sand and gravel		NB	12			/					-	_									I			
					CL				12							_											I			
	4	\leq			to CI				14		4																			
6						- -			16										_									÷		
18						•			18-	-	╢╴╢				-															ļ
0	5	\leq				– Grey – Low Plasticity			20-		↓ .																			
2						- Gravelly			22.																	-				
4			_	_+	-	·			24.								-				4									

· · ·

.

• ...*

· -

•

	Ε.	W.	В	RO	ок	ER	8 A	SSOCIA	TES	LTD.		DRILL	но	LE	R	EPO	ORT	•			DE	PAR	TMENT MA	OF CKE	PU NZ	BLI IE	C V HIG	VOF	RKS	, CAN	ADA	
	NI -	ALB	3	FIEL	13 D.	NG		DATE DRILLE	ED11/3/	173AIRP	HOT	O NO: A22767	<u>- 15</u>	52 ent t	CHA	INAG	E VEG	49 ETA	04 ÷	60 (Th	EST.) Druce	0FF 40 - 50'	SET	FIE	V: •	280	~		TEST	HOLE	
Ē	T	Ţ		×	z			ivid ym			ĝ	105	T		• •				-					GRA	IN· S	IZE	209.			MILE	B.C.S	NUMBER
E	E	5		OVER	ANCE	Y N BO	SOIL	DESCRIPT	ION	2	CROU	DESCRIPTION	ĒĒ	0	= WAT	ER	CONT	ENT	(% (OF DI	RY W	EIGHT)	ANA	LTS:	<u>ه</u>	Ę.	HSITY L	NSIT)	400		
18	SAMP	8108	TYPE	REC	ENETE	UNIF I					OZEN		195		= ICE	CON	ITEN' Lasti	r (%	o OF	SAMP	יעב יי נומטוו	VOLUM D	E)	5	ŞIL	SAN	GRAV	ET DE (PC 4	30	032	3	4
	+-	4		*	ĨĨ	"					3 2			ļ		<u>م</u>	LIMIT 4(<u> </u>		, 	LIM2 80	r 	100 100	%	%	%	%	3	5	R	EMARKS	
							CLAY (TILL	Y)			F	NR		<u> </u>	₽				-+	\rightarrow	-+-											
2	6					to	(- same			•		26					\dashv						1								
		,	\neg			CI												-			-			1								
2							END	OF HOLE 2	28'				28		.								1									
3	0												30																			
														 			-			\rightarrow	_											
3	2												32					_	+				ļ									
												•		<u> </u>				†	-+				<u> </u>									
3	4		1										34							-+	-+	-+										
١.										Í			20						···		+											
ľ	Ĭ												36						·					1								
3	8							•					38																			
Į																			_				l									
4	9												40								_								·			
																				-+												
⁴	2			i									42-						-+													
4	4																Í					-	1	1								
ľ							1																									
4	5						•						46					_				. 										
																			-+				ļ				•					
4	3												48					\dashv					<u> </u>									

Page 2 of 2

] {	Ξ. γ	Y. E	BRC	ЮК	(ER	8	ASSOCIATES	LTD.		DRILL	но	ד ונ	1	PED	<u>np</u>	Ŧ	<u>}</u>		DEF	AR	TMENT	OF	PI	IRI	IC 1	NO	RKS		ADA	or z
DW:	A	LB	FIE	LD E	NG	NRA	A DATE DRILLED 11/3			O NO:							<u> </u>				MA	<u>CKE</u>	NŽ	IE	HI	<u>SHV</u>	NAY	, CAN	AUA	
CKD	B	<u>D</u>	TE	CH ·		Ţ,	RIG Mayhew	SURFA	ICE	DRAINAGE Ex	cell	ent f		AINA		49 GET	205 + 2	<u>0 (E</u> Thia	<u>ST.)</u>		0FF	SET	1		- 0 -			TEST	HOLE	
		ł	 	z					ę			T	<u> </u>			0211		mic	к эр	ruce	20 - 50	684	ELE	V	<u>381</u>	<u> የ'</u>			r	
₹E	u S		X EN	ATIO	0 BN	so	L DESCRIPTION	5	EQU:	ICE	2~		= 902	TFD	CON	TENT	10/ 01					ANA	LYS	IS .	_	<u>ع</u> ا	ž	MILE	B,C,S	NUMBER
10	LAND UNB	YPE YPE	U U U U	ETR	L S)			5	Z		EPT.	۱ŏ	= IC	E CO	NTEN	IT (9	% OF S		I WIC LE V	.16#1 0:11M) F)	¥	5	9	VEL	ENSI C	ENSI	632	S	5
	ΰž	SA	*	PEN	500	•		LIMI	ROZ		105			P	LAST	ю <u>–</u>		i			- /	5	ŝ	SA SA	GR.A		20	ļ		
		†	+	<u> </u>	07	PEAT	- Dk. Brown					+		20			<u>60</u>	· ·	BO		00 100+	%	%	%	%	ž	5	R	EMARKS	
							<u> </u>	''		NB		 				ļ		_ <u> </u>										Boswor	th Cree	k
2	ł	\leq	1	.		CLA	Y (TILL)			V .	2	<u> </u>			ļ															~
1 (?]		CL		- Lt. Brown			5 - 7%	ĺ	<u> </u>	ļ	<u> </u>		0		_]		
4		Ι.					- Some Grovel				4	A				<u> </u>												ĺ		- 1
	2	\leq]											1		[!				1		
6			1				•				6.	<u> </u>								1		·		İ				ł		
		•			1				Ļ		Ť				V_{-}															
8					CL		- Med. Brown	I			я.				ſ					1										1
							- Silty			NB				$\overline{7}$					1	1										
101	3						- Low - Med.							V					1	<u>†</u>	···- ·							-		•
	Ť				10		- Some Gravel				10			Î				+-	-	+				· .				· ·		
12	Ī				ci														+	+								F		2
				ľ							12-			1-1				+					ĺ							1
]			- 1			İ		1				╂───				+-	+	╉┉┥										
•	٨ĥ	\neg		[•	<u>^</u>		ľ		-14																ļ			
	╶┝	ျ			İ		- Grey			ł	ł			<u> </u>																
[0]							- No Gravel	יעי <i>ו</i>			16		<u></u>	[]_]		_				 										
										·	ŀ		·	┞┦━┦																
181											18-			[4									- 1			
	Ĺ			-	CI		- Dk. Grev								_															
20	5 [to		- Med. to High		-		20+																			
			Ī		СН		Plasticity	1	Į	NB -	ļ							1							Ì		Ļ	ocket D	onatra-	
22	Í						- Silty		F	V T	224																[1.36	rnerrom ⊧tsf	eler
								:		Irace								Γ							.					
24	⊢	-+	- +	-+					L		<u>_</u>										{				ľ					
											<u> </u>							1							·		- 1			

•	E.V	V. E	BRO	ок	ER	8	455	SOCIA	TES	LTD	-	DRILL	но	LE	R	EPO	ORT	·		D	EP4	ART	MENT	OF	PU	BLI IE		NOF	RKS	, CAN	ADA	of 2
DW.	N At BD	<u>B</u>	FIEL	D E!	NG	NRM TJ	DAT	E DRILLE May	.011/3/1 hew	73AIRP SURF	ACE	O NO: A22767 DRAINAGE: Ex	-152 celle	2 ent to	CHA S	INAG	E: VEG	49()5 + 2	0 (ES 20 -	57.) - 50'		OF	FSET	FIF	V. 2				TEST	T HOLE	
			RY	2 W	or						DND	ICE												GRA	UN- S	IZE	01.0	·	,	MILE	B,C,S	NUMBER
DEPTH	MPLE	UPLE VPE	RE COVE	STANC	SYME	SO	LD	ESCRIPT	ION		S OF	DESCRIPTION	EPTH EET)	0	WAT	ER (CON	CONTENT	ENT (r (%	% OF OF S#	DRY	WER E VO	GHT) LUME)	N N	5	07	AVEL	DENSIT	DENSIT C.F.)	632	S	5
	N C	SA SA	*	PEN	S O IL	•					LIMIT FROZ				2	ר אין ס	ASTIC		60		QUID Imit 80	10	001 0	%	%	5 %	8 %	ΨET 	Pay Pay	F	EMARK:	s
	6	\geq			CI	CLAY (TILL	5 -	Same			F	NB to			_	Ļ		-		1	F			-					1			
20	1.	ŀ										V-Trace	26								1				ļ							
28													28	$\left - \right $		+				-	ļ				ĺ			•				
30	7	\vdash											1					-		+-	+			1								
	ľ	->											50	\square		Ĭ			\square													
32													32		-	+	\rightarrow	+		+			<u></u>	$\left\{ \right. \right\}$							•	
34													34					-														
	8	\geq														┢╎		_														
36													36																			
38													36		_		_															
40		_												\vdash		┼┤	-	+								•						
	. 7												40																			
42				ĺ					•				42			$\left \right $						-+		$\frac{1}{2}$								
44			-										44		·	+																
											ŀ								_													
46													46			-		+	+-	-			··									
48	10	\leq		_	_	CLIC							48																			
40	[END	OF	HOLE 4	8'				48		- †		+															

	E.W	/. E	BRC	ок	ER	8	ASS	SOCIAT	ES LT	D.	DRILL	но	DLE	R	EPO	ORT	•			DEP	AR	MENT	OF	PU	BLI	C V	VOF	RKS	, CAN	ADA	
DWI	i A	LB	FIE	LDE	NG	NRA	DAT	E DRILLED	1/3/73 AL	RPHO	TO NO: A22767	- 15	2	СНА	INAG	F: 49	008	+ 20 7	Fet			MA	UKE	<u>IVZ</u>	IE .	HIC	н	YAY			
CKD	Bi	Ο.	TE	СН		ΤJ	RIG	Mayhew	SL	IRFAC	E DRAINAGE: F	nir te	W			VEG	FTA		5			C	SEI	F 1 F 1					TEST	HOLE	
Ì		-								6	<u></u>		<u> </u>						Spar	se As	pen	Sabrings	1004	ELE	175	360.	<u>0'</u>	1	<u> </u>	r	
1.0			E	No B	BO					NR NR	ICE												ANA	LYSI	S		~	2	MILE	8,C,S	NUMBER
E E	2.5	ي تر	l S	TAN	SYN	50	IL D	ESCRIPTIO	•	ō g	DESCRIPTION	Ĕ£	0	= WAI	TER (CONT	ENT	(% 0)	FOR	Y WE	IGHT)	-		•	đ	Lis ~	5~	422		
1ª E	NN N	ANP	2	NET SIS	L NL	•				15 ZEN		PEP		ICE	CON	TEN	r (%	OFS		LE VO	DLUM	ε)	LA.	1	AN	RAV	50	30	032	2	0
ļ		۳	8	2 2	° - 8				•	E M		1			PI	LASTIC	, –		1 ⁴	LINIT				~	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		5	25		SHARK	
						CLE	AN	ICE					┾	Z		40		<u>60</u>		80	·'	00 1004	70	70	70	%	-	Ľ.,	"	LIMANNO	
	Į	1				CDA	1/61			-			├ ─── 						_	_		·							Recurs		.
2	[.			1		0.04	VEL	Mad 8.		1	· · ·	1 2									1	l I						[]	Doswor	TR Cree	kon
1	1				GW		-	Sandy or	own wl.elew			-		9							1	<u> </u>	1						Figr in	Midale	or
			F	[1		-	Some Si	t ciuy	Į	NF			[+		1						vaney		
-								:	•	Ē		4	<u>+</u>				\rightarrow				+		{ .								
	2			!								$\left\{ \right.$	┝				-+				ļ		(1	1)	21	68					. 1
6				[0		6		\mathcal{F}			·												1		
							-	Free Wa	er		Unfrozen			Δ				ļ	i												
6			F	i i							0			$\overline{\mathcal{N}}$			-				1		1								
	2											8		-1			\rightarrow				+										.
1	~			1		ELID	00			+		1	┝─╂		0						 	<u> </u>					ļ	Í			
10				ſ		ENU	OFI	HOLE A.				10	┝╌┼				_ļ				<u> </u>										
		i	1				-																				1				
12	1													1				•													
												' 							-1-	+	+					1					
																	-+				+			- 1							
14	- 1											14	┝──┟				+										[
						•											_														
16																										1	į	•			·
																				-	1	•	ĺ			Ì	- [
		1															-+		+-									1			
"	- 1											18-		+			-+	-+-	-+-												
- 1			· .		1						•			+			-				_		1								
20					Ī							20-														Ì	f				İ
					,							- -						· [1						-
22	ŀ				1								Γ	T						1	1.										
	•											22		-+	-f		+			+											·
1												i I												- 1		·	1				[
24	ł											24	<u> </u>	_			_		+							1					Í
							_							f				1					1	-	1		- 1	1			

.

.

									T				_															rage	or 4
	E.\	W.	BRC	OK	ER	8 A	SSOCIATES LT	D.	DRILL	HC		ER	EP	ORT			D		RT	MENT MA	OF CKE	PU NZ	IBL. IE	IC V HIC	VOF	RKS	, CAN	ADA	
0)	TEC	H ·	NG:	TJ	RIG: Mayhew SU	RFAC	to no: a22767 e drainage: Ex	celle	3 ent	to N	AINAG	SE: VEGI	4910 TATI	+ 30	(EST nick	.) Spru	ce 40	0FF 0 - 50'	SET	ELE	v	281	~		TEST	HOLE	
			ž	Nou		Ì		UND	ICE		Τ										GRA	IN- S	SIZE	<u>+ 195</u>	<u> </u>	<u> </u>	MILE	B,C,S	NUMBER
DEPTH		PLE PLE	ECOVE	TRATI	FIED	SOIL	DESCRIPTION	N GRO	DESCRIPTION	PTH EET)	2) = WA' \ = ICE		CONTE	NT (9 (%)	6 OF		WEld	SHT)	ì	*	5	2	VEL	ENSIT	ENSIT F.	632	s	7
	- S	SAM	<u>}</u>	PENE	SOL	•.		FROZE		55			P	LASTIC						•	5	5	8	2 2 2	VET D (P.C	RY 0 (P.C		FMADKS	
	1-	1	1	 		CLAY	· · · ·				╈		<u>~</u>	40		<u> </u>		<u> </u>		0 100 1	, 70	70	%	70	-				
	2				CL		- Lt. Brown - Silty		v	2	E										1	-			ĺ		Boswo	rth Cree	ek
		P	4				- Low Plasticity		5 - 10%	-		<u>e</u>	<u> </u>			-						İ							
•	•	Ľ					- Grey			4	┝╴	<u>s</u>	\vdash	+	-{-						{								
	2	P									\vdash				+	+	+												
			<u> </u>							6											1						1		
	•					SAND	- Lt. Brown			8-	₋		arphi			·													
					SP		- Coarse - Med.		NF		┝	+/	<u> </u>	┝╌┼	·														•
["	"	P		2			- Trace Silt			10	†	11-			+	+	+	-	-+		1								
1										12-																			
	ĺ								. 1		L																		
14	4									14	 			┝─┼╸			$\left \right $												
	4	\geq									┝	- ¢																	
										16										· · · ·									
18	PI									18-		ļ																	
														┝╍┝	-		$\left - \right $	_	-+						•.				
20	5	\vdash			·	SILT (T	ILL)			20-	\vdash			┝━╌┼╴		+	$\left - \right $	-+											
22					ML		- Lt. Grey - Clavey			22-										· · · · · · · · · · · · · · · · · · ·	1								
							- Some Gravel					\mathbb{A}			_														
24		F	+-	-	┝─┤		_ Low Plasticity _		<u> </u>	24		++		┝╌┼╸			$\left - \right $	_											

Page 2 of 4 DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY E.W. BROOKER & ASSOCIATES LTD. DRILL HOLE REPORT NRM DATE DRILLED12/3/73 AIRPHOTO NO: A22767 - 153 CHAINAGE FIELD ENG DWN: ALB 4910 + 30 (EST.) OFFSET TEST HOLE SURFACE DRAINAGE: Excellent to N CKD 8D TECH TJ RIG Mayhew VEGETATION: Thick Spruce 40 - 50' ELEV 384 0 OF GROUND GRAIN - SIZE MILE B,C,S NUMBER ICE ANALYSIS WET DENSITY (P.C.F.) DRY DENSITY (P.C.F.) DEPTH DEPTH (FEET) SAMPLE NUMBER SAMPLE TYPE PENETRATI RESISTANCI UNIFIED SOIL SYMB DESCRIPTION O = WATER CONTENT (% OF DRY WEIGHT) SOIL DESCRIPTION DEPTH (FEET) RECOVI GRAVEL \$AND CLAY △= ICE CONTENT (% OF SAMPLE VOLUME) SILT LIMITS FROZEN 632 S 7 LIQUID LIMIT 80 PLASTIC * LIMIT REMARKS % % % % 20 60 100 100+ SILT 6 - Light Grey (TILL) F NB - Gravelly 26 26 - Dry ML - Non-Plastic 28 28 30 7 30-32 32 . 34 34 8 36 36 38 36 CLAY. 40 9 - Grey, Silty 40 CL Low Plasticity ۷ 42 Trace 42 44 44 10 46 46

Page 3 of 4

Ĺ	E.\	N. I	BRC	ок	ER	8 A	SSOCIATES	LTC).	DRILL	НС	DLE	REF	POR	Т		1	DEP	ART	MENT	OF	PU	BLI	<u>Ç</u>	NOF	RKS	, CAN	ADA	
DW	NEA	LB	FIE	LO EI	NG:	NRM	DATE DRILLED 12/3	7BAIRI	РНОТ	O NO: A22767-	153		CHAIN	GE	- 1	010 +	20 /6	CT \			UKE	NZ		HIC	SHV	<u>YAY</u>	_	-	
CK	<u> B</u> E)	Τε	CH		IJ	RIG: Mayhew	SUR	FACE	DRAINAGE: Ex	cel	ent t	0 N	VF	GEL	ATION:	<u>JU (C</u> Thic	<u>21.1</u> 2505		$\frac{10}{40} = 50!$	SEI	C 1 C 1		201			TEST	HOLE	
-			CRV	LON CE	BOL				QNND	ICE							11110			10 - 30	GRA	IN- S		384	<u>0.</u>		MILE	B,C,S	NUMBER
DEPT	MPLE	MPLE	ECOV	ETRAT	SYN	SOIL	DESCRIPTION		S OF	DESCRIPTION	EPTH EETH		WATER	CON	TENT	'(%0 %0Fs	F DRI Sampl	r WEI .e vo	GHT)) E)	X	5	Q	IVEL	ENSIT	ENSIT F.)	632	5	
	SA N	S.	8	PEN	ч г с с	•••		•	LIMIT FROZI		<u>م</u> ک		•••	PLAST			i	IQUID LIMIT		- '	נד א	6 SI	A SA	P CR	ET D	0 4 0 0 4 0	002	FMARKS	<u></u>
					CL	CLA	Y .						Ť	<u> </u>	Î.			1		00100+		70	70	70					
50	h1		1.				- Same		F	V~ Irace	50													•					
									۲ I	Unfrozen						<u> </u>													
52	1										52	┝──┼				┠──┠─													
54			1				· ·		ł		54			1	<u>.</u>	<u>}</u> }-		+				ĺ							
	12		1								94																		
56								Ē			56																		-
										•			-/																
									l		58		/ -	1				+				-							
60	13	K			j						60-	(·						ĺ							
										-						· .					Í								
62					-						62		┝╌┟──					+											
64						-							┼┼─					+								ĺ			
	14	И							Ì		041										ł								-
66											66			 							ļ				Ī				
68													-\-					+								j			
~~								· F	U		68 -							+											
70	15	\leq			ľ		- Grey - Silty		to F	Unfrozen-	70																		
							,				ŀ			┨─┤			_								·				
72						_				[72	÷	-+	$\left - \right $				┝╼┥				·							

Γ																				_										Page 4	of 4
	E.\	<i>N.</i> (BRC		ER		AS	SOC	JATE	S LT	D.	DRILL	НС	DLE	RE	EPC	DRT			DE	PAR	TMENT MA	OF CKE	PU NZ	BLI IE	C V HIG	VOF	RKS	, CAN	ADA	
			TE		NG	TNKIV	I DA	TE DR	ILLEO 4	-/ J/ / JAI	RPHO	TO NO: A22767	<u>-15:</u>	3	CHA	NAGE	:	4910	+ 30	(EST,	.)	OF	SE T								
F	<u> </u>	<u>-</u>	1121	1	·	11	RIG	<u>): N</u>	<u>layhew</u>	SU	RFACI	E DRAINAGE EX	celle	ent to	N		VEGE	ATIO	N: Th	ick S	pruce	50 - 50 ¹		ELE	V: 3	384.	0'		TEST	HOLE	
I = :			ERY	NOI	BOL						OUND	ICE				_							GRA	IN- S	IZE S	_	٤	2	MILE	B,C,S	NUMBER
DEPT	AMPLE	MPLE	RECO	ETRA	VIFIED L SYN	. 50	12. 1	DESCH	GPTION		EN GF	DESCRIPTION	FEETH		ICE	ER C	ONTEN TENT	T (% (% OF	OF C SAN	DRY W	EIGHT) IE)	LAY	L.	AND	AVEL	DENSI	DENSI'	632	s	7
	vi 2		*	PEN	5 C	``					LIM:				20	PL.	ASTIC				D T	100 100	%	° %	3 %	د %	WET	Υ ^R Ο	R	EMARKS	
						CLA	(-	Sor	ne		Τu		1		Ī	TT	Ť	<u> </u>	Ĩ	Ť	1	1 100-									
1_				ļ							to	Unfrozen			+	┈┼╶┼			+			<u> </u>	- 1								
'	*1			·							F	to V-trace	74	1		+		+				+	-								
7	5		•								Î		76								_										
		[1									Į				TΤ		1					1								
71	14	K	ł					•			1	-	-			Π						<u> </u>	1 ·								
			١										78.								1-										
80													80					-				_	1								
	ĺ.						•															1	1								
82				1 17			•	•					92		Τ							1		Ī							·
							•						92															İ			
64																		1			-		1								l l
							_						0.4		_			1			_		1								ŀ
86						END	OF	HOL	E 85'						_							1	1		İ						
		[•	86		-1						-1-										
88																	-					<u> </u>									
													88		-+	-						<u> </u>									
90																								ĺ							
													90			+														•	
02													Ì		-+-	-†			┝──┼	-+-											
													92			-		┝╌┥										· •			
94													ľ	-	-†			┼─┤													
													94		-+-	+		┼─┤													
96																-†-										1					
30.												ĺ	96			+				+											

• •

	m 11		200																	T												<u> </u>	agelo	f 2
	C. Y	V. 1	BRI	JOK	ER	8	AS	so	CIATE	ES	LTD).	DRILL	- H (OLE	F	REP	OR	Т			Di	EPA	ART	MENT	OF		ΪËΓ	IÇ <u>)</u>	NÖ	RKS	, CAN	ADA	
DW	NEA	LB	FIE	LD E	NG	NR	V DA	TE DE	RILLED]	2/3/7	73 AIRF	нот	O NO: A22767	-153	3	Тсн	AINA	GE:	·	4911	+20	/FS	Υ γ					15	HI	<u>5HV</u>	<u>VAY</u>			
CKI	<u>) B[</u>	<u>}</u>	TE	CH :	·	TI.	RI	<u>G:</u>	Mayhev	w	SURI	FACE	DRAINAGE	Exce	llen	t to	N	VE	GET	TION	t: Th	ick.	Spru	100 4	10 - 50 ¹	1301	EL	FV: ·	205	<u></u>		TEST	HOLE	
			1×	z	1						Ì	QN	105		Т			• • •					<u> </u>		<u>v</u>	GR	AIN-	SIZE	272.	ř–	T	 ,		
1EB	u e	141	VER	ATIO NCE	a	s	ᆡᄂ	DESC	RIPTION	4		PE SEOU	DESCRIPTION	=	$\cdot \mid \circ$	= WA	TER	CON	TENT	1%		NPV	WEIG			AN	ALYS	IS		Ε	ž	MILE	B,C,S	NUMBER
105	4	MPL V PL	z ž	STA STA	S S						}	s N		143	ے ا	= ICE	E COI	NTEI	NT (9	% OF	SAN	IPLE	VOL			X	5	2	VEL.	182	ENS	632	S	8
	ŏ ž	S. ►	- 8	RS S R	5 õs							TIMI TO2		105	-		P	LAST	ue 🛌	-			UID				ŝ	× S	R.	100		┞╍╍╍┙		
-	+	╆	-	╈													20	CIMIT	40	6	0	' LIA 81	41T 0	:0	001 00	, %	%	%	%	×	8	R	EMARKS	
1	ĺ						Y				Í	F																	\square					-
2		6	4				•	- Lt. . cti	. Brown	า				,					1							1	Ì					Boswor	th Cree	k
	1'	\vdash	4					- 511 - 10	⊪ry w Plast	ticity			V ·	*				1	P							1								
4			ľ	[iony	İ		7 - 10%					†	¥—				-		·····	1								
	2	\vdash	-		1	•								4		¥		17	1	·						-	1							
6			4									Ì				1	f	ŀ¢	<u>+</u>					+		ł		ľ						
ļ°]					-						ŀ		6			<u> </u>									-	İ			1 7				
1.													NB						i					-+		-		ł						
5	İ													6	<u> </u>		┨────	H										ĺ						-
			ļ								Ì			1	<u> </u>	<u> </u>	ļ	¥	 ;	┝──┨														•
10	3	\leq]		lcı İ			Gr	-	ad			•	0	L	 .		l																
I					 			Pla	stic	JU .		[Ĺ		ĺ						- [ł						
12				ł				• • •						1.2				$\left \right\rangle$						1		1								
			1											1 "		-		$\mathbf{\Lambda}$					_							1				
14													-	İ				1		_			-+											
														14												í	ļ				ı İ			· · · · ·
	1																	-1			-+	\rightarrow	-+					•						
														16	 			-						-+-										
•															┝───			+					-		<u>-</u>									
18	ŀ									•			:	18-				4																
												ľ			<u> </u>		4																	
20	5		\vdash			SANU	<u> </u>			<u> </u>		-	···· <u>········</u> ··	20-	[•													ŕ		Ī	Sample	not	
	- [JAIN	· -	1+	Brown			ł					\square										ľ				ł	Grovel	Stave In	as Hala
22					SP		-	Coo	arse - /	Med.			NF	22.		/															·	Sand Bl	ows Out	
					1		-	Gro	velly							7						1												•
24	ļ			_	_ [_Trag	<u>ce Silt</u>							71					-+		-						Ì					
												T		24		/					-+	-+	-+											

٠

٠.

.

.

									····							r												P	oge 2 o	f 2
	E. V	V. E	BRO	OK	ER	& ASSOCIATES	LTD).	DRILL	НС	DL	E F	REP	OR	T			D	EPA	RT	MENT MA	OF CKE	PU ENZ	IBL IE		NO SH\	RKS NAY	, CAN	ADA	
СКІ	<u>`</u> A)B[2	TE	H.	NG	TJ RIG Mayhew	2/73AIRF	FACE	O NO: A2276	7-15 (cell	53 len	It to N	AINA V	GE:	49 GET#	1 +	20 (EST ick) Spru	ce 4	OF	SET	ELE	V:	205			TEST	HOLE	
			RY	δu	BOL			QNNC	ICE		Γ											GR	AIN- S	SIZE		ľ	,	MILE	B,C,S	NUMBER
DEPT	MPLE	KPLE KPLE	E COV	STANC	SYM	SOIL DESCRIPTION		S OF	DESCRIPTION	EPTH (EET)		O ≠ ₩/ ∆= ici	TER E CO	CONT	FENT FT (9	(% % 0F	OF I	DRY IPLE	WEIG	HT).UME)	A	5	9	AVEL	ENSIT	ENSIT	632	S	8
	S A	SA	*	PEN	10s			L IMIT FROZ		^ 2			1 20	LIMIT					UID	•		5 %	5 %	3 %	8	WET (DRY (R	EMARKS	
	6					SAND		_			T	1	Ī		Ľ					Ĭ	0_1004			-	<u> </u>					
26			.	ľ	SP			Г	NF .	26	5 - -		╞	ļ																
28			ĺ						-		\vdash		+	╂—					_											
							Í			28																				
30	7	\leq								30	+	-			·															
32		ľ.									╞	+-	+						-	-+										
										32																		Hole Cavina	@ 33'	·
34						END OF HOLE 33'				34	-						_													
36											┢	+	<u> </u>			•				-+										
										36																				
38										38			<u> </u>	$\left - \right $						_				1						
40						•					┝	+		$\left - \right $				-+	-+	-										.]
										40									_											
42										42					-				_	_										
44											-						-			-+-										
										44.4																				[
46				ļ						46							-	-	-+ [:]											
48																	+		-+	+			Ì			_				
										40						-			f-			- 1								1

E.	W.	8	RC	OK	ER	8	A AS	SOCIATES	LTD.		DRILL	Н	OL	E	RF	POF	₹Т	1		0	EP/	ART	MENT	OF	PL	JBL	IC 1	wo	RKS	CAN	Poge JΔDΔ	1 of 2
WN:	<u>\L</u>	3	FIE	LDE	NG			TE DRILLED 12/3	/7\$AIRPI	нот	0 NOA22767-	153			HAIN	AGE			- 00	(557	<u>.</u>	····-	<u>M</u> /		ENZ	<u>.IE</u>	H	GH	HAY			
CKD BI	- -		TE	<u>сн:</u>	<u> </u>	I.	j (R)	G: Mayhew	SURF	ACE	DRAINAGE: Ex	cel	len	it to	Ν.	V	EGE	TATIC	N: T	hick	spru Spru	ice 4	0 - 50'	521	ELE	V:	398.	0'		TES	T HOLE	
			ERY	N UN	j j					ONNO	ICE													GR	AIN- :	SIZE		 	 _	MILE	B.C.S	NUMBER
MPLE	N DE A	a Ja Ja	E COV	TRAT	SYN		SOIL	DESCRIPTION		5 8 8	DESCRIPTION	PTH		O = ₩ Λ = id	IATE Ce c	R CON	NTEN 'NT	IT (% (% 0	OF	DRY	WEI	GHT)		*	<u> </u>	e l	Ę	LISN:	ENSIT	632	s	9
- ₹	2	\$Å	*	PENE	N DS	1.				ROZ		ē;		<u> </u>		PLAS	TIC -				- 0	LONAL	.,	5	1	Š	GRA		20	 		
	+					$\frac{1}{c}$	LAY					+	┿		20		40		<u>60</u>		10 T		001 00	+ %	%	%	%	3	ă	ļ'	EMARKS	\$
2							-	- Lt. Brown			ν.						+-			+	<u> </u>			_		ľ				Boswor	th Cree	k
-11	F	\geq			CL		-	 Silty Low Plasticity 			7 - ,10%	*	2	8						+	<u> </u>			-								
4							-	- Some Gravel	,	ļ					┢			+-	+-	+		┝╾┤	- <u></u>	- ·								
2	k					ŀ						1	1		1	X	+-	1	1-	+		<u> </u>		1								
6																																
8																																
0 3																																
						[-	Grev					\vdash			-∦			<u> </u>	<u> </u>				1						ĺ		
2			i				-	Silty				12	:+		+-				╂-—	_			· · · · · · · · · · · · · · · · · · ·	4								
		ſ					-	Low Plasticity	/				\vdash		+-		+	+												 		
14	k	-								ŀ		14	+		+-	-#				 										1		
s	\vdash	7									V		\vdash		+		+	+				-+				•			÷.	Į		
											Trace	16	t		╀		┢	+	 -											1		
3												10	Γ					1	<u> </u>				· · · · · · · · · · · · · · · · · · ·	1		ĺ						
												10												1								
5	Þ											20		Ē								_					·					
													L		1																	
2												22	_				 	<u> </u>	L													
			ł						.				ŀ	<u>.</u>	+	-#	 		 								. •		ŀ			
4	F	+	-+	· –†	\neg		• • • •			-		24	┢		+		 	╂														
					I .					<u> </u>			L		1	Ш.	<u> </u>	I														

· ·

•

. .

•

2

٠

.

Γ.				014				1 77 0	Ť									DE	DAG		NT		DI				NC	CAN	ADA	
	W	/. E		UK	EK	a AS	SOCIATES				HO	LE	R	EPO	RT				.rai	V I 1910-1	MAC	KE	NŽI	E	HIG	SHW	AY	, CAN	AUA	
DWN		_8	FIEL	DE	<u>NG: </u>		TE DRILLED 12/3/	78AIRPH	IOT	O NO: A22767	-153		CHA	NAGE	49	1 + 9	<u>0 (E</u>	ST.)		70 57	OFF	SET						TEST	KOLE	
	ви	ŕ—	120	.n		J IN	o' Maynew	SURFA		DRAINAGEEXC	lier		N.	l	VEGE	TATIO	N: In	ICK :	spruc	e 40-30	<u>.</u>		ELEN	/: 3	<u>198. (</u>) i				
			RV	δw	ğ				No.	ICE	ł					_						ANA		22 S		2	2	MILE	B,C,S	NUMBER
EPTH	9 C 8	ي بي	COVI	TAN	IED.	SOIL	DESCRIPTION	5	5	DESCRIPTION	E		WAT	ER CO	ONTEN	T (%	OF C	DRY 1	WEIGH	T)		2	ь	ę	VEL	E NSI	L) SI	632	s	•
5 P	SAM	AMP TYP	2	NET	OIL UNIF			11S	OZE		5 2 2 3	0.	ιυc	PL	ASTIC	176 Ur	SAN		עטבט וומ '	INC I		3	ŝ	5A)	GRA	T DI	20 24			إحصرك
		Ĺ	×	āæ	ŵ			5					Ż	, LI	MIT P 40		60		11 7	_100	100+	%	%	%	%	WE	5	R	EMARKS	
	6	k	1			CLAY	- some	l i	۶İ	V-Trace																				
26			Ì								26]																	
						SAND																								
28					SP		- Lt. Grey, fin	e grdin	het		20																		i,	
					to		- Non-Plastic	,		NB	. 20			ĺ				Ţ											'	
30-		\leftarrow			SM		- Dry	`			30													ŀ		·				
	7					-							ľ																	
32				1							70		Ш																	ŀ
						•					32												1							.
34										•			П			—						N								
											34		11							-		Ì								
35	ļ												TT			· 1	1-1	_												
	l										36		\top			1													•	
70	8							·					\uparrow			1.		-												
~	ĺ					END OF	HOLE 38'				38		°†		-+	1														
						·				-			+			+														
*											40		-+			+	1-1		\rightarrow	-{						ł	•			
42													-+				<u> </u>					Ì								
72											42					+	┼┼													
										'			-†			1														
**]											44			-+-		+		\neg												
4						•		[ŀ	-+	-+			+		-+												
70											46	-+	-+	-+-		+	┼──┤	-+	[-											
											ŀ	_	-+				┟──┼													1
45											48	-+	-+			+	┼──┼	-+												

--

r		-	_											<u> </u>					··		<u>.</u>							Page 1	of 2
	E. W	/. E	RO	OK	ER	8 A	SSOCIA	TES L	TD.	DRILL	НС)LE	RE	P0	RT			DEF			OF CKE	PU NZ	BLI	C V HIC	VOF	RKS	, CAN	ADA	
CKE		<u>-B</u>	TEC	<u>. U Еі</u> ;н:	NG		RIG Mayhe	w	SURFACE	DRAINAGE FY	-153	3 Int to	CHAI	NAGE	4	212 + (00 (E	ST.)			SET	125	WE	ST			TEST	HOLE	
		ļ	1.					<u></u>	9		Γ				LULI			<u> </u>		10 - 50	GRA	IN-S		96.0	0' 	— —			
Ξ÷			VERY	NCE N	0 W.	SOIL	DESCRIPT	ION	DF.	ICE DESCRIPTION	II.	0	= WATI	ER CO	NTEN	r (%	OF O	ay w	FIGHT	,	ANA	LYSI	s		11	Ϋ́	MILE	B,C,S	NUMBER
DCP.	MPL	APLE V PE	RECO	E TRA	SY				S S S		FE ET		= ICE	CONT	ENT (% OF	SAM	PLE V	OLUM	, E)	T AY	5	AND	AVEL	DENS	C.F.)	632	S	10
	ΰź	₹\$ F	*	PEN	2 2 2				LIMIT		102	ĺ	20	PLA					? `.		%	" %	%	5 %	WET	DRY P.	R	EMARKS	
						CLAY			F	V			ΠŤ		Ť	ŢŢŢ	Ť	Ť	- <u>-</u> -	100 100 +									
2					CL		- Lt. Bro	own		0 - 5%										1							Boswor	th Cree	k
1 -	1	\triangleright					- Low P	Some Gra lasticity	ivel	, , , , , , , , , , , , , , , , , , ,	2		e							1	t I								
4				1			-			NB [,]				X						1									
1	2	\vdash	1			:	- Grey								X				-										
6	~		1		to		- Low -	Med.	f		6																		
		ŀ			Ci		Plastic	ity			Ĩ																		
8										-	8																		
										·									_										•
10	3									17-70-509-	10			-							·								
										V 40-30%					_ /				· .										ļ
12.										•	12				_/	· ·								·					
															Д_	l.													
14-											14-																		
	4	\geq										-		{		┣──┦		_ <u> </u>					Ì	Ì					. 1
16-									· ·	V - Trace	16 -															·			-
				ľ									-+-			+					ĺ								
18-	Í										18-					┥─┤													1
										•			-+				-+-												
20	5	\Box									20-				╞╌┼──					·				Ī					
																										Į			
22.		ļ									22-		-+	-+-		+										ſ			
																┼╍╍┼													
24			- 1	- 1	-				+ +		24-		-+	-+	+-		-+	-+											1

Page 2 of 2

	E.V	V. E	BRC	юк	ER	a /	ASSOCIATES	LTD.	DRILL	нс	DLE	RE	POF	۲۲.		D	EPAR	TMEN	T OF	PL	18L		NOF	RKS	, CAN	ADA	
DW	N AI	.В	FIE	LD E	NG	NRM	DATE DRILLED 12/3	73AIRPHO	TO NO A22767	-153		CHAIN	GE:	10	$\frac{1}{2 + 00}$	(ECT	~~~~~		FEET	12	51 14		2114	TAT			
СК	D RD		TE	сн∘		LT	RIG Mayhew	SURFAC	E DRAINAGE E	cell	ent to	N.	Tv	EGET	TION: T	nick !	Spruce	40 - 50	1		5 99	esr 20(TEST	HOLE	
-			EAV	TON	BOL				ICE	T									GR	AIN- S	SIZE	390.	2	۲	MILE	B,C,S	NUMBER
05PT	MPLE	WPL E Y P E	RECOV	ETRAT	L SYM	SOIL	DESCRIPTION	5	E DESCRIPTION	FEETH		ICE C	CON DNTE	NTENT	(% OF % OF SA	DRY MPLE	WEIGH VOLU	T) ME)	N	5	ON	AVEL	DENSIT	CENSIT	632	S	10
	22	4°+	*	PEN	5 ios			LIMIT		102		20	PLAS	TIC				100 10	o₊ %	۳ %	3 %	5 %	L.	DRY (R	EMARKS	
	6		5			CLAY							\square							1						, <u></u>	
26]	1.	CL		- some			26	5		- \$					_		Į							
		. ?		ŀ	CI			· ·	Ì				\star	+-					_	[
20	1	1	·					· F	Vataga	28		-17	4-	<u> </u>		╆╾╂											
30	7	\leq	└──					!	y-muce	30									- ·	ĺ							
	ľ					SILT	- Lt. Grev					-/							_								[
32	1				ML		- Some Sand			32	+	++				+	-+-		-								
34			ľ	!. !			- Low Plasticit	y					+	1					1								·
							- Grovally			34																	
36							Glovelly			36	-		+						_								
30	8								1		$\vdash \uparrow$		+-			┝╌┤											
						END	OF HOLE 38'			38	-			+		┝╼╌┼			-								
40										40																	
															····-	┦─┤			_								
42										42-						┝╼╌╢											
44										44													·				
!																											
46			·							46	-+		+						-								
48													+	$\left - \right $		+			-			·					
					[48			1-	+		\vdash		+	-								

Γ													<u> </u>																	Page	1 of 2	
		Ν. ε Ι Β	TRIE				AS	SOCIATES).	DRILL	HC		- F	EP	OR	T			DE				OF <u>CKE</u>		JBL. LIE	IC V HIC	NOF SHV	RKS VAY	, CAN	ADA	
C	D BI	D	TEC	CH ·		TJ	RIG	Mayhew	SUR	FACE	DRAINAGE: Ex	cell	ent	to N	AINA	GE	<u>49</u> 65 ta	2 + TION	<u>30 (</u> u. Th	EST.	.) Spruz	- A(OFF	SET	1	<u>30' E</u>	AST			TEST	HOLE	
			×	z				· · · · · · · · · · · · · · · · · · ·		Ŷ		Τ	1								00100			GR/	IN- S	SIZE	401.	<u>0.</u>	[
Ĩ	Elwe	5 6	DVER	ATIO	08	soi	с :	DESCRIPTION		0F GROU	DESCRIPTION	EC	0	= WA	TER	CON	TENT	(%	OF C	RY	WE(G)	(Τ)		AN/	LYS	IS		Ł	ž	MILE	8,C,S	NUMBER
8	AWPL	LAPL.	REC	IE TR	NIFIE					LS N		FEET	۵	= 108	co	NTEN	NT (9	6 OF	SAN	PLE	VOLI	JME)	Ì	Ā	5	8	AVEL	DENS C. 2.	DENS C.F.)	632	S	11
	× 2	* ~ _	8	3.5	°					LIMI']	ł		, 	PLAST LIMIT	¦°				010 171			0	w		ŏ	5	ž		CHADKE	
			1	<u> </u>		SILT	-	Lt. Brown				+	+	<u> </u>	<u> </u>	T			<u> </u>		<u> </u>	- 100	1004	70	%	1%	%		-		LMARNS	
			l l		ML		-	Low Plasticity					<u> </u>											ł			İ -			Boswoi	th Cree	k
	[]·]]. 	ļ			-	Trace Gravel				2	┢──	6		+	┼──┤					-										
						CLAY	1							+	+-	+				-+	-+		· ·	.		ľ						
1 1			4				-	Lt. Brown				4	 		\wedge	╂──	<u>}</u>			-+		-	· · ·	•								
	2	\mathbf{P}					-	Silty	·				┝──	+	19	+	┝─┤					+-		ł								
1							-	Low Plasticity			NB	6.		+	+		┼──┤															
Ι.												ĺ .	<u> </u>		+		┥──┤															
]. °									Ì			8-		†	╆┼	+	-1			\rightarrow		-+										
Ì.								•					 	<u> </u>	$\left \right $					-+												
"	ן ארי שיין	\vdash						Grey-Brown				10		 																		
1.									}	Ì				┼──	$\vdash \uparrow$	+																
"	1									F		12			+≁-	┼─┤				-+												
					CI		-	Grey, silty, som	e	υ	Unfrozen -					+		+	-+	-		· ·										
"							-	sand and gravel		to	V - Trace	14-			¥																	
) IS]*						-	Soft Med. Plasticity		F					 			-						31	50	· ([p)					
1								mourressieny				16-					+															
. 18																						-+-										
						•						18-							-													
20		\vdash												$\left \cdot \right $						-+						:			İ			
[]	l ,	ert										20-	· · · ·					+	-	-+	-+-	+										
22																	-	-+		-		-										
												22-				<u>├</u> ─-		-+		-+		-†-										
Ż4			_]			•	•						 		-	$\left - \right $		+					·									
								·	Ť	1	·	24			\					-+						ł			[

. . **-** . . .

.

.

~~

•

•

·

.

.

•

												1																		Page	<u>2 of 2</u>	
-	E. W	/. E	BRO	OK NO	ER	8	AS	SOC		S LT	D.	DRILL	HC	LE	RE	EPO	RT	_		D:	EPA	RTI		ОҒ <u>СКЕ</u>	PU NZ	18L.I IE	IC \ HI		RKS VAY	, CAN	ADA	
CK		<u>- D</u>	TEC	<u>. 0 е</u> Эн •	NG			G Ma	LLED12	2/3//BAI	RPHO	TO NO: A22767	-153		CHA	NAGE	4	912 +	<u>30 (</u>	EST.	<u>)</u>		OFF	SET	130	' Eas	st	·		TEST	HOLE	
	T	<u>.</u>		1	T	<u> </u>		- //	a ynew			L DAGINGOL LY	I		N		VEGE	AHO	a: In	ICK	Spru	ce 4L	-50.	0.04	IELE	V: 4	01.0)' T		[r
1			E A	NO 1	(g						NNO	ICE	1											ANA	ULYSI	SZE.		۱٤	Σ	MILE	8,C,S	NUMBER
EPT!	9 L E 9 L E	2.	Ś	TANT	SYN S	SC		DESCR	IPTION		55	DESCRIPTION	E	١ v	= WAT - 105	ER C		T (%	OF	ORY	WEIG	HT)		2	-	e	ų	122	Sec.	632		11
100	SAM NUN	SAM TYI	Ē	ENE	1 1 1 1 1 1 1 1 1 1						NITS 02E		22			PLI	STIC	176 Ur	- SAI	APCC LIO		UME	•	5	รี	SAN	GRA	ې ته ۲		002		
	-		*	<u> </u>							15 5				20) ^{L(}	MIT 40		10		NIT O	100	100+	%	%	%	%	×	5	8	EMARKS	
	6		1	ł		CLA	۱Y .	- 507	Ma		U	Unfrozen				I		1								· · · ·	<u> </u>		t			
26			1					541	ine .		to	to V-Trace	1			Ĩ								1								
					CI						F		20				·		1					t								
1 20											i							+	1													
۔ ا						CAIT		- 1101	c 001				28					+					· ·									
						EINL			E 28'						┝╼╾╁								• <u> </u>									
1											1		30			-+			<u> </u>													ļ
		-													┝━╌╁			+														
32	1					•							32						<u> </u>													Í
												•										_										•
34													34																			Ì
					1													1														
36													36																			
																		·														
38													38				_							İ								
																																1
40																																·
42	[-+			ļ	ŀ		Ì					
													42					1														
44															+		-					-+							.			
													44+					+		+					- 1							
46													ŀ			-+-		1				<u> </u>										
	·	ļ											46					╉╾╌┥														
												•	- F																			
46													48			-+-		$\left - \right $		+												
			_	-		-		_					L		1		1	1 1			- 1	E E	1	- 1		- 1	- 1	. 1	- 1			. i

.

.

-

											γ <u> </u>		·																Pa	ge I of	2
	E.V	N. E	BRC	OK	ER	- 8t <i>i</i>	ASS	SOCIATES	LTI) .	DRILL	н	DLE	R	EP	OR.	r			DEP	AR ⁻			PU N7	BL		VOF	RS	, CAN	ADA	
DW	¥∶A	LB	FIE	ĽDΈ	NG:	NRM	DATI	E DRILLED12/3	/378IA	PHOT	TO NO: A2276	7 - 1	53	СН	INAG	E:	401	3 + 0/		T 1			UNL ISET	.142				AI	_		
СК). BI	<u> P</u>	TE	CH ·		<u> </u>	RIG	Mayhew	SUP	FACE	DRAINAGE E	xcell	lent '	to N		VE	GETA	TION	Thic	k Spr	uce -	40 - 50'		ELE	.v:	406	01		TEST	HOLE	I
			Ł	اگ	5					a No	ICE							-					GRA	IN- S	SIZE		<u>.</u>		MUE	BCS	NUMBED
HE	5		OVE	ANCE	ΥNB ΥNB	SOI	L DI	ESCRIPTION		G OF	DESCRIPTION	EF	0	= WA'	TER	CONT	ENT	(% 0:	FDR	Y WE	IGHT)	ANA			r e	115	si TY		0,0,0	NUMBER
105	AMP	AMPL	RE	VETE	IL S	•				T S ZCN	1	DEP.	Δ	= ICE	CON	ITEN	т (9	6 OF S	AMP	LE VO	DLUM	E)	ELAY .	11	AND	RAVE	0 EN	DEN	632	S	12
		"	8	22	- 6	•	<u> </u>			L S			1		PI 20	LASTI LIMIT 4	° ––-	60				00 100-1	%	%	%	%	wET CP	ρ87 Γ	R	EMARKS	
			İ			CLAY	1			F	V				Ĩ	·		Ť	T	Ĩ	Ţ				<u> </u>					-	
2	.]		CL		-	Lt. Brown			5 - 10%									_ <u>_</u>	+		1	ŀ					Boswo	rth Cree	k
	'	\square	1				-	Silty Low Plastici	hu [']		, •	2				5	>				1-		t								
4									· 7			٦.				1					+	1									
	2	K									NB	4				7				<u> </u>	1		1								
6	1	\vdash	1											-		1		-			+		1								
		.										6	<u> </u>			(<u> </u>	1						•		
8		1													7						+		i								ł
						•					•	•								1-	1				[.						.
10	3	\leftarrow	ł.				_	Group Law			•				T					1	1		·				Ì	1			Ì
	Ŭ	\vdash					-	Plasticity				10			Î				-†-	<u> </u>	<u>† </u>			' :							
12.																					·										
												12						· •	+		1										
14-										F									_												
	4									ñ		 																			ļ
16							-	Med. Plastic	ity	F	Unfrozen-										<u> </u>										
					Í						V- Irace	16								-	1							Í			
18																					<u> </u>										
											· .	10.								1	1							·			
201	5	\square										20			T					-†	1										
	. "											20-			Ϋ́					-	1-								,		
22			Į									22								1	1.										
	·											22								1	†			•							-
24											-									1	T										
] [*]				×				+											

Page 2 of 2

	E. W	/. B	RO	οĸ	ER	8	AS	so	CIA	TES	LT	D.	DRILL	но	LE	R	EP	ORI	r			DE	PAR	TME		OF KE	PU NZ	BLI IE	C V HIC	NO	RKS	, CAN	ADA	
CKD	BD	<u>. B</u>	FIE	LD E	NG-			G	May	ED12/ hew	3//3AIF	RFACE	TO NO: A22767 E DRAINAGE: E	xcel	lent	to N	INAG		1913 SETA	+ 00 TION:	(ES Th	T.) ick S	pruce	40 -	0FF5 50'	SET	ELE	<u>v:</u>	1.06	01		TEST	HOLE	
			2	7	or.							QND	ICE		Γ			-								GRA	IN- S	IZE	400.	ľ,	<u>}</u>	MILE	B,C,S	NUMBER
HE	PLE		COVE	TANCE	'tED SYMB	, so)IL	DES	CRIPT			N GRO	DESCRIPTION	PTH (12	0	= WA1	CON		ENT	(% (FD	RY W	EIGHT	·)	ł	*	-	<u>e</u>	VEL	F.)	F)	632	5	12
105	SAM	SAMP	*	PENET RESIS	SOIL	•.,						ROZE		12.5		- 102	P	LASTI	۰. ب	0 UF	JAM			NC /	ļ	C	511	SAI	GRA	0 1 1 1 1 1	A D	002	EMARKA	
—						<u> </u>		_ <		trace	of	1		┼─	┿──	2	° T		°	<u> </u>		- 0		100	100+	%	%	%	%	-	–		CMARKS	
26	0					0	~ '	 s	and a	and gr	avel,	to	Unfrozen				 - ê		-					-	-1	34	60	5	1					
		,						n	ned.	plasti	city	F		20																				
28			ļ											28	ļ						_	_									·			
	æ																						_											
30		•				ENE		: нс	DLF 3	30,		+		=. 30							-+		+-		\neg									
32																						-†-	-	+								-		
								•																									•	
34		•							•					34										 										
																				-														
36														36							┽			+										
38																					+			1										
														. 38					_															.]
40														40		 				_		_					ľ							
																					+													
42			•											42																			•	
44														44																				
46														46-							\downarrow													
																					+	_												. [
48														48				-			+													



GRAIN SIZE DISTRIBUTION

- 1



FIGURE ဂ N



PERCENT SMALLER

GRAIN SIZE DISTRIBUTION





FIGURE C-5

BORE		NATURAL	Atte	erberg Li	imits		MECHANICA		IS	6 011	•
HOLE	DEPTH	CONTENT	WL	W _P	PI		(M.I.T. CLAS	SIFICATION	N)	CLASSIFICATION	REMARKS
	feet	%	%	%	%	%CLAY	% SILT	% SAND	% GRAVEL	(UNIFIED)	
632-C-4	5	29.1	30.4	19.6	10.8					CL	Organic Content 12.04% SO ₄ - 0.135%
632-5-1	5	35.0	34.0	20.5	13.5					CL	so ₄ - 0.158%
632-5-2	20	11.5	27.3	20.9	6.5					CL-ML	
632-5-3	2 1					(1	7)	29	54	GM	
632-S-4	10					54	37	8	1	CL-CI	
632-5-6	5					(1	1)	21	68	GW	
632-S-11	15	20.9				.31	50	19		CL	
632-5-12	25	29.0	40.0	24.7	15.3	34	60	5	1	C1	



DWG. No.

<u>C-6</u>

EBA ENGINEERING CONSULTANTS LTD.

