

**REPORT ON SUBSURFACE SOIL
CONDITIONS FOR PROPOSED -
WHITESAND CREEK
BRIDGE MILE 459.6
MACKENZIE HIGHWAY**

Underwood McLellan & Associates Limited

SUBSURFACE
SOIL CONDITIONS
FOR THE
PROPOSED WHITESAND CREEK BRIDGE
MILE 459.6, MACKENZIE HIGHWAY
NORTHWEST TERRITORIES

Prepared by:
Underwood McLellan & Associates Limited
Consulting Engineers



Underwood McLellan & Associates Limited

2540 KENSINGTON ROAD N.W. CALGARY, ALBERTA T2N 3S3 TELEPHONE 283 4061 TELEX 038-24565

OUR FILE NO. 2106-032-45

April 6, 1973

Department of Public Works
P. O. Box 488
Edmonton, Alberta

Attention: Mr. F. E. Kimball,
Project Manager

Dear Sir:

Re: Subsurface Soil Investigation
Proposed Whitesand Creek Bridge,
Mile 459.6, Mackenzie Highway

Attached please find our report on the subsoil and foundation conditions for the proposed Whitesand Creek Bridge on the Mackenzie Highway in the Northwest Territories.

If you have any questions concerning the contents of this report, we would be pleased to discuss them with you at your convenience.

Yours very truly,

UNDERWOOD McLELLAN & ASSOCIATES LIMITED

Per:

A handwritten signature in cursive script, appearing to read 'D. G. Pennell'.

D. G. Pennell, Ph.D, P.Eng.

DGP/al

INDEX

	<u>Page No.</u>
A. INTRODUCTION	1 - 2
B. FIELD AND LABORATORY INVESTIGATION	3 - 6
C. SITE AND SUBSOIL CONDITIONS	7 - 10
D. CONCLUSIONS AND RECOMMENDATIONS	11 - 25
1. Pier and Abutment Foundation.	
2. Lateral Abutment Loads.	
3. Bridge Approach Grades and Borrow Material	

APPENDIX

Explanation of Field and Laboratory Test Data 1 - 6

- | | |
|--------------------|---|
| Plate No. 1 | Mosaic and Test Hole Location Plan. |
| Plate No. 2 | Bridge Site Profile and Soil Cross-section. |
| Plate No. 3 | Photographs of Proposed Bridge Crossing. |
| Plates No. 4 - 12 | Centreline and Structure Test Hole Logs. |
| Plates No. 13 - 21 | Borrow Pit Test Hole Logs. |

A. INTRODUCTION

The present report summarizes the results of sub-soil investigation operations conducted in connection with the proposed Whitesand Creek bridge at mile 459.6 on the Mackenzie Highway.

This bridge site investigation was undertaken as part of the geotechnical investigation from mile 450 to 550 on the Mackenzie Highway for the Department of Public Works, Government of Canada.

It was the intention of the present investigation to determine the vertical sub-soil material sequence, physical and structural properties, permafrost conditions and ground water conditions which would be expected to influence the stability of the valley slopes and the design and construction of the bridge foundation.

The included conclusions and recommendations have been based upon exploratory and sample acquisition operations conducted at a total of 9 positions along the proposed bridge center line in the river

channel and slopes of the bridge approaches.

In the formulation of conclusions and recommendations, the consistency and composition of the subsoil material between and in the proximity to the individual test boring positions has been assumed but not verified.

B. FIELD AND LABORATORY INVESTIGATION

A total of 9 test holes have been drilled within one mile of the bridge structure. In addition to the 9 centerline testhole logs, 9 borrow test hole logs in the vicinity of the bridge site have been included in the Appendix. Test holes along the centerline were drilled to depths varying from 11 to 90 feet below the existing site grades. Borrow test holes were generally advanced to the 15 foot level.

Test borings were drilled December 6, 8 and 12, 1972, and January 9 and 12, 1973, by Kenting Big Indian Drilling of Calgary, utilizing a Meyhew 1000 and Heli drill. Air recovery methods were generally employed except where severe caving was encountered at bridge crossings, water and mud drilling methods were utilized. The locations of the individual test borings were selected and located by Underwood McLellan & Associates Limited. The approximate test boring locations are graphically illustrated on the accompanying Mosaic and Test Hole Location Plan.

All variations of soil, permafrost and groundwater conditions encountered during the test hole boring operations were noted and representative samples of the existing subsoils were taken. The majority of the samples were disturbed having been obtained by air recovery methods. Sampling was also undertaken with 2" and 3" O.D., split spoon sampling tubes and 3" O.D. thin walled Shelby tubes. In the laboratory materials obtained from the drilling operations were subjected to standard laboratory classification procedures including particle size distribution and Atterberg index property determination. Moisture contents were obtained for all samples returned to the laboratory. Wherever a sufficient length of intact sample was retained in the penetrometer tube, both wet and dry densities were obtained.

Permafrost samples were classified according to NRC technical memorandum No. 79 "Guide to the field description of permafrost." The excess ice content

in permafrost samples was determined by visual inspection and by measured thicknesses of ice lenses. The excess ice content was obtained by division of the ice thickness by the total sample thickness.

All soil samples were classified according to the Unified Soil Classification system.

All results of laboratory and field tests are summarized in the Appendix on the test hole logs.

Test holes have been designated by mileage, type and number. Examples include 459C 80B, 459S 132A and 459B 159B. The letter symbols and numbers indicate

459 - indicates mileage

B, C, and S - between mileage and test hole number
indicates borrow, centerline or
structure test holes, respectively.

80, 132 and 159 - indicate test hole numbers.

A, and B - after test hole numbers indicate drilling
performed by Meyhew 1000 or Heli drill,
respectively.

Test holes should be designated by a number
followed by A or B.

C. SITE AND SUBSOIL CONDITIONS

The Whitesand bridge site is located at mile 459.6 (chainage 880 + 00) on the Mackenzie Highway in the Northwest Territories. The Whitesand river flows into the Mackenzie River from the east having a drainage basin which extends to the Franklin mountains. This stream has a typical sand-gravel bed which is presently in a state of depositing floodplain sediments at the entrance to the Mackenzie River.

The Whitesand stream bed elevation is 280 (DPW datum) with the estimated high water mark at elevation 306 as a result of ice jams along the Mackenzie River. The main valley of the Whitesand Creek is approximately 400 feet wide, and 50 feet deep. The main stream flow in recent years has been against the north bank in a trench approximately 100 feet wide and 15 feet deep.

Two test holes 124A (879 + 70) and 132A (881 + 70) were drilled at the bottom of the main valley to depths of 40 and 90 feet, respectively. Test hole 124A disclosed alternating layers of sand and gravel to the termination of the hole. These granular materials exhibited very low moisture contents and the water table was indicated at 22 feet below existing grades which was approximately coincident with the stream water level.

Test hole 132A which was drilled to a depth of 90 feet disclosed alternating sand and gravel layers to a depth of approximately 70 feet where a sandstone and shale bedrock was confirmed. The bedrock in the general area of the investigation is believed to consist of sedimentary deposits of inter-bedded shales siltstones and sandstones which were deposited during the Cretaceous Geologic age.

Test hole 124A did not disclose any permafrost but test hole 132A indicated permafrost to a depth of approximately 30 feet where the water table was encountered. Below the water table, the soil would

be classified as semi-frozen.

Although the mud and water circulation method was utilized, sloughing was extensive and "undisturbed" samples could not be retrieved.

Test holes drilled along the valley walls and near the uplands within approximately $\frac{1}{2}$ mile south and north of the proposed bridge site disclosed granular sand and gravel deposits which were previously deposited by the Whitesand stream when it flowed at higher elevations. It may also be concluded from the test holes drilled that the stream banks and upland consist primarily of permafrost. The majority of the granular materials exhibit very low moisture contents although these materials are frozen.

The gravel samples which were obtained during drilling operations indicated approximately 50% material coarser than the # 10 sieve, but these samples which were subjected to crushing during drilling would exhibit a true gravel size content

higher than recorded.

Exception to the dry granular materials was indicated in test hole 123A (885 + 00) which has a surface deposit of 16 feet of high moisture content silt and clay with excess ice contents of approximately 5%. The dry density of the silt clay varied from 88.7 to 92 lb/cu.ft. The materials below the 16 foot level in test hole 123A consisted of dry sand with some boulders and was further underlain by a firm clay till of stiff consistency.

A Soil Profile of the bridge valley site is included in the Appendix on Plate 2.

D. CONCLUSIONS AND RECOMMENDATIONS

On the basis of the present investigations we wish to offer the following generalized conclusions and recommendations relative to the design and construction of the proposed Whitesand Creek bridge foundations and approaches.

1. Pier and abutment foundation.

A footing foundation for the abutments and piers will be founded in the gravel and sand deposits which are described in the previous section. These materials which were stream deposited have not been subjected to preconsolidation and significant settlements would result under foundation loadings. In addition, considerable difficulty would be experienced in performing excavations for piers in the saturated granular soil. Consequently, a driven pile foundation system is recommended for all structures.

The pile types generally available would include timber, precast concrete, steel H-piles and pipe piles. The timber piles are not recommended as a result of their low capacity and

possible damage when driving through gravel strata. The pre-cast concrete piles are also not recommended primarily due to the difficulty in establishing ultimate pile lengths and unless the lengths can be pre-determined considerable difficulty in splicing results.

Steel H-piles or pipe piles are, therefore, recommended for consideration primarily based on high driving strength, high load capacity and relative ease in splicing. The granular strata at this site will provide adequate lateral support such that instability in the form of buckling of the piling will not be a problem.

It is recommended that all piles be driven to "refusal". "Refusal" will depend upon the energy rating of the hammer but is commonly 15,000 ft. lb. As an initial guide, piles should be driven to blow counts of 180 blows/ft. or 15 blows/inch. The pile capacity is largely

a function of the amount of energy expended in installing the pile and not just of the recorded resistances. The pile which is driven to a sustained resistance will perform better than one which is terminated the instant a given resistance is attained. Of course, the pile must not be driven until damage occurs and whenever resistance increases greatly, the driving should be terminated.

At the Whitesand Creek site, it is anticipated that steel pipe or H-piles for piers will be approximately 60 feet long based on data summarized on test hole log 132A where bedrock was encountered at elevation 220. The pier foundations will be nearer the stream channel than test hole 132A and the "rotten" nature of the permafrost will likely be more developed. Difficulty exists in establishing the insitu density and therefore, predicting the "refusal" depth in gravel strata. Steel piles driven to refusal can be expected to attain allowable load capacities in the range of

80 tons depending upon the steel section area.

"False" refusal may occur whenever extremely large boulders cannot be penetrated during driving. Such boulders were encountered at the 16 foot level in test hole 132A.

Although refusal may be attained while driving, fundamental refusal bearing capacity may not exist below the pile tip. Load tests would be necessary to establish allowable pile loads if this situation is recognized. In order to attain penetration of the steel piles around large boulders, it may be necessary to utilize vibration techniques. Alternatively, large diameter open steel pipe may be utilized to penetrate boulder strata by crushing the boulders with churn-drill methods within the pipe pile.

Whenever conventional driving techniques are employed, the capacity of a pile should be established in the field by several pile-driving tests. The ultimate capacity would be calculated

on the basis of a dynamic pile-driving formulae such as the Hiley, Danish or Weisbach. It is recommended that the Engineering News formula not be utilized as a result of its extreme variation in factor of safety.

The south abutment location is proposed in the large fill section at station 881 + 40. Wherever the embankment consists of compacted granular fill as recommended in section D3, the abutment may be placed on a spread footing utilizing 4000 pcf allowable bearing stress. If inferior materials or compaction techniques are utilized in the embankment, the foundation must consist of driven piles into the granular subsoils below. Piles driven through fills subject to settlement must be designed to carry negative skin friction.

At the north abutment, station 883 + 90, a change from fill to cut occurs at the proposed location. The soil strata consists of clayey silt and clay permafrost at this elevation and would not allow satisfactory long-term abutment foundation performance. Piles driven to refusal in the glacial till at elevation 308 should be utilized but steam-jetting of the surface materials will likely be necessary to achieve penetration.

It is further recommended that static load tests be performed to establish more accurately the bearing capacity of a typical steel pile and the applicability of dynamic pile formulae. Data obtained from load tests on piles driven into deep granular deposits will be of assistance in designing piles throughout the Mackenzie Highway System.

The lateral resistance of piles can be established by recently developed methods based on the beam on elastic foundation method but the simple and more conventional approach is based on calculation of the Rankine passive earth pressure against the pile. Using Rankine theory the ultimate passive resistance force/ft² of pile can be obtained by $P = \frac{1}{2} \gamma_p K_p H^2$. The submerged unit weight of the granular material may be taken as 60 pcf and the passive pressure coefficient K_p as 3.0. In order to establish the allowable lateral load a factor of safety of 2.5 should be applied to the above ultimate load. Generally, in cohesionless soils the lateral load tends to exceed the passive resistance and the above simplified approach is on the conservative side.

2. Lateral Abutment Loads

The magnitude of the pressure applied to the abutment will depend upon the characteristics of the backfill chosen for the approach fill and upon the movements that the wall undergoes during and subsequent to fill compaction.

It is recommended that granular backfill from the river terraces or borrow pits be utilized for the abutment approach embankments which will be in the order of 30 feet high.

The most common procedures for analysis of the earth pressures against gravity retaining walls include the Rankine and Coulomb methods.

Generally, it is assumed that the wall rotates sufficiently to allow mobilization of the backfill shear strength which reduces the pressure to the active case, the lowest pressure that can be realized. This assumption applies reasonably accurately when the backfill consists of uncompacted granular material but pressures greater than the active occur wherever compaction of the backfill is undertaken. While the total yield at different elevations on the abutment may be adequate for mobilization of the full backfill strength, a gradual build-up of the backfill also results in a gradual yielding of the wall. Therefore, by the time the backfill is complete only a fraction of the total yield of the wall has become effective in decreasing the earth pressure. At the present time it is accepted that the actual earth pressure magnitude will exceed the active case and may approach the earth pressure at rest. Pressures greater than the at-rest case may occur if

heavy equipment is utilized near the concrete abutment.

If the Coulomb approach is utilized, the angle of wall friction between concrete and coarse sand and gravel would be 20 degrees. The angle of internal friction for compacted granular material would be 38 degrees and the dry density may be taken as 115 pcf. For a simple vertical retaining wall abutment with horizontal backfill the Coulomb active coefficient would be .24 and the at-rest coefficient based on $K_0 = 1 - \sin \phi$ would be .38. The Rankine procedure which disregards the wall friction would also result in an active coefficient of .24. Whenever the wall or backfill are inclined or a surcharge exists, the Coulomb procedure will result in a lower active pressure which will be more exact than the conservative Rankine method. The pressure distribution behind a gravity retaining wall has been shown to be non-

triangular, but as a first approximation and for simplicity, the triangular pressure diagram is recommended. It is also recommended that whenever backfill is compacted in lifts by vibratory compactors the at-rest coefficient may be utilized for calculation of the ultimate earth pressure.

A driven pile foundation has been previously recommended for the abutments which will provide significant lateral resistance but it is further recommended that some batter piles be utilized to ensure adequate lateral support against earth pressures.

Positive drainage including horizontal perforated tile and weep holes should be provided to prevent development of hydrostatic pressure against the wall. In addition, free drainage of water will prevent the development of frost heaving pressures against the walls.

3. Bridge Approach Grades and Borrow Material

Major cuts are proposed at the north and south banks of the proposed bridge site.

The cut on the south bank at station 872 + 00 will be approximately 35 feet in height and will extend approximately 1,000 feet. These cuts will be performed in dry frozen sand and gravel with no excess ice. It is anticipated that the stability of this cut slope will not be a problem and a slope of 2:1 is recommended, although a flatter slope may be employed to increase available fill material.

The cut on the north bank at station 886 + 00 will be undertaken in primarily dry gravel and sandy silt with moisture contents less than 6%. In the lower portion of the cut section at station 885 + 00, the cut of 10 feet will be primarily in silt and silty clays with moisture contents in the order of 25% and excess ice contents of 5%. At this

section cut slopes of 2:1 are recommended.

Some sloughing of the 10 foot cut can be expected after excavation during thermal readjustment. It is recommended that consideration be given to raising the grade line approximately 12 feet near the north abutment to eliminate cutting in the surface silt permafrost. Some thaw settlement can be expected as the section would be composed of a four foot fill.

Fills of 3 to 5 feet have been proposed north and south of the major cuts which were described in the above paragraph. These fill heights are considered adequate at stations 894 + 00 and 864 + 00 as the subgrade consists of dry granular soil which is not expected to undergo significant thaw settlements, but in the area of test hole 80B at station 855 + 00 approximately 10 feet of fine sandy silt is present which exhibits moisture contents of 40%; dry density near 70 pcf., and contains random ice. It is expected that thaw settlements in the order of 1 to 2 feet will occur.

Therefore, it is recommended that the fill depth in this area be increased to approximately 8 feet if granular materials are utilized.

The approach fills to the bridge will be approximately 30 feet high and it is recommended that because of an adequate granular material supply, these materials be utilized in all fills near the bridge approaches and be compacted to 95% of Standard Proctor utilizing vibratory compaction. Although construction may be performed during the winter, the dry nature of the granular materials will allow adequate compaction. Compaction of these deep approach fills is mandatory to ensure slope stability and all fill slopes should be constructed at slopes of 2:1.

In addition to common excavation which will be obtained from valley cut sections, granular

borrow material may be found adjacent to the centreline at station 871 + 00 and 891 + 00. The borrow pit investigated at station 831 + 00 consists of silty clay with moisture contents in the range of 40% and is not considered suitable for roadway embankment fill. Test hole logs for the borrow material are included in the Appendix.

APPENDIX

EXPLANATION OF FIELD & LABORATORY TEST DATA

The field and laboratory test results as shown for a particular test boring by the Test Hole Log Data Sheet are briefly described below:-


NATURAL MOISTURE CONDITIONS & ATTERBERG LIMITS

The relation between the natural moisture content and depth is significant in determining the subsurface moisture conditions. The Atterberg Limits should be compared to the Natural Moisture Content of the subsurface soil as well as plotted on the Plasticity Chart.

SOIL PROFILE & DESCRIPTION

Each soil strata is classified and described noting any special conditions. The unified classification system is used, and the soil profile refers to the existing ground elevation. When available the ground elevation is shown.

The soil symbols used are briefly shown below but are indicated in more detail in the Soil Classification Chart.



TESTS ON SOIL SAMPLES

Laboratory and field tests are identified by the following symbols:


- QU - unconfined compressive strength usually expressed in tons per square foot. This value is used in determining the allowable bearing capacity of the soil.
- γ_d - dry unit weight expressed in pounds per cubic foot. This value indicates the density or consistency of the in-situ soil.

- C - Consolidation test. These test results are separately enclosed and provide information on the consolidation or settlement properties of the soil strata.
- M.A. - grain size analysis. These test results are separately enclosed and indicate the gradation properties of the material tested.
- SO₄ - water soluble sulphate content is conducted primarily to determine whether sulphate resistant cement is required for the foundation structure.
- N - standard penetration field test. This test is conducted in the field to determine the in-situ consistency of a soil strata. The "N" value recorded is the number of blows from a 140 lb. hammer dropped 30 inches (free fall) which are required to drive a 2" O.D. Raymond type sampler 12 inches into the soil.

The resistance and unconfined compressive strength of a cohesive soil can be related to its consistency as follows:-

N - BLOWS/Ft.	QU - T/Ft. ²	CONSISTENCY
2	0.25	very soft
2-4	0.25-0.50	soft
4-8	0.50-1.00	medium or firm
8-15	1.00-2.00	stiff
15-30	2.00-4.00	very stiff
30	4.00	hard

The resistance of a non-cohesive soil (sand) can be related to its consistency as follows:-



SAMPLE CONDITION AND TYPE

The depth and condition of samples are indicated by the following symbols:


UNDISTURBED


DISTURBED


LOST SAMPLE

SAMPLE TYPES

T - 3" O.D. Shelby tube sample
P - penetration tube sample
C - rock core sample

PERCENTAGE WATER SOLUBLE SULPHATE CONCENTRATION

0 0.1 0.2 0.3 0.4 0.5 0.6 0.7%

Negli- gible	Posi- tive	Considerable	Severe
RELATIVE DEGREE OF SULPHATE ATTACK			

Negligible - Normal Portland Cement may be used.

Positive - Normal Portland Cement may be used, provided the strength of the concrete is increased up to 500 psi higher than the compressive strength which would normally be used.

Considerable - Type V cement must be used and the concrete compressive strength should be increased to 500
















psi higher than the compressive strength which would normally be used.

Severe - Type V cement must be used and the concrete compressive strength should be increased from 500 to 1000 psi higher than the compressive strength which would normally be used.

GROUND WATER TABLE

The water table is indicated by the level of standing water in a test boring after equilibrium has been reached. This is generally taken 24 hours after the drilling operation. The water table is usually an inclined surface that is dynamic in nature with its highest level late in the winter or early spring gradually falling throughout the summer.


UNIFIED SOIL CLASSIFICATION SYSTEM

MAJOR DIVISIONS			GRAPH SYMBOL	LETTER SYMBOL	TYPICAL DESCRIPTIONS	
COARSE GRAINED SOILS	GRAVEL AND GRAVELLY SOILS	CLEAN GRAVELS (LITTLE OR NO FINES)		GW	WELL-GRADED GRAVELS, GRAVEL-SAND MIXTURES, LITTLE OR NO FINES	
				GP	POORLY-GRADED GRAVELS, GRAVEL-SAND MIXTURES, LITTLE OR NO FINES	
		GRAVELS WITH FINES (APPRECIABLE AMOUNT OF FINES)		GM	SILTY GRAVELS, GRAVEL-SAND-SILT MIXTURES	
	MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE			GC	CLAYEY GRAVELS, GRAVEL-SAND-CLAY MIXTURES	
		SAND AND SANDY SOILS	CLEAN SAND (LITTLE OR NO FINES)		SW	WELL-GRADED SANDS, GRAVELLY SANDS, LITTLE OR NO FINES
					SP	POORLY-GRADED SANDS, GRAVELLY SANDS, LITTLE OR NO FINES
FINE GRAINED SOILS	SANDS AND SANDY SOILS	SANDS WITH FINES (APPRECIABLE AMOUNT OF FINES)		SM	SILTY SANDS, SAND-SILT MIXTURES	
				SC	CLAYEY SANDS, SAND-CLAY MIXTURES	
		MORE THAN 50% OF MATERIAL IS SMALLER THAN NO. 200 SIEVE SIZE			ML	INORGANIC SILTS AND VERY FINE SANDS, ROCK FLOUR, SILTY OR CLAYEY FINE SANDS OR CLAYEY SILTS WITH SLIGHT PLASTICITY
	SILTS AND CLAYS		LIQUID LIMIT LESS THAN 50		CL	INORGANIC CLAYS OF LOW TO MEDIUM PLASTICITY, GRAVELLY CLAYS, SANDY CLAYS, SILTY CLAYS, LEAN CLAYS
					OL	ORGANIC SILTS AND ORGANIC SILTY CLAYS OF LOW PLASTICITY
				MH	INORGANIC SILTS, MICACEOUS OR DIATOMACEOUS FINE SAND OR SILTY SOILS	
HIGHLY ORGANIC SOILS	SILTS AND CLAYS	LIQUID LIMIT GREATER THAN 50		CH	INORGANIC CLAYS OF HIGH PLASTICITY, FAT CLAYS	
				OH	ORGANIC CLAYS OF MEDIUM TO HIGH PLASTICITY, ORGANIC SILTS	
				PT	PEAT, HUMUS, SWAMP SOILS WITH HIGH ORGANIC CONTENTS	

NOTE: DUAL SYMBOLS ARE USED TO INDICATE BORDERLINE SOIL CLASSIFICATIONS.

SOIL CLASSIFICATION CHART

PLASTICITY CHART



NATIONAL RESEARCH COUNCIL PERMAFROST
CLASSIFICATION SYSTEM

Permafrost ground ice occurs in three basic conditions including non-visible, visible (less than one inch in thickness) and clear ice.

A. Non-visible - N

N_f - poorly bonded or friable frozen soil

N_{bn} - well bonded soil, no excess ice

N_{be} - well bonded soil, excess ice

B. Visible - V (less than 1" thick)

V_x - individual ice crystals or inclusions

V_c - ice coatings on particles

V_r - random or irregularly oriented ice formations

V_s - stratified or oriented ice formations

C. Visible Ice - (greater than 1" thick)

Ice - ice with soil inclusions

Ice + Soil - ice without soil inclusions.

A more complete description of this system is included in NRC publication TM 79.



Issue	Date	Remarks	No.	Revision	Date	By	Approved

**UNDERWOOD McLELLAN
& ASSOCIATES LIMITED**

CONSULTING ENGINEERS - TOWN PLANNERS

BRITISH COLUMBIA • ALBERTA • SASKATCHEWAN • MANITOBA • ONTARIO

Drawn: H.S.
Checked: D.M.P.
Design:
Traced:
Scale:
1" = 1000'

MACKENZIE HIGHWAY

**WHITESAND CREEK MOSAIC AND
TEST HOLE LOCATION PLAN**

Drawn: H.S.
Job:
Sheet:
Drawing:
PLATE-1
Issue:



Viewing Hill at Sta. 874+00 from
Station 880+00 looking South
Proposed 30 foot Cut Area.



Viewing E of Crossing from Station
880+00 Looking North



£

Viewing Proposed Crossing from Station 884+20
Top of North Bank & Looking at Station 874+00
South of Crossing

£



View down slope of North Bank from
Station 884+20 looking South.

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY							
JOB: 11.5 W		FIELD ENG: 5 M		DATE DRILLED: 12/12/12		AIRPHOTO NO:		CHAINAGE: 905+00		OFFSET: 2					
C/O: DGP		TECH: DM		RIG: AIR		SURFACE DRAINAGE: GOOD		VEGETATION: SPRUCE TO 25'		ELEV:					
TEST HOLE		MILE		S.C.S		NUMBER									
		460		C		99B									
REMARKS															
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS				WET DENSITY (P.C.F.)	DRY DENSITY (P.C.F.)
										PLASTIC LIMIT	LIQUID LIMIT	CLAY %	SILT %	SAND %	GRAVEL %
										20	40	60	80	100	100+
										○ = WATER CONTENT (% OF DRY WEIGHT) △ = ICE CONTENT (% OF SAMPLE VOLUME)					
2					DT	COARSE, FIBROUS, GRANULAR SAND			2						
4					SM	BROWN, SOME SILT FEW PEBBLES		Nbn	4						
6						GRVELLY			6						
8						BROWN, SILTY			8						
10						GRVEL		Nf	10						
12					GM	BROWN, SANDY		Nbn	12						
14									14						
16						END OF HOLE			16						
18									18						
20									20						
22									22						
24									24						

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY								
DATE: 12/12/72		FIELD ENG: B.M.		DATE DRILLED: 12/12/72		AIRPHOTO NO:		CHAINAGE: 895+00		OFFSET: 0						
CKD 062		TECH: D.M.		RIG: AIR		SURFACE DRAINAGE: FAIR		VEGETATION: SPRUCE TO 25'		ELEV: 0						
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS				WET DENSITY (pcf)	DRY DENSITY (pcf)	REMARKS
										CLAY %	SILT %	SAND %	GRAVEL %			
						PEAT COARSE, GRANULAR MUSKIE, MOSS, ROOTS	F									
2						SAND			2							
4					SM	REDDISH, GRAVEL, SILT		Nf	4							
5						BROWN, GRAVEL										
6						WHITE, GRAVELLY										
8						GRAVEL										
10					GP	SOME LARGE SIZES		Nf	10							
12						COBBLES, SILTY										
14									14							
16																
18																
20																
22																
24																

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY								
OWN A.F.M.		FIELD ENG. R'S		DATE DRILLED 6/12/72		AIRPHOTO NO:		CHAINAGE: 236+00		OFFSET: 2		TEST HOLE				
CKD D.P.P.		TECH. D.M.		RIG: AIR		SURFACE DRAINAGE: NORTH-SOUTH		VEGETATION: SPRUCE TO 25'		ELEV: 34269		MILE: 459 E.C.S. NUMBER: C 76A				
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS				WET DENSITY (P.C.F.)	DRY DENSITY (P.C.F.)	REMARKS
										CLAY %	SILT %	SAND %	GRAVEL %			
2						GRAVEL			2							
4					GP	COARSE, BOULDERS			4							
6									6							
8						SANDY, POORLY GRADED			8							
10									10							
12						SILT			12							
14									14							
16					GC	SANDY WITH BOULDERS			16							
18									18							
20									20							
22									22							
24						END OF HOLE @ 35'			24							

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT		DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY								
DRY AEW FIELD ENG R S		DATE DRILLED 9/11/73		AIRPHOTO NO.		CHAINAGE: 885100		OFFSET 50' E OF L						
C/D DGP TECH DM		RIG: AIR		SURFACE DRAINAGE: SOUTH		VEGETATION: CONIFER TO 50'		ELEV 3334.50						
								TEST HOLE						
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS		WET DENSITY (PCF)	DRY DENSITY (PCF)	REMARKS
										CLAY %	SILT %			
○ = WATER CONTENT (% OF DRY WEIGHT) △ = ICE CONTENT (% OF SAMPLE VOLUME)														
PLASTIC LIMIT 20 40 60 80 100 100+ LIQUID LIMIT 60 80 100 100+														
4					Pe	PEAT ORGANIC			4					
8					OL	SILT FINE SAND, LITTLE CLAY VERY SOFT WHEN THAWED		Nbc	8					
12					CL	SANDY, HARD CLAY HARD WITH SILT AND SAND SEAMS		Vr	12					
16						SAND			16					
20					SM	COARSE, SANDY WITH SOME CLAY BOULDERS		Vr	20					
24						TILL			24					
28					GC	FIRM, CLAYEY LESS CLAY, SOFTER SILTY, DRY, COARSE SAND			28					
32									32					
36									36					
40						END OF HOLE			40					

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT		DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY												
DRY A.E.W.		FIELD ENG. T.S.	DATE DRILLED 12/11/73		AIRPHOTO NO:	CHAINAGE 881+70		OFFSET	TEST HOLE									
CKD DGP		TECH. D.M.	RIG AIR		SURFACE DRAINAGE:		VEGETATION: CONIFER TO 30'		ELEV 293.73									
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS				WET DENSITY (P.C.)	DRY DENSITY (P.C.)	MILE	E.C.S.	NUMBER
										CLAY %	SILT %	SAND %	GRAVEL %					
										○ = WATER CONTENT (% OF DRY WEIGHT) △ = ICE CONTENT (% OF SAMPLE VOLUME)								
										PLASTIC LIMIT 40 60 80 100 100+ LIQUID LIMIT 80 100 100+								
4					SM	LENT - MUSKEG SILT SANDY SAND DRY, SILTY	F		4									
8						HARD ROCK			8									
12						GRAVEL			12									
16					GM	SILTY, SANDY			16									
20							UF		20									
24									24									
28						CLAY GREY, FINE SAND			28									
32						GRAVEL			32									
36					GM	CLAYEY, COARSE			36									
40						END OF HOLE			40									

SAND MAY BE
 WISHER AWAY.
 TEST HOLE ON
 ADJACENT STEEP
 HOLE REQUIRED
 TO 30' (SEE NEXT
 PAGE)

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY										
ENGR. A. E. N. FIELD ENG. D.M.		DATE DRILLED 12/1/73		AIR PHOTO NO.		CHAINAGE 881+70		OFFSET		TEST HOLE								
CDX 667 TECH		RIG AIR		SURFACE DRAINAGE 6CMP		VEGETATION POPLAR & CONIFER TO 45' ELEV												
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNITED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS				WET DENSITY (P.C.F.)	DRY DENSITY (P.C.F.)	MILE	E.C.S. NUMBER	REMARKS
										CLAY	SILT	SAND	GRAVEL					
										CLAY	SILT	SAND	GRAVEL					
										PLASTIC LIMIT	LIQUID LIMIT							
										20	40	60	80	100	100+			
8					DE	FIBROUS MUSKEG	F		8									
					SP	SAND FINE		Nbn										
						GRAVEL												
16					GP	SOME BOULDERS												
						SAND												
24					SP	LITTLE CLAY												
32						GRAVEL	UP	FREE WATER										
							F											
40					GW	COARSE SAND												
48						CLAY MIXED WITH SAND LENSES												
56																		
64					GP	FINE, SAND LENSES		Nbn										
72						SANDSTONE LAYER @ 62'												
						CLAY												
80					CH	BLUISH GREY, MED PLASTIC, SANDSTONE OR SHALE LAYERS		Nbn										
88						SHALE VERY HARD, SANDSTONE												
96						END OF HOLE												

ROCKS IN SAMPLE ARE FROM WALLS AT 62' COMING UP.

PLATE 8A

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY										
DATE A.E.W. FIELD ENG. R.S.		DATE DRILLED 9/11/73		AIRPHOTO NO.		CHAINAGE 879+70		OFFSET 50' E OF 4		TEST HOLE								
CKO D.6 P		TECH		RIG AIR		SURFACE DRAINAGE:		VEGETATION: CONIFER TO 40'		ELEV. 295.4								
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS				WET DENSITY (PCF)	DRY DENSITY (PCF)	MILE	E.C.S.	NUMBER
										CLAY	SILT	SAND	GRAVEL					
										%	%	%	%					
4					DEAT	ORGANIC, GRANULAR	F		4									
8					SAND	FINE, MOIST	UF		8									
12					GRVEL				12									
16					GC	MED. COARSE SAND SILTY, BOULDERS CLAYEY			16									
20									20									
24									24									
28					SAND				28									
32					SC	CLAYEY			32									
36									36									
40					GC	GRVEL CLAYEY			40									
44						END OF HOLE			44									

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY					
DAY: A E W		FIELD ENG: 7.5		DATE DRILLED: 12/12/72		AERPHOTO NO:		CHANGE: 674 +06		OFFSET: 2		TEST HOLE	
CKD: 36 P		TECH: DM		RIG: AIR		SURFACE DRAINAGE: EAST TO WEST		VEGETATION: SPRUCE TO 40'		ELEV:			
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION PLASTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	GRAIN-SIZE ANALYSIS		WET DENSITY (P.C.F.)	DRY DENSITY (P.C.F.)	REMARKS
									CLAY %	SILT %			
5					ML	SLT LIGHT BROWN, SANDY							
					GM	GRAVEL LIGHT BROWN, SANDY SILTY							
10						SAND							
15					SP	BROWN, MED COARSE SOME GRAVEL, DRY							
20						SANDY							
25													
30						GRAVEL							
35					GC	BROWN, COARSE, SOME CLAY							
40													
45					GP	FINE, BROWN							
50						CLAY							
55					GC	BROWN, SANDY, GRAVEL COARSER WITH DEPTH.							
60						END OF HOLE							

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY								
DATA: AEW		FIELD ENG: B.M.		DATE DRILLED: 8/12/72		AIRPHOTO NO.		CHAINAGE: 865+00		OFFSET: L		TEST HOLE				
CND DSD		TECH: D.M.		RIG: AIR		SURFACE DRAINAGE: FAIR		VEGETATION: SPRUCE & ASPEN		ELEV.						
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS				WET DENSITY (PCF)	DRY DENSITY (PCF)	REMARKS
										CLAY %	SILT %	SAND %	GRAVEL %			
						DEAT - COARSE, FIBROUS, MOSS ROOTS										
2					SP	SAND - FINE, SOME GRAVEL DRY		Nbe	2							
4						GRAVEL			4							
6					GP	SOME SAND, DRY			6							
8									8							
10									10							
12									12							
14						END OF HOLE			14							
16									16							
18									18							
20									20							
22									22							
24									24							

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY																					
OWN: F.W.		FIELD ENG: D.M.		DATE DRILLED: 8/12/72		AIRPHOTO NO:		CHAINAGE: 855+00		OFFSET: 2																			
CKD: D.S.P.		TECH: D.M.		RIG: AIR		SURFACE DRAINAGE: 5000		VEGETATION: SPRUCE & POPLAR TO 25'		ELEV:																			
DEPTH (FEET)		SAMPLE NUMBER		SAMPLE TYPE		% RECOVERY		PENETRATION RESISTANCE		UNIFIED SOIL SYMBOL		SOIL DESCRIPTION		LIMITS OF FROZEN GROUND		ICE DESCRIPTION		DEPTH (FEET)		GRAIN-SIZE ANALYSIS		WET DENSITY (P.C.F.)		DRY DENSITY (P.C.F.)		TEST HOLE			
																				CLAY %		SILT %		SAND %		GRAVEL %		MILE 159 C 80B	
2												SILT		F		V+		2											
4												FINE SAND						4											
6												SM						6											
8												FINE, SANDY						8											
10												SAND						10											
12												SD						12											
14												SAND						14											
16												SILTY, LITTLE CLAY						16											
18												TRACE OF GRAVEL						18											
20												END OF HOLE						20											
22																		22											
24																		24											

DEPARTMENT OF PUBLIC WORKS, CANADA
MACKENZIE HIGHWAY

DAN A. EW.	FIELD ENG. B.M.	DATE DRILLED 9/11/73	AIRPHOTO NO.	CHINA: 391400	MAXIMUM DEPTH	10.00
CKD D.G.P.	TECH. D.M.	RIG: D/R	SURFACE DRAINAGE	WOOD	VEGETATION: SPRUCE & ASPEN TO 25' ELEV	TEST HOLE

DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS		WET DENSITY (PCF)	DRY DENSITY (PCF)	MILE NO. & NUMBER	REMARKS
										CLAY	SILT				
										○ = WATER CONTENT (% OF DRY WEIGHT) △ = ICE CONTENT (% OF SAMPLE VOLUME)					
										PLASTIC LIMIT ——— LIQUID LIMIT 20 ——— 40 ——— 60 ——— 80 ——— 100 ——— 120	%	%	%	%	

2
4
6
8
10
12
14
16
18
20
22
24

GM

GRAVEL 1/2" ORGANIC
SILTY, SANDY

GP

VERY HARD FINE SAND

END OF HOLE

F
UF

2
4
6
8
10
12
14
16
18
20
22
24

Depth (ft)	Soil Description	Blow Count (F)	Penetration Resistance (UF)
0	Gravel 1/2" Organic		
2	Silty, Sandy	2	2
4	Silty, Sandy	4	4
6	Very Hard Fine Sand		
8	Very Hard Fine Sand		
10	Very Hard Fine Sand		

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT		DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY								
DR: A.E.W. FIELD ENG. B.M.		DATE DRILLED: 9/1/73		AIRPHOTO NO.		CHAINAGE: 891400		OFFSET: 2						
CKD D6P TECH. D.M.		RIG: AIR		SURFACE DRAINAGE: GOOD		VEGETATION: SPRUCE TO 30'		ELEV.						
TEST HOLE		MILE		S.C.S.		NOVEB								
DIPIN (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION (L.SISTANCE)	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	<div style="display: flex; justify-content: space-between;"> <div> ○ WATER CONTENT (% OF DRY WEIGHT) ○ ICE CONTENT (% OF SAMPLE VOLUME) </div> <div> PLASTIC LIMIT 20 40 60 80 100 100+ LIQUID LIMIT 90 </div> </div>	CLAY % SILT % SAND % GRAVEL %	WET DENSITY (PCF)	DRY DENSITY (PCF)	REMARKS	
2						GRAVEL	F							
4						SANDY, SOME SILT	UF							
6														
8														
10						FINE SAND, VERY HARD FROM 9 1/2								
12						END OF HOLE								
14														
16														
18														
20														
22														
24														

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT		DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY													
DATA A-EW		FIELD ENG. B.M.	DATE DRILLED 9/11/73	AIRPHOTO NO.	CHAINAGE 691100	OFFSET 2	TEST HOLE												
CKO DGP		TECH. DM	RIG AIR	SURFACE DRAINAGE GOOD	VEGETATION SPRUCE, POPLAR & BIRCH			ELEV											
DEPTH (FT.)	SAMPLE NO.	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	WATER CONTENT (% OF DRY WEIGHT)	ICE CONTENT (% OF SAMPLE VOLUME)	GRAIN SIZE ANALYSIS				WET DENSITY (P.C.F.)	DRY DENSITY (P.C.F.)	MILE	B.C.S.	NUMBER
											CLAY	SILT	SAND	GRAVEL			459	B	1582
																			REMARKS
2					GM	GRAVEL		F											
4						SILT, SAND	UF												
6					GW														
8						VERY HARD													
10					GP	FINE SAND													
12						END OF HOLE													
14																			
16																			
18																			
20																			
22																			
24																			

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY										
DAN A.E.W.		FIELD ENG R.S.		DATE DRILLED 9/11/73		AIR PHOTO NO:		CHANNAGE 871+00		OFFSET 2		TEST HOLE						
CKD D6P		TECH D.M.		RIG DIR		SURFACE DRAINAGE:		VEGETATION: CONIFER TO 60'		ELEV								
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS				WET DENSITY (G/CC)	DRY DENSITY (G/CC)	MILE	D.C.S	NO. FEET
										CLAY %	SILT %	SAND %	GRAVEL %					
										○ = WATER CONTENT (% OF DRY WEIGHT) △ = ICE CONTENT (% OF SAMPLE VOLUME)								
										PLASTICITY CHART 20 40 60 80 100 100+								
2						PEAT - MUSKEG			2									
4						GRAVEL			4									
6						FINE SILT			6									
8						MED. COARSE SAND WITH BOULDERS			8									
10						COARSE SAND			10									
12									12									
14									14									
16						END OF HOLE			16									
18									18									
20									20									
22									22									
24									24									

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY										
DATA A.E.W.		FIELD ENG. R.S.		DATE DRILLED 9/1/73		AIRPHOTO NO:		CHANCE 871400		OFFSET 2		TEST HOLE						
CKD D6P		TECH: D.S.		RIG: AIR		SURFACE DRAINAGE:		VEGETATION: CONIFER TO 60'		ELEV:								
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNITED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FT)	GRAIN-SIZE ANALYSIS				WET DENSITY (PCF)	DRY DENSITY (PCF)	MILE	B.C.S.	INVEST
										CLAY %	SILT %	SAND %	GRAVEL %					
										C = WATER CONTENT (% OF DRY WEIGHT) Δ = ICE CONTENT (% OF SAMPLE VOLUME)								
										PLASTIC LIMIT ——— LIQUID LIMIT 25 ——— 40 ——— 60 ——— 100 ——— 100+								
2						GRAVEL			2									
4					GM	FINE, DRY			4									
6									6									
8									8									
10						SAND			10									
12					SP	MED FINE TRACES OF GRAVEL			12									
14									14									
16									16									
18						END OF HOLE			18									
20									20									
22									22									
24									24									

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY											
DATA A-EW		FIELD ENG. 7.5		DATE DRILLED 9/11/73		AIRPHOTO NO.		CHAINAGE 871+00		OFFSET 2		TEST HOLE							
CKD DGP		TECH. DM		RIG AIR		SURFACE DRAINAGE		VEGETATION SPRUCE TO 60'		ELEV									
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS				WET DENSITY (P.C.F.)	DRY DENSITY (P.C.F.)	MILE 459	S.C.S. B	NUMBER 127A	REMARKS
										CLAY %	SILT %	SAND %	GRAVEL %						
2						GRAVEL			2										
4						SANDY, SILTY			4										
6									6										
8									8										
10						SANDY			10										
12									12										
14									14										
16						LOOSE, SANDY			16										
18						SOME COBBLES			18										
20									20										
22						SOME SILT			22										
24						END OF HOLE			24										

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY										
DRAWN A.E.W.		FIELD ENG. B.M.		DATE DRILLED 9/11/73		AIR PHOTO NO.		CHAINAGE 831+00		OFFSET 300' E OF W		TEST HOLE						
CKD 06P		TECH. D.M.		RIG AIR		SURFACE DRAINAGE FAIR		VEGETATION: SPACE TO 35'		ELEV.								
DEPTH (FT.)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBO.	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FT.)	GRAIN-SIZE ANALYSIS				NET DENSITY (P.C.F.)	DRY DENSITY (P.C.F.)	MILE	S.D.S.	NUMBER
										CLAY	SILT	SAND	GRAVEL					
									C = WATER CONTENT (% OF DRY WEIGHT) Δ = ICE CONTENT (% OF SAMPLE VOLUME)									
									PLASTIC LIMIT ——— LIQUID LIMIT 20 40 60 80 100									
									%									
2					Fe	FEAT - FINE FIBROUS, MUSKEG			2									
4						CLAY			4									
6						SILTY, ROOTS TO 2'			6									
8						MOIST,			8									
10					CL			Nbc	10									
12									12									
14						GREY, TILL LIKE, SOME EXCESS ICE			14									
16									16									
18						END OF HOLE			18									
20									20									
22									22									
24									24									

UNDERWOOD McLELLAN & ASSOCIATES LIMITED										DRILL HOLE REPORT										DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY									
CAP. AEW			FIELD ENG. BM			DATE DRILLED 9/1/73			AERIAL PHOTO NO.			CHANNEL 831+00			OFFSET 300' E OF &			TEST HOLE											
CKD DGP			TECH DM			RIS AIR			SURFACE DRAINAGE FFR			VEGETATION SPRUCE TO 35'			ECLL														
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIFIED SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	WATER CONTENT (% OF DRY WEIGHT) ICE CONTENT (% OF SAMPLE VOLUME)	GRAIN-SIZE ANALYSIS				WET DENSITY (PCF)	DRY DENSITY (PCF)	MILE	S.C.S.	ALVEOL											
										CLAY %	SILT %	SAND %	GRAVEL %																
2	P				Pe	PEAT - FINE FIBROUS, MUSKIE																							
4	P				CL	CLAY GREY, SILTY, VERY HARD, FINE SAND, SOME WOOD FIBRE		V+ EXCESS ICE ≤ 5%							99.5	71.0													
6																													
8																													
10	P				SM	SAND SOME SILTY CLAY		V+							95.1	62.9													
12																													
14	P				CL	CLAY SILTY		EXCESS ICE ≤ 5% V+							103.9	74.8													
16						END OF HOLE																							
18																													
20																													
22																													
24																													

UNDERWOOD McLELLAN & ASSOCIATES LIMITED				DRILL HOLE REPORT				DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE HIGHWAY										
DATE: AEW		FIELD ENG: B.M.		DATE DRILLED: 9/1/73		AIRPHOTO NO:		CHANGE: 851+00		OFFSET: 300' E OF L		TEST HOLE						
CKD: D.S.P.		TECH: D.M.		RIG: AIR		SURFACE DRAINAGE: FAIR		VEGETATION: SPRUCE TO 35'		ELEV:								
DEPTH (FEET)	SAMPLE NUMBER	SAMPLE TYPE	% RECOVERY	PENETRATION RESISTANCE	UNIT SOIL SYMBOL	SOIL DESCRIPTION	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (FEET)	GRAIN-SIZE ANALYSIS				WET DENSITY (PCF)	DRY DENSITY (PCF)	MILE	E.C.S.	NUMBER
										CLAY %	SILT %	SAND %	GRAVEL %					
2						PEAT FINE, FIBROUS, MUSKEG			2					107.8	72.8			
4						CLAY VERY HARD, SOME SILT, SILTY, LITTLE SAND		V _p EXCESS ICE 25%	4									
6		P							6									
8									8									
10		P				SOME WOOD FIBRE CHIPS FIRM			10									
12									12									
14						SAND LENSE - 9"		EXCESS ICE 25% V _p	14									
16		P							16									
18						END OF HOLE			18									
20									20									
22									22									
24									24									