

ISSUE #39



Underwood McLellan & Arrociater Limited

2540 KENSINGTON ROAD N.W., CALGARY, ALBERTA 12N 353 TELEPHONE 283-4901 TELEX 038 24505

OUR THE NO 2106-032-45 April 6, 1973

Department of Public Works P. O. Box 488 Edmonton, Alberta

Attention: Mr. F. E. Kimball, Project Manager

Dear Sir:

Re: Subsurface Soil Investigation Rainbow Creek Bridge, Mile 471.6 Mackenzie Highway

Attached please find our report on the subsoil and foundation conditions for the proposed Rainbow Creek Bridge on the Mackenzie Highway in the Northwest Territories.

If you have any questions concerning the contents of this report, we would be pleased to discuss them with you at your convenience.

Yours very truly,

UNDERWOOD MCLELLAN & ASSOCIATES LIMITED

Per:

D. G. Pennell, Ph.D, P.Eng.

DGP/al

REPORT ON SUBSURFACE SOIL CONDITIONS FOR THE PROPOSED RAINBOW CREEK BRIDGE MILE 471.6 MACKENZIE HIGHWAY NORTHWEST TERRITORIES

Prepared By:

Underwood McLellan and Associates Limited Consulting Professional Engineers

INDEX

		Page	No	's.
Α.	INTRODUCTION	1	-	2
в.	FIELD AND LABORATORY INVESTIGATION PROCEDURES	3		6
с.	SITE AND SUBSOIL CONDITIONS	7	-	11
D.	CONCLUSIONS AND RECOMMENDATIONS	12	-	23
	1. Pier and Abutment Foundation Design			
	2. Lateral Abutment Loads			

3. Bridge Approach Grades and Borrow Material

APPENDIX

Explanation of 1	Field and Laboratory Data Page 1 - 6
Plate l	Mosaic and Test Hole Location Plan.
Plate 2	Bridge Site Profile and Soil Cross- Section.
Plate 3	Photographs of Bridge Crossing.
Plate 4 - 16	Centreline and Structure Test Hole Logs.
Plate 17 - 24	Porrow Dit Wort Volo Lord

Plate 17 - 24 Borrow Pit Test Hole Logs.

A. INTRODUCTION

The subsoil investigation undertaken at the Rainbow Creek forms part of the overall geotechnical investigation which was conducted from mile 450 to 550 on the Mackenzie Highway for the Department of Public Works, Government of Canada.

The present report summarizes the results of the geotechnical investigation conducted in connection with the proposed Rainbow River bridge, mile 471.6. This report deals specifically with the design of the bridge abutments and piers and approach fills and cuts.

It was the intention of the present investigation to determine the vertical sequence of the subsoil materials, together with certain physical and structural properties, permafrost conditions and ground water conditions.

The included conclusions and recommendations have been based upon exploration and sample acquisition

- 1 -

operations conducted at a total of 13 positions on or near the centreline of the proposed roadway at the bridge site and along the adjacent river banks.

In the formulation of conclusions and recommendations the consistency and composition of the subsoil materials between and proximity to the individual test boring position has been assumed but not verified.

B. FIELD AND LABORATORY INVESTIGATION PROCEDURES

A total of 13 test holes have been drilled within one-half mile of the bridge structure. In addition to the test hole logs located nearest to the bridge site several borrow pit test holes have been included in the Appendix. Test holes along the centreline were drilled to depths ranging from 12 to 50 feet below existing side grades and the borrow pit test holes were generally advanced to the 15 foot level.

Test holes were drilled December 1, 2, 26, 29 and 30, 1972 and January 13 and 14, 1973, by Kenting Big Indian Drilling of Calgary, utilizing a Mayhew 1000 and Heli drill. Air recovery methods were generally employed except where caving was encountered at bridge crossings, water and drilling mud circulation was employed.

The locations of the individual test borings were selected and field located by Underwood McLellan & Associates Limited. The approximate test boring

- 3 -

locations are graphically illustrated on the accompanying Mosaic and Test Hole Location Plan.

All variations of soil, permafrost and ground water conditions encountered during the test drilling operations were noted and representative samples of existing subsoils were taken. The majority of samples were disturbed having been obtained by the air recovery method. Samples were also undertaken with 2" and 3" O.D. split spoon sampling tubes.

In the laboratory, samples of materials derived from the drilling operations were subjected to standard laboratory classification procedures including particle size distribution and Atterberg index property determinations. Moisture contents were obtained for all samples returned to the laboratory and whereever a sufficient length of intact sample was retained in the penetrometer tube, both wet and dry densities were obtained. Permafrost samples were classified according to N.R.C. Technical Memorandum

- 4 -

No. 79 "Guide to the Field Description of Permafrost". The excess ice content of permafrost samples was determined by visual inspection and by measured thicknesses of ice lenses. The calculation of excess ice content was performed by division of ice thickness by the total sample thickness.

All soil samples were classified according to the Unified Soil Classification System.

The results of all laboratory and field tests are summarized in the Appendix on the test hole logs.

Test holes have been designated by mileage, type and number. Examples of test holes designations include 471S 138A, 470C 27B, and 470B 222B;

471, 470 - mileage

S, C, B - these letter symbols between mileage and test hole numbers refer to structures, centreline and borrow pit logs, respectively.

138, 27, 222 - indicate test hole numbers.

- 5 -

A, B - these letters occurring after test hole numbers indicate the drilling rig utilized. A - refers to the Mayhew 1000 and B to the Heli drill.

C. SITE AND SUBSOIL CONDITIONS

The Rainbow bridge site is located at mile 471.6 (chainage 1053 + 00) of the Mackenzie Highway in the Northwest Territories. The Rainbow Creek flows into the Mackenzie River from the east having a drainage basin which extends to the Franklin Mountains. The stream has a typical sand-gravel bed which is presently in a state of depositing floodplain sediments at the entrance to the Mackenzie River.

The Rainbow stream bed elevation is approximately 366 (DPW datum) and the recently estimated high water mark near the proposed bridge site as a result of ice jams on the Mackenzie River is at elevation 393.0.

The existing Rainbow stream channel is approximately 325 feet wide and 35 feet deep at the proposed bridge site location.

In general, the overburden material which exists at the location of the bridge site and approach

- 7 -

2

fills is composed of granular sands and gravels which were deposited on the river terraces when the river flowed at higher elevations.

Test holes 33B, 34B, 35B and 140A drilled at the edge of the stream channel were advanced to depths of 40, 35, 23 and 12 feet below existing site grades, respectively.

These test holes in the river channel generally indicated approximately 8 to 10 feet of gravel and sand overburden materials except test hole 140A on the north bank, which disclosed approximately 4 feet of granular material. Below the granular material a 6 foot depth of weathered clayey shale was found. The weathered shale was underlain by a very hard fissile grey shale which constitutes the bedrock at the site. This Cretaceous shale or siltstone bedrock is low plastic, exhibiting a plastic limit of 18% to 22% and a liquid limit from 26% to 31%. The average natural moisture content of 7% is well below the plastic limit and generally confirms the dense

- 8 -

nature of the bedrock strata. The boulder nature of the overburden materials would not allow the performance of field, penetration tests and the utilization of drilling mud and water prevented accurate determination of the permafrost condition. But in general it has been concluded that the materials below the stream bed at the site were unfrozen.

The water level was present at approximately 4 feet below the ground surface in test hole 33B. This water level was approximately coincident with the river level at the time of drilling.

Test holes 137A and 50A were drilled on the north river banks above the approaches to the bridge, to depths of 30 and 18 feet, respectively below the existing sites grades. These two test holes indicated that a surface gravel and sand mixture existed to depths of 18 feet which was underlain by approximately 12 feet of very dry sand. Numerous samples obtained from the gravel strata indicated that

- 9 -

approximately 60% to 85% of the material was larger than the #4 sieve. In addition, these materials were unfrozen and exhibited moisture contents of approximately 6%.

Test holes 51A, 229B, 32B and 138A were drilled 20 to 50 feet below the surface. These test holes again indicated that the overburden was primarily gravel and sand deposited as a terrace, but in addition, the upper holes exhibited a surface strata of approximately 6 feet of light brown silty clay. The shale bedrock was encountered at 3 of the 4 test holes on the south bank and there was approximately 20 feet of overburden.

The bedrock and overburden materials are shown on the geologic profile which is included in the Appendix. The permafrost condition was again difficult to establish because of the wet drilling process but there appears to be some frozen areas on the slope and in all cases the moisture contents of the granular materials were below 10%, except

- 10 -

for test hole 138A which was drilled at the lower portion of the bank and in which free water was encountered.

The gravel samples which were obtained during drilling operations were subjected to crushing during drilling and would exhibit a true gravel and boulder size content higher than obtained from sieve analyses.

In conclusion, the test holes which were drilled throughout the Rainbow Creek valley generally indicated a granular overburden of 10 to 20 feet which was underlain by a shale bedrock.

D. CONCLUSIONS AND RECOMMENDATIONS

On the basis of the present investigation, we wish to offer the following generalized conclusions and recommendations relative to the design and construction of the proposed Rainbow Creek bridge and approaches.

1. Pier and Abutment Foundation Design

The relatively shallow depth of the granular overburden at this site allows the consideration of a shallow spread footing foundation type or driven piles. Although the depth to bedrock would allow the establishment of pier and abutment footings, variation in bedrock elevation exists and extreme difficulty will be experienced in excavation of overburden materials for footings. Therefore a driven pile foundation is recommended for all structures.

The pile types generally available include timber,

- 12 -

pre-cast concrete, steel H-piles and pipe piles. The timber piles are not recommended as a result of their low capacity and possible damage when driving through gravel strata. The pre-cast piles are also not recommended because splicing becomes difficult and expensive, whenever it is not possible to establish the exact ultimate pile length.

Steel H-piles or pipe piles are, therefore, recommended for consideration primarily based on high driving strength, high load capacity and relative splicing ease. The granular strata at this site will provide adequate lateral support such that instability in the form of buckling of the piling will not be a problem.

It is recommended that all piles be driven to "refusal". "Refusal" will depend upon the energy rating of the hammer but is commonly 15,000 ft.-lbs. As an initial guide piles should be driven to blow counts of 180 blows

- 13 -

per foot, or 15 blows per inch. Pile capacity is largely a function of the amount of energy expended in installing the pile and not just on the recorded resistances. The pile which is driven to a sustained resistance will perform better than one which is terminated the instant a given resistance is attained. Of course, the pile must not be driven whenever damage may result and whenever resistance increases significantly, the driving should be terminated.

At the Rainbow Creek site, it is anticipated that steel pipe or H-piles will be approximately 15 to 20 feet in length. The exact depths of the steel pipes will depend upon the weathered shale zone depth which varies across the stream channel. It is anticipated that the allowable ultimate capacity of each pile will be in the range of 80 tons, and will depend upon the x-section utilized. The capacity of the piles should be established in the field by several

- 14 -

pile driving tests. The ultimate capacity would be calculated on the basis of a dynamic piledriving formulae such as the Hiley, Danish, or Weisbach. It is recommended that the Engineering News Formula not be utilized as a result of extreme variation in factor of safety.

It is further recommended that static load tests be performed to establish more accurately the bearing capacity of a typical steel pile and the applicability of dynamic pile formulae for capacity prediction. At this, site refusal will be attained in the bedrock but some difficulty will be experienced in penetration of boulders in the gravel strata. Vibratory procedures may be utilized to provide advancement of the pile to the bedrock.

The lateral resistance of piles can be established by recently developed methods based on the beam on elastic foundation method but the simple and more conventional approach is based on calculation of the Rankine passive earth pressure against the pile.

- 15 -

Using Rankine theory the ultimate passive resistance force/ft.² of pile can be obtained by $P = \frac{1}{2} \chi_{b} K_{p} H^{2}$. The submerged unit weight of the granular material may be taken as 60 pcf and the passive pressure coefficient K_{p} as 3.0. In order to establish the allowable lateral load a factor of safety of 2.5 should be applied to the above ultimate load. Generally, in cohesionless soils the lateral load tends to exceed the passive resistance and the above simplified approach is on the conservative side.

Wherever the deep embankments are constructed of compacted granular fill as outlined and recommended in section D3, the abutments may be placed on spread footings in the fill. If inferior material or compaction techniques are utilized in the embankment, the abutments must be carried on piles to refusal in the bedrock. Piles must be designed to carry a negative skin friction load whenever embankment fills may undergo settlement.

- 16 -

2. Lateral Abutment Loads

The magnitude of the pressure applied to the abutment will depend upon the characteristics of the backfill chosen for the approach fill and upon the movements that the wall undergoes during and subsequent to fill compaction. It is recommended that granular backfill from the river terraces or borrow pits be utilized for the abutment approach embankments which will be in the order of 30 feet high.

The most common procedures for analysis of the earth pressures against gravity retaining walls include Rankine and Coulomb methods.

Generally, it is assumed that the wall rotates sufficiently to allow mobilization of the backfill shear strength which reduces the pressure to the active case, the lowest pressure that can be realized. This assumption applies reasonably accurately when the backfill consists

- 17 -

of uncompacted granular material but pressures greater than the active occur wherever compaction of the backfill is undertaken. While the total yield at different elevations on the abutment may be adequate for mobilization of the full backfill strength, a gradual build-up of the backfill also results in a gradual yielding of the wall. Therefore, by the time the backfill is complete only a fraction of the total vield of the wall has become effective in decreasing the earth pressure. At the present time it is accepted that the actual earth pressure magnitude will exceed the active case and may approach the earth pressure at rest. Pressures greater than the at-rest case may occur if heavy equipment is utilized near the concrete abutment.

If the Coulomb approach is utilized, the angle of wall friction between concrete and coarse sand and gravel would be 20 degrees. The

- 18 -

angle of internal friction for compacted granular material would be 38 degrees and the dry density may be taken as 115 pcf. For a simple vertical retaining wall abutment with horizontal backfill the Coulomb active coefficient would be .24 and the at-rest coefficient based on $K_0 = 1 - Sin \emptyset$ would be .38. The Rankine procedure which disregards the wall friction would also result in an active coefficient of Whenever the wall or backfill are inclined .24. or a surcharge exists, the Coulomb procedure will result in a lower active pressure which will be more exact than the conservative Rankine method. The pressure distribution behind a gravity retaining wall has been shown to be non-triangular, but as a first approximation and for simplicity, the triangular pressure diagram is recommended. Ιt is also recommended that whenever backfill is compacted in lifts by vibratory compactors the at-rest coefficient may be utilized for calculation of the ultimate earth pressure.

- 19 -

A driven pile foundation has been previously recommended for the abutments which will provide significant lateral resistance but it is further recommended that some batter piles be utilized to ensure adequate lateral support against earth pressures.

Positive drainage including horizontal perforated tile and weep holes should be provided to prevent development of hydrostatic pressure against the wall. In addition, free drainage of water will prevent the development of frost heaving pressures against the walls.

3. Bridge Approach Grades and Borrow Material

The proposed centreline grades at the Rainbow Creek valley will not involve cuts but will be entirely fill. The proposed fills will vary from 30 feet in depth at the bridge abutment to approximately 3 - 5 feet above the main stream channel valley. On the north side of the river

- 20 -

these relatively shallow fills will directly overlie unfrozen gravel and sand deposits and, therefore, these fill depths are considered adequate and performance should be satisfactory. Near the south approach banks at station 1058 + 00 these fills overlie approximately 6 - 8 feet of It is anticipated that silty clay permafrost. thawing of the subgrade will occur with the 3foot fills and therefore it is recommended that in these areas on the south bank, the fill depths be increased to at least 6-feet if granular materials are utilized. It is recommended that granular fill be used in all approach fills to the bridge abutments and this material should be compacted to 95% of Standard Proctor density utilizing vibratory compaction. Although construction may be performed during the winter, the dry unfrozen nature of the granular materials will allow satisfactory compaction. Compaction of these deep approach fills is mandatory to ensure stability

- 21 -

and in addition, fill slopes are proposed at 2:1 whenever compacted granular materials are utilized.

Common excavation will not be available from the valley slopes as the grade line has been proposed entirely in fill. Satisfactory granular embankment is available throughout the river terraces but its utilization as a construction material may be prohibited by land use regulations. Suitable borrow pits have been located on the north and south upland areas. One gravel borrow pit was located approximately one mile south of the proposed bridge site at station 1104 + 00 and consisted of suitable low moisture content frozen gravel materials.

Another borrow pit on the south side was located at 1056 + 00, 500-feet east of the proposed centreline and consisted of suitable low moisture content gravel. On the north side at station 1025 + 00 a borrow pit approximately 1/2 mile from the bridge site was investigated

- 22 -

but consisted of a silty clay which is not recommended for fill at the bridge approaches.

•

APPENDIX

EXPLANATION OF FIELD & LABORATORY TEST DATA

The field and laboratory test results as shown for a particular test boring by the Test Hole Log Data Sheet are briefly described below:-

NATURAL MOISTURE CONDITIONS & ATTERBERG LIMITS

The relation between the natural moisture content and depth is significant in determining the subsurface moisture conditions. The Atterberg Limits should be compared to the Natural Moisture Content of the subsurface soil as well as plotted on the Plasticity Chart.

SOIL PROFILE & DESCRIPTION

Each soil strata is classified and described noting any special conditions. The unified classification system is used, and the soil profile refers to the existing ground elevation. When available the ground elevation is shown.

The soil symbols used are briefly shown below but are indicated in more detail in the Soil Classification Chart.



TESTS ON SOIL SAMPLES

Laboratory and field tests are identified by the following symbols:

- QU unconfined compressive strength usually expressed in tons per square foot. This value is used in determining the allowable bearing capacity of the soil.
- Jd dry unit weight expressed in pounds per cubic foot. This value indicates the density or consistency of the in-situ soil.

- Consolidation test. These test results are separately С enclosed and provide information on the consolidation or settlement properties of the soil strata.
- grain size analysis. These test results are separately M.A. enclosed and indicate the gradation properties of the material tested.
- water soluble sulphate content is conducted primarily SO4 to determine whether sulphate resistant cement is required for the foundation structure.
- N standard penetration field test. This test is conducted in the field to determine the in-situ consistency of The "N" value recorded is the number of a soil strata. blows from a 140 lb. hammer dropped 30 inches (free fall) which are required to drive a 2" O.D. Raymond type sampler 12 inches into the soil.

The resistance and unconfined compressive strength of a cohesive soil can be related to its consistency as follows: -

N - BLOWS/Ft.	$QU - T/Ft.^2$	CONSISTENCY
2	0.25	very soft
2-4	0.25-0.50	soft
4-8	0.50-1.00	medium or firm
8-15	1.00-2.00	stiff
15-30	2.00-4.00	very stiff
30	4.00	hard

The resistance of a non-cohesive soil (sand) can be related to its consistency as follows: -



2 -

SAMPLE CONDITION AND TYPE

The depth and condition of samples are indicated by the following symbols:

9		
UNDISTURBED	DISTURBED	LOST SAMPLE

SAMPLE TYPES

T - 3" O.D. Shelby tube sample

P - penetration tube sample

C - rock core sample

PERCENTAGE WATER SOLUBLE SULPHATE CONCENTRATION

0 0.1 0.2 0.3 0.4 0.5 0.6 0.7%

Negli- gible	Posi- tive	Considerable	Severe
	RELATIVE	DEGREE OF SULPHATE ATTAC	<u>CK</u>

Negligible - Normal Portland Cement may be used.

<u>Positive</u> - Normal Portland Cement may be used, provided the strength of the concrete is increased up to 500 psi higher than the compressive strength which would normally be used.

<u>Considerable</u> - Type V cement must be used and the concrete compressive strength should be increased to 500

- 3 -

psi higher than the compressive strength which would normally be used.

<u>Severe</u> - Type V cement must be used and the concrete compressive strength should be increased from 500 to 1000 psi higher than the compressive strength which would normally be used.

GROUND WATER TABLE

The water table is indicated by the level of standing water in a test boring after equilibrium has been reached. This is generally taken 24 hours after the drilling operation. The water table is usually an inclined surface that is dynamic in nature with its highest level late in the winter or early spring gradually falling throughout the summer.

UNDERWOOD MILELLAN & ASSOCIATES LIMITED



2



.

SOIL CLASSIFICATION CHART

MOTE: DUAL SYMBOLS ARE USED TO INDICATE BORDERLINE SOIL CLASSIFICATIONS.

M	AJOR DIVIS	IONS	GRAPH SYMBOL	LETTER SYMBOL	TYPICAL DESCRIPTIONS
	GRAVEL AND	CLEAN GRAVELS		GW	*ELL-GRADED GRAVELS, DRAVEL- Sand Mertures, Little or ag fines
COARSE GRAINED	SCILS	Fines)		GP	POORLY-GRADED GRAVELS, GRAVEL- Samu Nixtubes, Little or No Fines
30/123	WORE THAN SON	GRAVELS WITH FINES		GM	SILTY BRAVELS, GRAVEL-SAND- SILT WIRTURES
	ON NO.4 SIEVE	OF FINES)		GC	CLAVEY BRAVELS, GRAVEL-SARD- CLAY MIXTURES
	SAND AND	CLEAN SAND (LITTLE		sw	WELL-GRADED SANDS, GRAVELLY Sands, Liftle or no fines
WORE THAN SON	SOILS			SP	POORLY-GRADED BANDS, GRAVELLY Samds, Little or MG Fines
200 SIEVE SIZE	MORE THAN SOL OF COARSE FRAC-	SANDS WITH FINES (APPRECIABLE AMOUNT		SM	SILTY SANDS, SAND-BILT WIXIWES
	TICH PASSING NO. 4 SIEVE	OF FINES)		SC	CLAVET SANDS, SAND-CLAV MIXTURES
	1 1 -			ML	INDRGANIC SILTS AND VERY FINE SANDS, ROCE FLOUR, SILTY OR GLAYEY FINE SANDS OR GLAYEY SILTS WITH SLIGHT PLASTICITY
GRAINED SOILS	SILTS AND CLAYS	LIQUID LINHT		CL	INDRGANIC CLAYS OF LOW TO MEDIUM PLASTICITY, GRAVELLY CLAYS, Sandy Clays, Silty Clays, Lfam Clays
				OL	GRGANIC SILTS AND ORGANIC Silty Clays of Low Plasticity
				мн	INDRGANIC SILTS, MIGACEQUS GA Diatomaceous fing sand or Silty soils
MORE THAN SON OF MATERIAL IS SMALLES THAN NO. 200 SIEVE SIZE	SILTS AND QLAYS	GREATER THAN SO		СН	INORGANIC GLAYS OF HIGH PLASTICITY, PAT CLAYS
				он	CREANIC CLAYS OF MEDIUM TO NIGH Plasticity, organic silts
. н	CHLY ORGANIC SOL	.5		PT	PEAT, HUMUS, SWAMP BOILS WITH HIGH ORGANIC CONTENTS

UNIFIED SOIL CLASSIFICATION SYSTEM

NATIONAL RESEARCH COUNCIL PERMAFROST CLASSIFICATION SYSTEM

Permafrost ground ice occurs in three basic conditions including non-visible, visible (less than one inch in thickness) and clear ice.

A. <u>Non-visible</u> - N

 N_{f} - poorly bonded or friable frozen soil N_{bn} - well bonded soil, no excess ice N_{be} - well bonded soil, excess ice

B. <u>Visible</u> - V (less than 1" thick)

 V_x - individual ice crystals or inclusions

V_c - ice coatings on particles

V_r - random or irregularly oriented ice formations

V_s - stratified or oriented ice formations

C. <u>Visible Ice</u> - (greater than 1" thick)

Ice - ice with soil inclusions

Ice + Soil - ice without soil inclusions.

A more complete description of this system is included in NRC publication TM 79.

-6-



					••••••••••••••••••••••••••••••••••••••						(A-
						U Z	2 2				
460			. •		· · ·	1001	50				
and the second	anana ar singer bi si nationalise ange				, -	I L	I		1		
440				•	1 .	N CN	C Q				
			n an ann ann an ann ann ann ann ann ann		антан рады талана уш түрдө - октору у акфур аруылдады. 11	Û	0	PROPO	SED & GRAD		
420					و معرف المراجع	S O	9 9 0				<u> </u>
						ROF	20			·	4
400		CLAY	\sim		SAND SAN	J JA		SILT CLAY	• •		2 1
	23	68			GRAVEL GRAVE	L GREEL	CLAY	SAND GRAVI	1 .		:
380	ر		· · · · · · · · · · · · · · · · · · ·	l - - 	50A SANE	53	GRAVEL	GRAVEL SHALI	5 		
							RAVEL 328	SHALE	* *		
360		 		· · · · · · · · · · · · · · · · · · ·	(i	37A)	JE GRAVE		 	ی ا بر بر	
					an a	SHALL	W W SHAL	T E Good			•
340			·				ASCI N A	, .			
					n - Englisher ganner Englisher ganner	55					
320	·.	1	•				338	nnag – anna galantar maga kaga a carganaga kasan nagar - cara kagan da			
				: :					•		:
300	· · · · · ·						· · · · · · · · · · · · · · · · · · ·	····· · · · · · · · · · · · · · · · ·			
	÷										•
				• • •							1479 8 1 973 996
									ł		
	99 - 79 - 11 - 11 - 11 - 11 - 11 - 11 -			· · · · · · · · · · · · · · · · · · ·					.	ی ایر ایر ایر	
		• • • • • • • • • • • • • • • • • • •									
			4	···· · · · · · · · · · · · · · · · · ·				·			
	1030	00	1040 Backing	+ 00)(050 00		1060	100	Drewn: H.S.)+0(
					Abbien en		ERWOOL	McLELL	AN This	Checked: D.G.P.	
						& AS	SOCIAT	ES LIMIT		Tracéd :	
		-					-	ENGINEERS - TOWN P	LANNERS	AS SHOWN	PR
			······································		1	SRITISH COLL	UNDIA) & ALBERTA	• BABKATCHEWAN •	MANITOBA • ONTARIO		
				1		A State	1				4





South Bank of Rainbow Crossing looking South Westerly.



North Bank of Rainbow Crossing Viewing along & of Crossing.



Sec. Sec.



South Bank of Rainbow Crossing looking South Westerly.





North Bank of Rainbow Crossing Viewing along b of Crossing.



South Bank of Rainbow Crossing Viewing in a Southerly Direction.



South Bank of Rainbow Crossing Viewing along & of Crossing.

UNDERWOOD MeLELLAN & ASSOCIATES	DRILL H	IOLE	REPORT	DEPARTM	ENT OF MACKE	PUBLIC W	ORKS, HWAY	, CANADA
CAN A.F.W FIELD ENG B.M. DATE DRILLED /4//73 AIRPHO	TO NO:		CHAINAGE: 10	30 +00	OFFSET	L.	Ì	TEST HOLE
			VEGETA	THOM SPRUCE & BIRCH	10 20 GRA	AIN- SIZE		MILE B.C.S NUMPER
SOIL DESCRIPTION		E 0 -	WATER CONTENT	(% OF DRY WEIGHT)				(7) C 236 B
	440		ICE CONTENT (9	6 OF SAMPLE VOLUME)	CLA	SAL SAL		
			20 LIMIT	60 80 :00	100+ %	% % %	3 . 3	REMARKS
CLAY F								
2	V	2						· · ·
DARK, SANDY								
		4	<u></u>					
								•
.5		6		╞╼╾┼╾╴┝╼╌┝╶╴				
								•
								•
10 LIGHT, SANDY		10						
SOME GRAVEL								
12-		12						
			╺╍╀╂╂╺┼╍╸					•
	V+	14						
								•
END OF HOLE		16						
								•
zc		20						
			┝╾╼┟╶╺╂╌━╡╌╼	┼╌╽╴╽╺╁╍┽╸╏╴	·			
22		22		┥━╌┝━╍┝╾╍┝╍╌┥╾╍┥━				
24		24						•

-																					1							
	UN	DE	RW	00	D	McI Ll	ELLAN & ASSOCIATES	5	DRILL	НО	LE	REI	POR	Г			DEF	PART	MENT MA(OF CKE	PU NZI	BLI	C V HIC	VOH	IAY	, CAN	404	
F	DWN:	A E	₩. Q	FIEL	D E!	NG D. N	T. S DATE DRILLED: 26/11/12 AIRP	HOT	O NO: DRAINAGE:	FLA	7	CHAIN	AGE:	/ SETA	047+	CON	P	OPLAR,	OFF	SET:	ELE	<u>Q</u> V: -	104	38		TEST	HOLE	;
Ī		-		>	2	7		g	ICE		Í									GRA	N- S	IZE S		7	2	MILE	8,C,S	NUMBER
	H L	. 835 56.8	5	COVER	RATIO	1E0 \$7M80	SOIL DESCRIPTION	K GRO	DESCRIPTION	FTH EET)		= WATER	R CONT	ENT	(%) 6 OF	OF D	RY WI	EIGHT) /OLUMI	=)	Α.	5	2	AVEL	SENSIT	C F)	411	С	50A
	ē.	NUN	SAMP TYP	% ¥6	PENET RESIS	UNIF		FROZE		25			PLAST	ic				2		5 %	·5 %	20 2/0	5 %	NET O	DRY (R	EMARKS	
ł							SAND						_			<u></u>		·	100 100+		1							
	2							UF		2		0								2	יי 7	73.						
			$ \ge$				FINE, SOME GRAVEL		•			\mathbb{V}^+					_				2	-						
	4								•.	4		1						-										
	6		\sum			SW				6	Д																	
							•.		· .		H					_												
	8								· · · ·	8	Ħ	┨──┤─				_								·				
	n.						· ·			10	Ħ									11	<u>,</u>	39	50					
			ert									$\left - \right $		-					 		1							
	12									12	┢┥									1								
	14						GRAVEL			14	Ħ									1			ļ					
											ł			-				_		{	ľ.						-	
	16-		\vdash		ŀ	GW	SANDY			16	+	┼─┼		-						ŀ								
	10						Some Rocks			1 18									· ·						Ì			
			\square				COARSE SAND				4	1								Ι,		52	24					
	20		\vdash							20	+			┼─		-				¦ '	ſ	136	'					
	22						END OF HOLE			22										1								
	~~				1	. 					·		_ _		<u> </u>				. 	-								•
	24									24		┼──┞		+						-								
l		L ;	1 1	 1	- L	- i	[ا من عد ا	l	- احمد ۱	- -	i I		- -		i	ا ــــا ۱		• I •-	- L	- 	. . .		 ;	i lanna i			**** ********************************

4

UNDERWOOD MCLELLAN & ASSOCIATES	DRILL	но	LE REPORT	DEPARTMENT	OF			WORKS GHWA	S, CANADA
DATE DRILLED 14/1/73 AIRPHO	TO NO:		CHAINAGE: 10	49 + 00 OF	FSET	r			TEST HOLE
CKS USP TECH DM RIG AIR SURFAC	E DRAINAGE: 6	6000	VECETA	ITION: POPLAR'S & CONIFER TO	2 30	ELEV	400	4:00	
	ICE		•	·	ANA	LYSIS	٤.	2 2	MILE 5,C,S NUMEE
SOIL DESCRIPTION	DESCRIPTION	HL	O = WATER CONTENT	(% OF DRY WEIGHT)	1×		KEL 6	ENSI LINE	471 5 137A
RE TYPE RE TYP		0 5 5 5 5	DE CONTENT 13	LIQUE	5	8. 8.	5A		ALDER MARKED THE REAL PROPERTY OF ALL PROPERTY
	-		20 LIMIT -	LIMIT 100 100	+ %	%	% %	3 5	REMARKS
GP GRAVEL I' CREANIC F			φ						50 011%
A UF					7				504-01176
MED. FINE, SILLY SANDY		-	4		7	6 4	10 54		
					٦				
6		0			1				
					-	\$ }	55 60		•
12 COARSE SAND, BOULDERS		12		┟╼╍┼╺╾╽──╽╴╵╽╴──					HARD DRILLING
DRY & DUSTT			┝╌┫╸└──┤┄╶┤╾─╽╌╍╸		-	<u>ا</u> ا	5 82		
16		16-	· / . - - - - - - - - 	┟╾╷╴╸┥╼╌┟╴╴┥╸╌┝╴╾╾╸		Ĩ	1		
				┨╼╍╶┨╼╍ ╶ ╽╺╾ ┇╺╺┥ ╼╍╾	-				
10: D 24NO		20-	¢	┟╼╍┟╼╾┝╼╸╽╼╾┟╼╼╼╸	- 2	4 7	76		
BROWN LOOSE		•	┨──┼╾╸┝╼╾┝╼╼╽╶╍╸	<u> </u>	-				
24- VERY DAY, SILTY		24			_				
			ð .		_i /	6	72 4		NO RETURN HOLE
28		28						-	5100611116
					z	5 6	98		
32		122							
END OF HOLE	· ·				٦	·			
		2							
		~							
			•		-				
			┟╍╍┟╍╍┟╍╍┟╼╼	┫╼╾ ┥ ╾╾┟╼╍╶┟	-				
			┟──┼╾╼┟╶╼┼╸╾┤╴╴╸	┨╼┈╢╴╏╺╾╂╼╾╄╼╾╾┝╼╾╼╾	-				
			┠──┼──┼──┼──	╁╾┄┟╼╾┟╌╸┟╶╸╿	-				
	••••		┝ ╺╺┟ ──┟──┟──┼╼─						
	· · ·		<u> </u>	<u>}</u>	_				•
	I			<u> </u>	_ i		_1_	<u> </u>	



						•	- 1,					•	•									•		•									
UN	DE	RW	00	D	Mol Li	ELL	AN E	A ASS		TE	S	DRILL	нс	DLE	R	EP	OR	T			DI	ΕΡΑ	RT	MENT	OF		JBL LIE		WO GH	RKS	, CAN	ADA	
DW14	AE.		FIELD	D EN	<u>s </u>	M	DATE	DRILLED /	4/1/73	AIR	PHOT	O NO:			СН	AINA	GE:		105	0+9	90			05	FSET						TESI	HOLF	
T	<u> </u>			, 		l	ALG	AIR		506	FACE	URAINAGE:	<u> 60</u>	00			VE	GETA	TION	: Co	NIFE	RE	POP	YAR TO	0 50	ELS						T	
		.	EAY	N al	ŝ		_				DUND	ICE												•	AN	ALYS	SIZE IIS		ŀΕ	E	MILE	5,C,S	NUMBER
1251		توريع	No l	NV I	SYN I	SOIL	CES	CRIPTION			5 0	DESCRIPTION	FTH		⇒ WA	IER F CO	CON	TENT	(%) (~ OF	OF L	DRY ADIE	WE!0	5HT }	•	AY	-	9	Ę,	ISE	L'ISI	471	S	140 A
	NUN S	TY	Ĩ.	L SIS	5 E						NITS		μĔΞ			. ССС Р	LAST	1C	0.01	341	ے ے میں۔ ایال	010	LOWE		5	5	3	234	-			1	
<u> </u>			<u> </u>								52		:	ļ.,		20	LIMI	10	6	0	L [A	VIT 0	10	0 100	• %	%	%	%	ž	5	F	EMARKS	5
	Ì		Ì	- 1		GRAVEL	•				F	 				<u> .</u>							·				İ						
2	I	ł			Gw	5	Rout N	509			UF		2			1										ł							
	ļ	i		!	į									L		1	ļ								j								-
4	-				.								4														1						
		_				SHALL						· .				L.																	1
5	1	\sum											6	Ш		<u> </u>		1												Ì			i
	1	Í										:]		•						
l al	i	I			i								a									·			1			i					
				1				:					ľ	[·	\ _·	ŀ									1			1				-	
1.5	4		·	·				•	•				1				,								1			1.		1			
	÷.	\geq	ļ					•					1.0		ľ	1		1	· · ·						1		Ì		1				1
	ļ	1	i						•						1		1	1							1	ł				1			į
				_						1			. "		1.		1	1							1				ļ				
	1		•			END	OF	HOLE	·	F							- <u></u>	1							1					1			
			•						- 1				14		Ī	1									1.								
16		Į													1	1	1	1							1.							•	
										·			16	<u> </u>		1		ŀ	1								ļ						
		Ì						•							1	1-	1.	1							1					÷ .			
		ļ			·				•				13	1		1	-	1		·	†										·		
															†	1		1						,·					1				
201								-					20	†	1	†		<u>†</u>							1.		1		1				İ
		ł	· .	1				· ·	•						1	1	1	†						·	1								
224			1		-								22	1	1	+	1			<u> </u>	†			- <u> </u>	1								
	1		ł												+	1	+								-		1						
24	1]. -							-	24			+	+								-								
		i	l.	<u> </u>							i	L		1	4	. <u> </u>		<u> </u>	L	L	L	I	·			<u> </u>	1	1	L	1			

. .

•

UNDERWOOD Molecula N & ASSOCIATES DRILL HOLE REPORT DEPARTMENT OF PUBLIC WORKS, CANADA MACKENZIE And E M FRED ENG & M.M. Dire GRILLD 20/9/22 ARPHOTO NO. GRAMAGE: /0.57 * 730 GOFFET:	• •		·					••	· • • ·					•		••••		-										• • •	-		•	• • • • •	,
DERWOOD MOLEILLAN & ASSOCIATES DRILL HOLE REPORT DEPARTMENT OF PUBLIC WORKS, CANADA LIMITED DA ROLLED 20/2/2 APPROVA DO DEVANAGE 7077 00 DOT 100 AM CREEXE AND A TO THE CONTRACT OF A																																	
CD C P TECH DM Init WITER SUBJECT DAMINAGE POOR VEGETATION Status ELE TEST POLE Unit of the status Soil DESCRIPTION		W.	FIEL	DEN	 IG 8		DATE	DRILLED	2/12/72	AIRP	нот	0 NO:			CHA	NAGE		105	1+30	0			<u>N</u>	OFFS	ET	NZI	<u>e</u>	HIG	HW				-
Lite with a state of a stat	CKD D 6	Ρ	TEC	н·	DM		RIG	WATER	2	SURF	ACE	DRAINAGE:	Po	OR			VEGE	TAT	ION:	SHRU	85	\$ 6	KISS	5		ELE	V				1231		<u>.</u>
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $	EC we		DVERT	ATION	NMBOL.	s	DE DE	SCRIPTIO	N		OF GROUND	ICE DESCRIPTION	¥9	0	= WAT	ER C	ONTE	NT (% 0	F DR	Y WE	GHT	,	-			S S	ונר/	NSITY	NSITY	MILE	B,C,S	NUMBER
2 2 20 00 00 00 00 00 00 2 3 10 10 10 10 10 10 10 2 3 10 10 10 10 10 10 10 2 3 10 10 10 10 10 10 10 6 3 10 10 10 10 10 10 10 6 3 10 10 10 10 10 10 10 6 3 50 7 10 10 10 10 10 10 10 10 10 10 10 10 10 10 12 3 10 10 10 10 10 10 10 12 10 10 10 10 10 10 10 10 12 10 10 10 10 10 10 10 10 12 10 10 10 10 10 10 10 10 14 10 10 10 10 10 10 10 10	CEP (FEC SAMPL NUMBE	SAMPL	4. REC	PENETR RESISTA	UNIFIE						LIMITS FROZEN		DEP		331 =	CON	TENT ASTIC	· (% ,	OF S		LE VO	LUM	E)		CLA	sr. %	% san	C GRAN	WET DE (PCI	DRY DE (F.C.	A 11 F	EMARK	5
22 CL Strate with and sourcest F NDn 2 Costsets Auto sourcest UF 4 Costsets 4 Costsets Auto sourcest UF 4 Costsets 6 Costsets Costsets UF 6 6 Costsets Costsets UF 6 6 Costsets Costsets Costsets UF 6 Costsets Costsets Costsets Costsets 70 Costsets Costsets Costsets Costsets 71 Costsets Costsets<	1				Pt.	PEAT	- FINE	, FIBRUUS	1		-		1	<u> </u>					<u> </u>	1	80			00+									
4 CCBSLES AND BOUDLES UF 6 COBSLES AND BOUDLES UF 6 COBSLES AND BOUDLES UF 6 COBSLES DFFICULT 70 SUBLE COBSLES 10 COBSLES DFFICULT 110 COBSLES DFFICULT 112 COBSLES DFFICULT 112 COBSLES DFFICULT 113 COBSLES DFFICULT 114 COBSLES DFFICULT 115 COBSLES DFFICULT 116 COBSLES DFFICULT 118 COBSLES DFFICULT 120 COBSLES DFFICULT 121 COBSLES DFFICULT 122 COBSLES DFFICULT 124 <	2				CL	51	ASONA	L FREE	Z /N 6		۲ 	non	2									1_											
a GP						<u>CLAY</u>	08845	S AND E	BOULDER	rs	UF	•			 				<u> </u>				<u> </u>								Í		
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	4				GP							•	4	┢			+	_															
8 500 FT, CLAYEY 8	6					GRA	VEL)			•	6									1									••		
8 5#4416 10 5#4416 10 10 12 6.8EY 14 14 16 10 18 10 20 10 22 10 22 10 24 10					GC		SOFT,	CLAY	Έy					<u> </u>									<u> </u>									-	-
10 12 12 14 16 18 18 18 18 18 18 10 10 10 10 12 14 14 16 16 18 18 18 18 18 18 18 18 18 18	8					5HI	ALE	:					8	 .		-				1		+									DIFFIC	MINE	FROZEN
12 GREY 12 14 14 14 14 14 14 14 14 14 16								•					10																		SOIL	WITH	WATER
12 GREY 12 14 16 16 16 18 10 10 20 20 10 22 10 10 22 10 10 24 10 10	-					-						••																		••	E DRI	LLING	WOD
14 14 14 16 16 18 20 20 20 22 22 24 24	12					-	6	REY					12									+											
16 16 16 18 18 20 20 20 20 21 20 22 20 22 20 24 24	14												14																.				
16 16 16 16 18 20 20 16 20 20 16 21 16 16 22 16 16 22 16 16 22 16 16 22 16 16 22 16 16 22 16 16 22 16 16 22 16 16 22 16 16 22 16 16 22 16 16 22 16 16 24 16 16								·	••	- 1																							•
	:6						- y			•			16					-+			_		 .								. ·	•	
20 22 22 24 END OF HOLE							•					•	18										-								Ι.		
20 22 24 END OF HOLE		ļ							•	.																							
22 24 END OF HOLE	20	ŀ						•					20						. <u>.</u>				 				1						
						. -								<u> </u>								-											
24 END OF HOLE	22												22																			•	
	24			[E	ND OF	- HOLE		4			24																				
	<u>t</u>	<u> </u>		<u>t</u>	· · ·	l					L	I	 I	- <u>-</u>		لــــــــــــــــــــــــــــــــــــ	l	<u>}</u>	-	!			 ,		1 i	ا ۱	ـــــــــــــــــــــــــــــــــــــ	i	<u> </u>	ا ن	J		

· · · · ·

											•			· ·		•					:								
	DE	RW	00	D	McI Ll		AN & ASSO D	CIATE	S	DRILL	но	LE	REP	ORI	Γ.		[DEPA	RT		OF CKE	PU NZ	BLI IE	C V HIC	NOR Shv	(KS IAY	, CAN	IADA .	
Wite /	A E	W a	FIEL	DE	NG: (3. AA.	DATE DRILLED /	12/72 AIR	PHOT	O NO:	```	c	HAINA	GE:	10	52+	70			OFF	SET		4	J			TES	T HOLE	E
	T		120	H:	ГĨ	<u>^</u>	HIG WATER	501	ACE	DRAINAGE		l ·		IVEG	ETA		GKHS	5 8	SA	RUBS	GRA	IN- S	V. 12E					1	1
E	ac H		COVERY	RATION	IED SYUBOL	SOIL	DESCRIPTION	•	OF CROUN	ICE DESCRIPTION	PTH ET)	0=v	VATER			(% 0I	F DRY	WEN	GHT)	•	ANA A	LYSI	S Az	VEL	ENSITY F)	ENSITY F)	471	S	34B
1)	NON	4MP	%. RE	PENET	VNIF				LIMITS FROZE		33		20	LASTI	°		1 ^L	19010 LIMIT	101112	, 1004	ರ %	- 	87 %	24 C 14	WET D	DRY D		REMARK	S
T	Ī				Pt	PEAT	ORGANIC		F	нç			Ť.			Ť		1	l ·]										
	Į					GRAVE	<u>= L</u>		UF																	l			
	N	\setminus										·]					1	ļ		
	•	Λ			GP		SMALL			· ·	4	·]·						_											
-	- 1	Y														·					4			1					
ł		\·					•			· ·	6	┟──┦-	_				_	- - -·			{			•			DIFFIC	ULT	TO
						CLAY	·		{											<u> </u>	-						DETER	IMINE I	FROZE
İ	F	-1									8		<u>.</u> -						$\left - \right $		1			[SOIL	WITH	WHIEL
					CH	. 5	SOME GRAVE	2												4	1			·			S Dec		11.0.12
1											10	├ ──		-							1					·			
											12										1								
						SHALL																							
					· .						14												Ì		•				
				ĺ																	4	ľ	ŀ.					•	•
	ļ	·					GREY	· .			16	├	_ _								-			•		1			
		·					•											_		<u></u>	ł					£ -			
							•				18	╁╾╌┼╴			·				+		1	Ì					•	1	
																				·····								-	
1											20	┇									1]						
						•				l .	0.00		_					1			1								
	-				-						**]			ľ				:	
						END	OF HOLE D	35'	1		24	 															•		
1					<u> </u>					L																ŀ			

UND	ER	NOC	DD	Mc LI	LELLAN & ASSOCIATE MITED	S	DRILL	но	LE	R	EP(DRT	•		D	EPA	RT	MENT	OF CKE	PU NZI	BLI IE	C V HIG	VOR	KS	, CAN	ADA	
OWN: A	EN	FIE	LO E	NG A	B.M DATE DRILLED 30/11/72 AIR	PHOT	0 NO:	00	0.0	СНА	INAG	E:	10.	53 +00	0			OFF	SET:			<u> </u>			TEST	HOLE	
	1	1120	.н: 			OFACE	URAINAGE:	1				VEG	EIA	HON: 6	RHSS	5 5	5/11	(035	GRA	ELE	V: 17 F	67	68				
		E A	N N	BOL	•	NNO.	ICE			- 11/4 7			-	/0/ or		na 🗁 i a		•	ANA	LYSI	S		1	7	MILE	8,0,5	NUMBER
1.			TANT	SYN	SOIL DESCRIPTION	6 G 1 G	DESCRIPTION	EETH		= WAI ≑ ICE	CON	TEN	eni t (%	OF SA	MPLI	E VO	LUME)	A	5	Q N	AVEL	ENS (L	ENS F	471	S	338
C L M	SAM		CNE1	E E		NIT 5		25			PL	AST	۰		L	QUID		• •	5	15	SA	8 5	50	2			ionen en la la la la la la la la la la la la la
	+		• ¤	4ª		32		·	ļ	2	<u>م</u>	40	<u></u>	<u>60</u>	· .	1011 80	10	+ 001 0	%	%	%	%	3	•	H	20483	
1	Ļ		Ì	Pt	MUSKEG GRANULAR								·			ļ											
2		4		CL	CLAY SILTY		Nbn	2						·	1_	<u> </u>											
				Ŭ_	SEASONAL FROST			1 -								<u> </u>	1					·					
	• [GRAVEL	UF				· ·												•					
		4		GP	FREE WATER @ 1'		-																		DRILLIN	16 WI	гн
	1				ROCKS,																				ROCK	817, W	ATER
					· · ·]			0											1	••					६ ७२॥	LING I	NUD
					CLAY	1									-i	•			1								
•								6.							Ť	1			1							•	
				CL	SOFT SHALE LAYERS		. <i>.</i>								-	+		······································	1			•			•		
10					GACY .			10	†						+				1							•	
							• ·	1							-												
124		-1 -1			SHALE			12	<u> </u>		e				+-										•		
	T	1.		10	SOFT, LAYERED												┼──┤	<u></u>									
14				6	FISSILE			14									<u> </u>		-	i	ŀ		-				
	Ż	- K-			CHAIF .	1			<u>}</u>		<u> </u>	┝─┤					┼╌┤								•	, •	
16	-	¥			<u>Struct</u>			16	╂										-								
	-	-		GP	GREY-BLUE , HARD						[$\left - \right $		-							· · · ·	
18	$ \rangle$			Ŭ.	LAYFRED			18	<u></u>				·	·			$\left - \right $	•	-						•		
	F	4							 	ļ	 				_			 			1					•	
30						4		30.	_	 	 	$\left - \right $		<u> </u>					-		.						
		1.			SHALE	.		l				 			. 			•	4								-
35	·	Ч – <u>Г</u>		GP	SOME GRAVEL			35	 		ļ						1		4							•	
					GRANICE PEBBLES	Į			L	ļ					·				1	ł						•	
20		7			BCULDEKS]		140	L												1	1			•		
			<u> </u>	ŀ	END OF HOLE	<u> </u>	· · · · ·		 		<u> </u>										<u> </u>			ŀ			· · · · · · · · · · · · · · · · · · ·
1 :	'n	1	ł	•		I		1	i	1	1			1	ļ	1			1	l	t	ŧ.	-	1			

PLATE II



PLATE 12

UNDERWOOD MeLE	LLAN & ASSOCIATES	s		 H0) F		 	Т.			DE	PAR	TME	NT	OF	PU	BLI	<u>Ç</u> y	VOR	KS	, CAN	ADA	
LIM	HITED M. DATE DRILLED 30/11/72 AIRP RIG A/R SUBF	HOT		500		СНАН	NAGE:	FGET	055	+00 : SPA	WCF	E BIR	CH T	MAC OFF	SET:			97.	77 77	- AY	TEST	HOLE	
		SOUND	ICE			- 11/475		A'TENT				VEIGHT			GRAI	N- S	IZE		117	11 Y	MILE	8,0,5	NUMBER
DI PITH (FELT) SAMPLT SAMPLE SAMPLE SAMPLE TYPE A FECOVI A FECOVI COL SYM	SOIL DESCRIPTION	MITS O	LESCRIPTION	DEPTH		= ICE	CONTI		% OF	SAM	PLE	VOLUI	ME)		CLAY	SILT	SAND	GHAVEI	(PCF)	RY DENS	47/	5 EMARKS	328
	TONES	52 F	NŞ		<u> </u>	20		40 		o	80		100	100+	%	%	%	%	5				
	BROWN, LARGE GRAVEL JERY DRY		Nbn	2	F											•	11	82					
ë GP	SOME SAND		Nf	6																	41%	COAR	SE
8 10 SN GN	RAVEL SMALL, SANDY, SOME BROWN CLAY		Nbn .	8	}- - }- }- }-									· · · · · · · · ·	T	7	35	48		••	FRACTO	ON C. 6 DAIL	RUSH ED LIMG
12	ARAVEL			12							•												
14 16	Серубу		Nţ	•16	, •		· · · ·												-				•
18-			•	18	, , ,																•		
20	END OF HOLE			20	2					<u>↓</u>													
24				24	\$					·													
		1	1		1							t	1		1	ļ	i	i	1	1	1		

. .

PLATE IJ

.



PLATE 14

UN	DE	RW	100	D	Mici	LELL	AN & ASSOCIATE	S	DRILL	НО		E REF	ORT		DE	PARTI	MENT	OF CKE	PUI NZ!	BLIC	C W HIG	IORI HW/	۲ ۹۲	, CANA	DA	
DWN	A.E	W	FIEL	DE	NG: 7	55.	DATE DRILLED: 26/11/12 AIR	PHOT	0 NO:			CHAINA	GE: /0	58 +00	,		OFF	SET	:	Ē,			Ĩ	TEST	HOLE	
CKD.	05	Р	TEC	H÷	D.M		RIG: AIR SUF	RFACE	DRAINAGE:	WES.	7	4 %	VEGETA	TION: e	CONIF	ER ZO	<u>, </u>		ELE	1:	107	31				
			2	2	đ			OND N	ICE	-								GRA	IN- SI LYSI:	IZE. S		2	2	MILE	B,C,S	NUMPER
EE			046	ANCE	YN8	SOIL	DESCRIPTION	OF GRO	DESCRIPTION	E	9) = WATER	CONTENT	(% OF	DRY 1	WEIGHT)	,	۸		9	KEL.	ENSI	22	471	С	51A
35	AMP UMB	AMPL	¥.	NE T F	1 - 2 - 1			ITS DZEH		E E	۲		PLASTIC	OUF SA	1101	ND	1	5	š	A S	GR4					AMOUNT
	n z		*	μ Π Π Π Π	20			L IM				20	LIMIT	60		11T 2 10	0 100+	%	%	%	%	3	<u> </u>	R	EMARKS	
					D,	PEAT		F	Nbn			•				·										
					ht i	0	REANIC, GRANULAR										o									ļ
		\sum]			CLAY	/]									·		·	-						
														· .					i i							
*		\sum_{i}				L	GHT BROWN, SILTY					$\boldsymbol{\mathcal{A}}$														
		\square				бем	E ROCKS & COBBLES,					1/							·					BACH 1	ONS#E.	0 BV
"			1			HA	AD			l °	Γ	1												DRILL	811	
																	· · · · · ·]	·							
- E	ļ		İ	ł		GRAV	EL	1			Γ	1														
		${ } $					••••• .		ł	. -	П															
			1			_			-	10								1						DIFFIC	ULT D	VILING
	i	1				F	NE, SOME ROCKS				Π			1				1							- •	
121		\geq				50/	ME CLAY		· ·	12	†٩	1-1-					>	1								
					GC						F							1	·							
14										14	+							1.			10				•	
		$\overline{}$								Ϊ.					-			1 /	0	22	60					
16		<u> </u>	ľ				·			16	t				-			1								
																		1								
18										18	ا			1	-			1								
		K	1	1	-	<	I F	1			+	- 		+				1								
20		┢──	4		1		- f.			20	+	¶						1								
		ļ					GREV					· -					•	1								
22				1			0.001	1	1	22	2 - -	╅┼╼╀╸		┤──┼─				1								-
											\vdash	┼┼━╌┼╍						1	ľ							
24		F	-			ENA	or was a 2-1		-	24	+	╋			<u></u>			-			1					
L <u>3</u> ¢]		1-	÷ <u>i</u>	. <u> </u>	┥┿	1 140	UP MOLE (S' 50		. I	- <u> </u>		<u>جال</u> غ	L	<u> </u> - 		۱ <u></u>		- I	 	<u></u> -	! !	┟───┟		L		

é

UN	IDE	RW	voc	DD	Мс	LELL	AN (8 AS	SOCI	ATES	S	DRILL	НС	LE	R	EPC	DRT			•	DEF	PAR	TME	NT	OF	PU	BLI	C V	VOF	KS	, CAN	ADA	7
DAN	1 5	14/	FIE	0.5	الط		DATE	000 1 51	2 reliet	1 4100		0.110			1			Į					j	MAC	CKE	<u>NZ</u>	E	HIC	<u>SHN</u>	<u>AY</u>			
CKD	DG	P	TEC	<u>н:</u>	D /	0.7VI IA	BIG:	AIR	5. 26/11/12		ACE	DRAINAGE	<u> </u>		СНА	INAG	E	//	074	+ 00) 		- 05.1	OFF	SET		<u>k.</u>				TEST	HOLE	1
		<u> </u>		<u> </u>	Ѓ́			,,,,,		130,11	200	Unamede.	100	<u> </u>		ļ	VEG	L FA		577	OCE	G H	SPEN	/0	35	ELE	/:		r				<u> </u>
			À.	ă.	ត្ត						ž	ICE													ANA	IN-S	X۲۵ S		-	>	MILE	8,C,S	NUMPER
E L	25	50	ō	ANO	E O	SOIL	. DES	SCRIPTIC	ON		0 8	DESCRIPTION	EG	0	= WA1	TER C	ONTE	NT ((% 0	FD	RY W	EIGHT	1		~	_	0	ಫ	in c	NSI .	170	<u> </u>	718
οž	AN I	AVP	R.	NET SIST	ц. 1. 1. 1.				· ·		SEN ZEN	·	95	0	= ICE	CON	TENT	(%	OF	SAMF	LE V	/OLUN	4E)		L A	5	SAŀ.	RAV	20	20	470		260
	ΨZ	~	*	2 8	چ ر						38					рц а Ц	ASTIC	 			LIQUID	2			%	0/2	9/_	0/_	ET L	Yes -	R	EMARKS	j
			1	1	51	PEHT	6.00		in the second	<u> </u>	-				<u> </u>	ř-T			- 60				100	100+		~		10	-				
			. .			CIAL	044	- CLAR	, 10 5 1			Nbn		<u> </u>				-+					-	<u> </u>									
2		\leftarrow	-			CLWY							2					<u>_</u>															ľ
		\vdash	ł		Cr.	BRO	wn,	SCM	E S/LÏ	r				L			Ľ								1		•						
4	1	1	1			Roc	KS.	C088(ES AN	0									-														
						Bo	ULDE	FR S														_	1			:				ļ			[
																														·			
°		$\overline{\nabla}$	1	Į		SAND						• .	6.	f				-+															·
		$ \setminus$	ł	ŀ									1	┝─┼	Ì			-+															
8		 	1			_							6					_										•					
		\vdash	{			50/	NE	GRAV	E L			:						_			•					·							
10		\square		ļļ	crl	CLA	iy Fi	NE S			F	NÊ .	<u>م</u>			i									1	8	58	24	•				
]		36						·			Π																. •			
	Ì	∇						•						P				-+															1
-12-		$\left \cdot \right\rangle$	1										12	┝᠆┼╴				-+													-		ļ
			t														<u> </u>						- <u> </u>		(
14		\leftarrow											14													'							
																				_		_		į								•	
16					ļ						Ì		<u>ا</u> م ا													.					• •		
					1	END	OF	HOL	E	4 I	İ		10-							1													
									. i	/												-								1			
18										1			18-								╾╂╍												
															[]								·										ł
20													20-					_													•.		
	·								·														{								-		1
22					_								2.2															·					1
													~~										1.										.
										·								-+		-†-													
24	·										· [24-					+-															· .
 ł	ļ	╘╼╼┦	L	<u> </u>				·····		┉┈╎	╾┞		 !	L				 .	<u> </u>]

. .

PLATE 16

÷.

W.S.	HI	F	ELD	L ENG	IMI E n		D ATE I		D: 14	1 73	AIRPH	HOT	O NO:	HC ,		R CH/			Г. 10 2	5+	00		FA	FX E IV	MA	CKE FSET	<u>NZ</u>		HIC		AY	, CAP		-	
KD.	<u>レネ.</u> T	; TI	ECH		<u>2.m</u>	R	lG:	A	1R		SURFA	ACE	DRAINAGE:	00	d			VEC	ETA	TION	Spr	ي د ي	, ci	•(1 •	w1,05L	cr. 20	ELE	V				TES	т но:	.E	
			R	. 3								NN	ICE	·						•						GR/	AIN+ S	SIZE		-	7	MILE	B,C,S	i NL	UMB
(FEFT)	AMPLE	TYPE	NETRATI	NIFIED		IOIL	DES	CRIPT	ION		TS OF	ZEN GR	DESCRIPTION	DEPTH (FEET)	0	= WA' = ICE	CON	CONT	ENT T (%	(% () OF	OF D	RY W Ple	VEIG	HT) UME)		CLAY	SILT	ONVS	GRAVEL	DENSIT	DENSIT	471	В	2	30
	2 0	*	2	ž _ S							. W	F RO					20.	LIMIT	°⊢ ∘	60	,	1 LIQUA 1 LIMA 80	T	100	100	1%	%	%	%	E S	087	-	REMAR	ĸs	
2				cı	CL dry per	AY -	List bi II b otic	ande onde	MUS d,d	KEG Ilfyi ump	<i>۲</i> ، ا		no Oisible Ice Va	2		9					-														
	·				well	. Ь. m	ən ài . '	و ب	e. t.	ot o			excess ice barely visible os random Crystale	6				}					- ' "							1:4.4	23-8	•	•	· ,	•
	F			c L	CLA per	y, u ette	vell 1418	bon n P	ded,	•			5-10% fair amount of exercis	5 10		· · · · · ·														116-2	9 3 -2				
· · · · · · · · · · · · · · · · · · ·					CLA	<u>¥</u> , s	ame	50.	nd, u	ve 11	•		Vn Ice lenses of	12												-					-	•			
					be.	ND	OF	НО	LE -	4			1/4" @oout 21"	16 ·																		This	hole	nia	ئ
						•							· . :	18 20-																		ic a	10: 12	47.4	
								•						22																					
								•	•••				••	24																					

PLATE	17
-------	----



UNDERWOOD MALELLAN & ASSOCIAT	Fe T				DEDADTMENT OF		0.5.40	
LIMITED	LS	DRILL	HO	LE REPORT	DEPARTMENT OF MACKI	PUBLIC W	IORKS. HWAY	, CANADA
DATE DRILLED ING P. M DATE DRILLED 14/1/73 /	AIRPHOTO	NO:	<u> </u>	CHAINAGE: 102	5 + 0 0 OFFSET	500'E ¢	_	TEST HOLE
CAD V TECH (VIN) RIG AIR.	SURFACE I	DRAINAGE: 9	ood	VEGETA	TION: Spruge, willow, aspen 20	ELEV		
NUMUER SAMPLE SAMPLE SAMPLE SOIL SYMUCE NUMIFIED SOIL SYMUCL SOIL SYMUCL	LIMITS OF FROZEN GROUND	ICE DESCRIPTION	DEPTH (Feet)	O = WATER CONTENT	(% OF DRY WEIGHT)	AIN-SIZE ALYSIS	WET DENSITY (PCF) DQY DENSITY (PCF)	MILE B,C,S NUMBER 471 B 2322 REMARKS
2 P CL CLAY Sondy, silly, brown Well bonded, penetration hard. 4. CLAY silly well bound	Fn	ice visible	2					
6 8 8 CL Lrown, Ciumpy, penetrati firm. Vr	- n - n	ice	6- 8-		· · · · · · · · · · · · · · · · · · ·		97.0 83.4	•
10 P CL well bonded, Sniooth Penciestian, firm.	۲ م تر	andon itystals; ust uisible .	10- 12-				107.5 83-5	
14. P CL Penetration, firm. 16. END OF HOLE	T S	andom rystals - mall amoust	14 _16				08-5 B6.A	
18 20		·	18- 20-					
22			22- 24-					•
· · · · i l			1			i i i i	ı i F	PLATE 19









